### NON-METALLIC • NON-CONDUCTIVE







Prevents Air Infiltration in New Construction

Vapor Boxes for Fans, Fixtures, Devices



# SCREW-ON Vapor Boxes for Fixtures, Devices NEW!

Arlington's non-metallic ONE-BOX™ fan, fixture and device boxes feature built-in flanges with gaskets attached that form a protective barrier against air infiltration, enabling installers to meet local codes where required.

Fast, easy, secure installation in new construction, our vapor boxes mount to wood or steel joists with nails or screws that ship captive.

ONE-BOX Vapor Boxes for Fixtures, Fans and Devices...


- · Non-metallic, non-conductive
- For fixtures (round), fan or fixture (bar hanger) and devices (single and multiple gangs)
- No loose parts ships with mounting screws or captive nails (on facing page) and installed NM cable connectors with gaskets attached
- For new construction with single or double drywall
- UL/CSA Listed

Patented. Other patents pending



### All Available with Ground Clip for Canada

## NM Cable Connectors with Gasket material already INSTALLED





### for Devices



F101F Single-gang



F102F Two-gang



F103F Three-gang



### Screw-on Single Drywall

Catalog Number	UPC/DEI/NAEI Mfg. #018997	O Vapor Box Size/Use	Cubic Inches	Unit/Std Pkg
F426F	06903	Round for fixtures	28.0	20
F101F	12520 S	ngle-gang for devices	22.0	25
F102F	06900	Two-gang for devices	42.0	10
F103F	06901 T	hree-gang for devices	59.0	10
F104F	06902 F	our-gang for devices	81.0	10

#### Screw-on with Ground Clip for use in Canada (GC suffix)

	JPC/DEI/NA Mfg. #01899		Cubic Inches	Unit/Std Pkg
F426FGC	06909	Round for fixtures	28.0	20
F101FGC	06905	Single-gang for devices	22.0	25
F102FGC	06906	Two-gang for devices	42.0	10
F103FGC	06907	Three-gang for devices	59.0	10
F104FGC	06908	Four-gang for devices	81.0	10

Includes Robertson head screws

## NAIL-ON Vapor Boxes for Fixtures, Devices



FN430F ships ready to install a FIXTURE on ceilings with Single Drywall







### Nail-on Single Drywall

Catalog Number	UPC/DEI/NAE Mfg. #018997		Cubic Inches	Unit/Std Pkg
FN430F	15100	Round for fixtures	30.5	20
FN101F	15130	Single-gang for devices	23.0	20
FN102F	15132	Two-gang for devices	43.5	10
FN103F	15134	Three-gang for devices	63.5	10
FN104F	15136	Four-gang for devices	85.3	10



### Voltage Separator Divides power/low voltage in box

Catalog Number	UPC/DEI/NAEI Mfg. #018997		Unit/Std Pkg
F102D		Divides power/low voltage in these boxes installed w/ single	
Two, thre	e, four-gang scr	ew-on F102F, F103F, F104F (an	d GC styles)
Ţ		ang nail-on FN102F, FN103F, F	

### Nail-on with Ground Clip for use in Canada (GC suffix)

Catalog UP Number M	C/DEI/NAE		Cubic Inches	Unit/Std Pkg
FN430FGC	15101	Round for fixtures	30.5	20
FN101FGC	15138	Single-gang for devices	23.0	20
FN102FGC	15140	Two-gang for devices	43.5	10
FN103FGC	15142	Three-gang for devices	63.5	10
FN104FGC	15144	Four-gang for devices	85.3	10

Includes Robertson head screws



### **Ground Clip for use in Canada**



Ground clip

## NAIL-ON Vapor Boxes for Fixtures, Devices



### Nail-on Double Drywall

	JPC/DEI/NAE Mfg. #018997		Cubic Inches	Unit/Std Pkg
FN440F	15120	Round for fixtures	39.5	20
FN101FD	15131	Single-gang for devices	28.0	20
FN102FD	15133	Two-gang for devices	53.0	10
FN103FD	15135	Three-gang for devices	77.8	10
FN104FD	15137	Four-gang for devices	103.5	10

### Nail-on with Ground Clip for use in Canada (GC suffix)

	PC/DEI/N/ Nfg. #0189		Cubic Inches	Unit/Std Pkg
FN440FGC	15121	Round for fixtures	39.5	20
FN101FDGC	15139	Single-gang for devices	28.0	20
FN102FDGC	15141	Two-gang for devices	53.0	10
FN103FDGC	15143	Three-gang for devices	77.8	10
FN104FDGC	15145	Four-gang for devices	103.5	10

Includes Robertson head grounding screws



For added convenience, these nail-on boxes ship with the nails captive





Made in USA

## Side Mount • SCREW-ON Vapor Boxes for Fans/Fixtures



Our economical L-shaped fan/fixture boxes mount securely to joist with a shipped-in-place center screw.


- · Styles for single or double drywall
- · Vapor barrier in box prevents air infiltration through ceiling or building envelope
- NM Cable Connectors and flange with Gasket material already INSTALLED
- · Fan/fixture bracket installation screws ship captive
- · UL Ratings: 70 lb fan/200 lb fixture CSA: 50 lb fan or fixture



















### **Press on Fan/Fixture Box**

#### Versatile, non-conductive box for new construction



FB426F



FB426F (back shown)

#### **Features and Benefits**

- · Flange with gasket attached forms a protective barrier against air infiltration
- NM Cable Connectors and flange with Gasket material already INSTALLED
- · Includes captive installation screws for fan/fixture bracket
- · Gripping tangs press-hold to the joist while you reach for your screwdriver
- · UL rated: 70 lb. fan, 200 lb. fixture; CSA rated: 50 lb. fan/fixture

	UPC/DEI/NAED Mfg. #018997	Description /Style	Unit/Std Pkg
FB426F	12521	For 1/2" or 5/8" Drywall 16.0 Cu. In.	25
Patented	. Other patents pendi	ng	

	UPC/DEI/NAED Mfg. #018997	Vapor Box Size/Use	Cubic Inches	Unit/Std Pkg
FB442F	76220	Joist Mount	15.5	25
FB443F	76222	Fan or Fixture	18.8	25

## Screw-on

Catalog UP Number M	C/DEI/NAED lfg. #018997	Vapor Box Size/Use	Cubic Inches	Unit/Std Pkg
FB442FD	76221	Joist Mount	25.0	25
FB443FD	76223	Fan or Fixture	28.5	25

Add suffix "GC" to catalog number when ordering for use in Canada, i.e. FB442FGC, FB442FDGC.







### For New Construction Plastic Vapor Box with Adjustable Steel Bracket for Fans/Fixtures

Arlington's heavy-duty, non-metallic fan/fixture boxes feature

adjustable



that fit joists spaced 16" to 24" o.c.




Just like our vapor boxes for fixtures and devices, these fan/fixture boxes have built-in flanges with gaskets installed that form a protective barrier against air infiltration, so installers can meet residential codes where required.

Best of all, they deliver flush ceiling installations!

Fast, secure installation in new construction, our fan/fixture vapor boxes mount to wood joists with supplied screws.

FBR415F ships ready to install on SINGLE drywall; FBR425F is for DOUBLE drywall.





FBR415F



FBR425F

- · Position box anywhere along bracket
- · Captive fan/fixture bracket installation screws, mud cover, installed NM cable connector, and all gasket material
- cULus Listed





### Arlington

1 Stauffer Industrial Park Scranton, PA 18517 800/233.4717

Fax 570/562.0646

www.aifittings.com ©2011 Arlington Industries, Inc.

REV1213/25M



Installation cutaway (single drywall shown)




FBR415F, FBR425F...for New Construction



Nail 'tooth' to joist to hold bracket in place temporarily.



2 Use supplied screws to secure bracket to joists.



Inside FBR415F box



Loosen box screw (provided). Slide box along bracket to position box between joists.

**UL Fixture Rated** 

Canadian Std. Rated

50# Fan/Fixture 16"-24" o.c.

90# at 24" o.c. 150# at 16" o.c.



4 Tighten box screw to lock box in position.



5 Remove captive installation screws to install fan/fixture mounting bracket (drywall installation not shown).

NM Cable Connectors with **Gasket material already** 

**INSTALLED** 

Catalog Number	UPC/DEI/NAED Mfg. #018997	Fan/Fixture Vapor Box Plastic box, adjustable steel bracket	Cubic Inches	Unit/Std Pkg
FBR415F	72204	for single drywall ceilings	18.3	5
FBR425F	72205	for double drywall ceilings	27.3	5

Distributed by

**UL Fan Rated** 70# at 24" o.c. 110# at 16" o.c.