



990

16/2 Solid Unshielded FPLR
Fire Alarm Signaling

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	16
• Conductor Stranding	Solid
• Conductor Type	Bare Copper
• Nominal DCR	4.1 Ohm/1000ft
• Cabling Lay Length	2.75 in
• Twists/Foot	4.4 twist/ft
INSULATION PARAMETER	-
• Insulation Type	Polypropylene - PP
• Insulation Thickness	0.008 in
• Insulation Color Code	1. Black 2.Red
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	23 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.022 in
Nominal Cable O.D.	0.168 in
Plenum	No
NEC UL Rating	FPLR
RoHS Compliant	Yes
Pull Tension	62 lbs
Bend Radius	1.512 in
Cable Weight	25 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1666 Vertical Shaft
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



990

16/2 Solid Unshielded FPLR
Fire Alarm Signaling

Related Products

RELATED PRODUCTS	
Plenum Number	60991B
Aquaseal Number	AQC225
Aquaseal Direct Burial Number	AQ225