



841

RG6/U BC Type CATV Dual Shield
CATV/MATV DBS

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	1
• AWG Size	18
• Conductor Stranding	Solid
• Conductor Type	Bare copper
• Nominal DCR	6.5 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Foam Polyethylene
• Insulation Thickness	0.18 in
SHIELDING PARAMETER	-
• Shield Type	Overall 100% Aluminum Foil
• Shield Type 2	Aluminum Braid
ELECTRICAL CHARACTERISTICS	-
• Nominal Impedance	75 Ohm
• Nom. Cap. Between Conductors	16.2 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.026 in
Nominal Cable O.D.	0.265 in
Plenum	No
NEC UL Rating	CATV, CM
RoHS Compliant	Yes
Pull Tension	70 lbs
Bend Radius	2.65 in
Cable Weight	32 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
Nominal Velocity of Propagation (VP)	82 %
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



841

RG6/U BC Type CATV Dual Shield
CATV/MATV DBS

Attenuation

FREQUENCY (MHz)	ATTENUATION (db/100ft)
5 MHz	0.57 dB
55 MHz	1.45 dB
100 MHz	1.85 dB
270 MHz	3.07 dB
400 MHz	3.85 dB
540 MHz	4.6 dB
750 MHz	5.4 dB
1000 MHz	6.3 dB
1450 MHz	8.05 dB
2250 MHz	9.99 dB
3000 MHz	11.9 dB

Related Products

RELATED PRODUCTS	
Plenum Number	25841
Aquaseal Number	AQC841
“F” Type Crimp	CN-F56ALM
“F” Type Compression	CN-F6MCV