



Product: 6120UJ ☑

Fire Alarm, #14-2c BC, FPLP

Product Description

Fire Alarm Cable, Plenum-FPLP, 2-14 AWG solid bare copper conductors with FEP insulation, Flamarrest® jacket with ripcord

Technical Specifications

Product Overview

		Suitable Applications:	Fire Alarm, Addressable Systems, Circuits: Audio, Control, Initiating, Notification
--	--	------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
14	Solid	BC - Bare Copper	2
Condu	ctor Count:		2

Insulation

Material	Material Trade Name	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	Teflon®	0.007 in

Color Chart

Number	Color
1	Black
2	Red

Outer Shield Material



Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	Flamarrest®	0.186 in	0.015 in

Construction and Dimensions

Cabling



Electrical Characteristics

Conductor DCR



Capacitance

Nom. Capacitance Conductor to Conductor
26 pF/ft

Inductance

Nominal Inductance 0.15 µH/ft

Current

Max. Recommended Current [A] 8 Amps per Conductor at 25°C

Voltage

UL Voltage Rating 300 V RMS

Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	0°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	33 lbs/1000ft
Max. Pull Tension:	100 lbs
Min Bend Radius/Minor Axis:	1.9 in

Standards

NEC Articles:	Article 760	
NEC/(UL) Compliance:	FPLP	
Other Compliance:	California State Fire Marshall	

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT6	
UL Flammability:	NFPA 262 Plenum Flame Test (UL910)	
UL voltage rating:	300 V RMS	

Plenum/Non-Plenum

Plenum (Y/N):	Yes	

Part Number

Variants

Item #	Color	UPC
6120UJ 0021000	Red	612825173694

Product Notes

Notes:	Teflon® is a trademark of DuPont.

History

Opuate and Nevision. Nevision Number: 0.225 Nevision Date: 00-24-2020		Update and Revision:	Revision Number: 0.223 Revision Date: 06-24-2020
---	--	----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.