



240

22/4 Solid Unshielded CMR
Audio and Control

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	4
• AWG Size	22
• Conductor Stranding	Solid
• Conductor Type	Bare copper
• Nominal DCR	17.5 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Thermoplastic
• Insulation Thickness	0.007 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.017 in
Nominal Cable O.D.	0.134 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Pull Tension	34 lbs
Bend Radius	1.206 in
Cable Weight	18 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1666 Vertical Shaft
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



240

22/4 Solid Unshielded CMR
Audio and Control

Related Products

RELATED PRODUCTS	-
Plenum Number	25240B
Aquaseal Number	AQC240