

TAA SmartPro 120V 1kVA 800W Line-Interactive Sine Wave UPS, 1U, Network Card Options, USB, 6 Outlets

MODEL NUMBER: **SM1000RM1UTAA**



Protects connected mission-critical equipment against damage, downtime and data loss due to blackouts, brownouts, power surges and line noise. Ideal solution for servers, storage devices and telecom hardware.

Description

The SM1000RM1UTAA SmartPro 120V 1kVA 800W Line-Interactive Sine Wave UPS provides battery backup and AC power protection against blackouts, brownouts, power surges and line noise that can damage electronics or destroy data. Ideal for backing up servers and network storage devices, the SM1000RM1UTAA switches to battery mode in milliseconds to keep your connected equipment running long enough to save files and shut down safely with no data loss.

Two of the six NEMA 5-15R outlets may be switched off remotely to reboot equipment or shed nonessential loads to maximize battery backup time for mission-critical equipment. The internal battery provides 14 minutes of support at half load (400W) and four minutes at full load (800W). Operating with a high 99% line mode efficiency, the SM1000RM1UTAA saves you energy and operating costs.

Automatic voltage regulation (AVR) maintains 120V nominal output over an input range of 83V to 147V without using battery power. EMI/RFI noise filtering improves your equipment's performance and prevents damage. 450-joule AC surge suppression protects your equipment from harmful power surges. With Tripp Lite's PowerAlert® software, available via free download, the SM1000RM1UTAA enables safe unattended system shutdown and file saves in case of a prolonged power failure. Compatible with Tripp Lite UPS management card options, including WEBCARDLX.

Features

Protects Mission-Critical Rack-Mounted Equipment Provides fully regulated sine wave AC output for servers, network storage devices and telecom hardware
Audible alarm signals loss of utility power, overload and low battery
6 NEMA 5-15R outlets
10 ft. power cord with 120V NEMA 5-15P input
450-joule surge suppression rating

Reliable Battery Backup Supports half load up to 14 min. and full load up to 4 min.
Internal batteries designed for hot-swap field replacement

Switchable Outlets 2 load banks, each with one outlet controllable remotely to reboot equipment or shed nonessential loads

Automatic Voltage Regulation (AVR) Maintains 120V nominal output over input range of 83V–147V without using battery power

Highlights

- Corrects under- and overvoltages from 83V to 147V
- 6 NEMA 5-15R outlets—2 switchable via network interface
- Network power management and control capability
- 99% efficiency rating saves energy and operating cost
- 14 min. runtime at half load; 4 min. at full load
- To use the Auto Probe feature, this product requires a WEBCARDLX network interface (sold separately) running LX firmware update 15.5.2 or later

Package Includes

- SM1000RM1UTAA SmartPro 120V 1kVA 800W Line-Interactive Sine Wave UPS
- USB cable
- DB9 cable
- EPO cable
- Mounting hardware
- Owner's manual



EM/RFI Line Noise Filtering Removes electromagnetic and radio frequency interference that can disrupt or damage equipment's performance

High Efficiency Operation 99% line mode efficiency saves money and energy and protects the environment

LED Indicators Front-panel LEDs signal power, voltage correction, load level and battery charge state

Optional Network Management Cards Compatible with Tripp Lite UPS management cards, such as WEBCARDLX

Communications Ports USB and DB9 ports enable data-saving unattended shutdown when used with Tripp Lite's PowerAlert software, available via FREE download from www.tripplite.com/poweralert EPO port supports emergency shutdown in large facilities

Versatile Installation Options Hardware included for mounting in 1U of EIA-standard 19 in. 2- or 4-post rack Optional 4POSTRAILKIT1U accessory available for extra support in 4-post installations

TAA Compliant Complies with Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

| OVERVIEW | |
|--|---|
| UPC Code | 037332218346 |
| OUTPUT | |
| Output Volt Amp Capacity (VA) | 1000 |
| Output kVA Capacity (kVA) | 1 |
| Output Watt Capacity (Watts) | 800 |
| Power Factor | 0.8 |
| Nominal Voltage Details | 120v nominal output in battery mode |
| Frequency Compatibility | 60 Hz |
| Output Voltage Regulation (Line Mode) | -21%, +8% |
| Output Voltage Regulation (Battery Mode) | +/- 5% |
| Load Management Receptacles | Two switchable single-outlet 5-15R load banks |
| Output AC Waveform (AC Mode) | Pure Sine wave |
| Output AC Waveform (Battery Mode) | Pure Sine wave |
| Nominal Output Voltage(s) Supported | 110V; 115V; 120V |
| Output Receptacles | (6) 5-15R |
| Individually Controllable Load Banks | Yes |
| INPUT | |
| Rated input current (Maximum Load) | 9.0A |
| Nominal Input Voltage(s) Supported | 120V AC |
| UPS Input Connection Type | 5-15P |
| Input Circuit Breakers | 15A |



| | |
|---|--|
| UPS Input Cord Length (ft.) | 10 |
| UPS Input Cord Length (m) | 3.1 |
| Recommended Electrical Service | 15A 120V |
| Input Phase | Single-Phase |
| BATTERY | |
| Full Load Runtime (min.) | 4 min. (800w) |
| Half Load Runtime (min.) | 14 min. (400w) |
| DC System Voltage (VDC) | 24 |
| Battery Recharge Rate (Included Batteries) | Less than 4.5 hours from 10% to 90% |
| Internal UPS Replacement Battery Cartridge | RBC69-1U |
| Battery Access | Front panel battery access door |
| Battery Replacement Description | Hot-swappable, user replaceable batteries |
| Expandable Runtime | No |
| VOLTAGE REGULATION | |
| Voltage Regulation Description | Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 83 to 147 |
| Overvoltage Correction | Input voltages between 128 and 147 are reduced by 12% |
| Undervoltage Correction | Input voltages between 83 and 107 are boosted by 14% |
| USER INTERFACE, ALERTS & CONTROLS | |
| Switches | 2 Switches control off/on power status and alarm-cancel/self-test operation |
| Alarm Cancel Operation | Power-fail alarm can be silenced using alarm-cancel switch; once silenced, alarm will re-sound to indicate low-battery status |
| Audible Alarm | Audible alarm indicates power-failure, overload and low-battery conditions |
| LED Indicators | 5 LEDs indicate line power, battery power, overload, voltage regulation and battery low/replace status |
| SURGE / NOISE SUPPRESSION | |
| UPS AC Suppression Joule Rating | 450 |
| UPS Dataline Suppression | 1 line TEL/DSL or Ethernet |
| EMI / RFI AC Noise Suppression | Yes |
| AC Suppression Response Time | Instantaneous |
| PHYSICAL | |
| Installation Form Factors Supported with Included Accessories | 4 post 19 inch rackmount; 2 post 19 inch rackmount |
| Included Mounting Accessory Description | Included mounting brackets provide front-rail installation in 2 or 4 post racks; For additional stability in 4 post racks, consider optional 4 post mounting accessories 4POSTRAILKIT1U & 4POSTRAILKITWM |



| | |
|---|--|
| Installation Form Factors Supported with Optional Accessories | 4 post rackmount full-depth (4POSTRAILKIT1U); 4 post rackmount short-depth (4POSTRAILKITWM) |
| Optional Mounting Accessory Notes | Optional 4POSTRAILKITWM enables installation in 4-port short-depth racks from 14.5 to 23.5 inches (368 to 597mm); Optional 4POSTRAILKIT1U enables installation in 4-post full-depth racks from 20.5 to 36 inches (521 to 914mm) |
| Primary Form Factor | Rackmount |
| UPS Power Module Dimensions (hwd, in.) | 1.75 x 17.5 x 16.75 |
| UPS Power Module Dimensions (hwd, cm) | 4.44 x 44.45 x 42.54 |
| Rack Height | 1U |
| Minimum Required Rack Depth (inches) | 19.75 |
| Minimum Required Rack Depth (cm) | 50.16 |
| UPS Power Module Weight (lbs.) | 32 |
| UPS Power Module Weight (kg) | 14.51 |
| Shipping Dimensions (hwd / in.) | 6.25 x 23.50 x 22.50 |
| Shipping Dimensions (hwd / cm) | 15.88 x 59.69 x 57.15 |
| Shipping Weight (lbs.) | 36.00 |
| Shipping Weight (kg) | 16.33 |
| Cooling Method | Fan |
| UPS Housing Material | Steel |
| Primary UPS Height (mm) | 44 |
| Primary UPS Width (mm) | 445 |
| Primary UPS Depth (mm) | 425 |
| ENVIRONMENTAL | |
| Operating Temperature Range | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius |
| Storage Temperature Range | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius |
| Relative Humidity | 0 to 95%, non-condensing |
| AC Mode BTU / Hr. (Full Load) | 39 |
| AC Mode Efficiency Rating (100% Load) | 99% |
| COMMUNICATIONS | |
| Communications Interface | USB; DB9 Serial; EPO (emergency power off); Slot for SNMP/Web interface |
| Network Management Cards | SNMPWEBCARD; TLNETCARD; WEBCARDLX |
| Network Monitoring Port Description | Supports detailed monitoring of UPS and site power conditions |



| | |
|---|---|
| PowerAlert Software | For local monitoring via the UPS's built-in USB or DB9 ports, download PowerAlert Local software at http://www.tripplite.com/poweralert |
| Communications Cable | USB and DB9 cabling included |
| WatchDog Compatibility | Supports Watchdog application, OS and hard-reboot restart options for remote applications |
| LINE / BATTERY TRANSFER | |
| Transfer Time | 5 milliseconds AC to DC; 1 millisecond DC to AC |
| Low Voltage Transfer to Battery Power (Setpoint) | 83 |
| High Voltage Transfer to Battery Power (Setpoint) | 147 |
| SPECIAL FEATURES | |
| Grounding Lug | Back panel grounding lug |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported |
| High Availability UPS Features | Hot swappable batteries |
| Green Energy-Saving Features | Greater than 95% efficiency - GREEN UPS; Individually controllable load banks |
| CERTIFICATIONS | |
| UPS Certifications | Meets FCC Part 15 Category A (EMI); TAA Compliant; Tested to CSA (Canada); Tested to NOM (Mexico); Tested to UL1778 (USA) |
| UPS Certification Details | UL 1778: 2014 R8.15 (5TH EDITION); CAN/CSA-C22.2 NO. 107.3-14 |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$250,000 Ultimate Lifetime Insurance |

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>