## Product data sheet Characteristics

## SBP2200RM

# APC SERVICE BYPASS PDU, 120V 20AMP W/ (6) NEMA 5-15R AND (2) 5-20R



#### Overview

Lead time Usually in Stock		Lead time	Usually in Stock
----------------------------	--	-----------	------------------



#### Main

Main Input Voltage	120 V	
Product or Component Type	Bypass kit	
Main Output Voltage	120 V	
Input Connection Type	NEMA 5-20P	
Number of rack unit	2U	
Cable length	8 ft (2.44 m)	
Number of cables	1	
Provided Equipment	User Manual	
	Rack Mounting brackets	

#### Physical

Color	Black
Height	3.50 in (8.9 cm)
Width	17.01 in (43.2 cm)
Depth	2.99 in (7.6 cm)
Net Weight	6.50 lb(US) (2.95 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted

#### Input

Input Frequency	50/60 Hz	
Permissible voltage	100125 V	
Max line current	20 A	
Input current limits	20 A	
Load Capacity	2200 VA	
Load Power Factor Range	01	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Output

Maximum Total Current Draw per Phase	20 A
Number of power socket outlets	6 NEMA 5-15R 2 NEMA 5-20R
Number of power socket outlets	10
Protection Type	Circuit breaker
Cord Length	4 ft (1.22 m)
Efficiency	99 %

## Conformance

Product Certifications TÜV	
----------------------------	--

### Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)
Relative Humidity	095 %
Operating altitude	015000 ft
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (0.0015240.00 m)

## Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304266754
Returnability	No
Country of origin	PH

## Packing Units

PCE	
1	
5.94 in (15.1 cm)	
11.61 in (29.5 cm)	
18.23 in (46.3 cm)	
8.38 lb(US) (3.8 kg)	

## Offer Sustainability

EU RoHS Directive	Compliant E EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☐ China RoHS Declaration	
RoHS exemption information	₫Yes	

### Contractual warranty

Warranty	0
vvarrantv	2 years repair or replace
vvarianty	Z years repair or replace