



Product: <u>6200FE</u> ☑

Security & Sound, 2 Conductor 16 AWG BC, Shielded, CMP

Product Description

Security & Commercial Audio Cable, 2-16 AWG stranded (19x29) bare copper conductors with Flamarrest® insulation, Beldfoil® shield, Plenum-CMP, Flamarrest® jacket with ripcord

Technical Specifications

Product Overview

Suitable Appl	cations:	Secur	ity Systems	, Intercom/PA Sys	tems, Sound/Audio	Systems, Po
Construct	on Details					
Conductor						
Element	No. of Elements	Size	Strandin	g Material		
Conductor(s)	2	16 AWG	6 19x29	BC - Bare Cop	per	
Insulation						
Element	Material		Nom. Thic	kness Nom. Ins	ulation Diameter	Color Code
Conductor(s)	PVC - Polyvinyl C	Chloride (0.009 in (0.2	23 mm) 0.075 in (1.9 mm)	Black, Red
Outer Shield						
Shield Type	Material		Coverage	Drainwire Type		
Таре	Bi-Laminate (Alun	n+Poly)	100%	24 AWG (7x32) T	C	
Outer Jacket						
Mate	ial Nom	. Thickne	ss Nom	. Diameter Rip	cord	
PVC - Polyvir	yl Chloride 0.015	in (0.38 m	nm) 0.184	in (4.67 mm) Yes		
Overall Cable	Diameter (Nomina	I): 0.184	in (4.67 mr	n)		
	Characteristic	2				

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	4 Ohm/1000ft	81.5 pF/ft (267 pF/m)	146.7 pF/ft (481.3 pF/m)	18 Amps per conductor @ 25°C

Voltage

UL Voltage Rating
300 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	0°C to +75°C

Bend Radius

Stationary Min.	Installation Min.
1.8 in (46 mm)	1.8 in (46 mm)

Max. Pull Tension:	84 lbs (38 kg)	
Bulk Cable Weight:	31 lbs/1000ft	

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262, UL 910 (Plenum), FT6, IEC 60332-1-2
	CPR Euroclass: Eca
CPR Compliance:	
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	5200FH

History

Update and Revision:

Revision Number: 0.525 Revision Date: 02-15-2024

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
6200FE 010Z500	Black	ReelTuff Box	500 ft		
6200FE 0101000	Black	Reel	1,000 ft	612825423454	
6200FE 010Z1000	Black	ReelTuff Box	1,000 ft	612825173915	
6200FE D151000	Blue	Reel	1,000 ft	612825173939	
6200FE 005Z1000	Green	ReelTuff Box	1,000 ft	612825350255	
6200FE 0051000	Green, Dark	Reel	1,000 ft	612825423447	
6200FE 877500	Natural	Reel	500 ft	612825423461	
6200FE 8771000	Natural	Reel	1,000 ft	612825173922	С
6200FE 877Z1000	Natural	ReelTuff Box	1,000 ft	612825350668	
6200FE 0031000	Orange	Reel	1,000 ft	612825350231	
6200FE 0021000	Red	Reel	1,000 ft	612825350224	
6200FE 0071000	Violet	Reel	1,000 ft	612825350262	
6200FE 0091000	White	Reel	1,000 ft	612825350279	
6200FE 0041000	Yellow	Reel	1,000 ft	612825350248	

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.