

32CH Network Video Recorder

H.265 2TB - 16CH PoE Ports



The R2-32CHNVR is a 32 channel H.265 Network Video Recorder designed to connect network cameras and provide powerful surveillance. This new generation NVR is widely applied in public security, education, communication, transportation, military, finance/banking and various other installation applications.

FEATURES

- UP TO 32CH IP CAMERA ACCESS
- UP TO 12MP RESOLUTION RECORDING
- 16CH POE PORTS
- SMART SEARCHING AND PLAYBACK
- SUPPORTS FOUR HDD, EACH UP TO 16TB HDD
- WARRENTY: 36 MONTHS
- PART #: R2-32CHNVR
- UPC: 840049307230
- LENGTH: 17.32"
- WIDTH: 14.5"
- HEIGHT: 2.76"
- WEIGHT: 10.25 LB (w/o HDD)



FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.

Enregistreurs Vidéo Réseau 32 Canaux



H.265 2To - Ports PoE 16 Canaux

Le R2-32CHNVR est un enregistreur vidéo réseau H.265 à 32 canaux conçu pour connecter des caméras réseau et fournir une surveillance puissante. Ce NVR de nouvelle génération est largement utilisé dans la sécurité publique, l'éducation, la communication, le transport, les forces armées, la finance/la banque et diverses autres applications d'installation.

FEATURES

- ACCÈS À LA CAMÉRA IP, JUSQU'À 32 CANAUX
- RÉOLUTION D'ENREGISTREMENT JUSQU'À 12 MPX
- PORTS POE 16 CANAUX
- RECHERCHE ET LECTURE INTELLIGENTES
- PRISE EN CHARGE DE QUATRE DISQUES HDD DE 16 TO CHACUN
- GARANTIE : 36 MOIS
- PART #: R2-32CHNVR
- UPC: 840049307230
- LENGTH: 17.32"
- WIDTH: 14.5"
- HEIGHT: 2.76"
- WEIGHT: 10.25LB (w/o HDD)



VIDEO INPUT	
IP CAMERA INPUT	32 CHANNEL
INCOMING BANDWIDTH	320 MBPS
OUTGOING BANDWIDTH	320 MBPS
VIDEO OUTPUT	
HDMI 1 OUTPUT	3840×2160,1920×1080, 1280×1024, 1024×768
HDMI 2 OUTPUT	1920×1080, 1280×1024, 1024×768
VGA OUTPUT	1920×1080, 1280×1024, 1024×768
DECODING CAPACITY	1CH 12MP, 4CH 4MP, 9CH 1080P, 16CH D1, 32CH D1
DUAL STREAM	SUPPORTED
MULTI-SCREEN DISPLAY	1ST SCREEN 1/4/8/9/16/32/36 2RD SCREEN 1/4/8/9/16
RECODING	
RESOLUTION	8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 ETC.
RECORDING MODE	MANUAL, SCHEDULE (REGULAR, CONTINUOUS), EVENT
TRIGGER EVENTS	MOTION DETECTION, VIDEO LOSS, ALARM IN, IVS
PLAYBACK AND BACKUP	
SYNC PLAYBACK	16/9/4/1
SEARCH MODE	TIME /DATE, ALARM, PICTURE GRID, EVENT
BACKUP MODE	USB DEVICE, NETWORK, ESATA
NETWORK	
INTERFACE	2 RJ-45 PORTS (10/100/1000 MBPS)
POE	16 PORTS (IEEE 802.3AF), 128W
NETWORK FUNCTION	HTTP, HTTPS, TCP/IP, IPV4, UPNP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP FILTER, DDNS, 802.1X, SNMP, 3G/4G, PPPOE
REMOTE USERS	8 USERS

SMART PHONE	IPHONE, IPAD, ANDROID
INTEROPERABILITY	ONVIF, SDK, CGI
STORAGE	
HDD	4 SATA PORTS, UP TO 16TB FOR EACH HDD
RAID	RAID5, RAID6, RAID10 SUPPORTED
CLOUD STORAGE	SUPPORTED
INTERFACE	
AUDIO I/O	1/1
ALARM INPUT	6CH
ALARM OUTPUT	2CH
USB	FRONT - USB 2.0 X 2 REAR - USB 3.0 X 1
GENERAL	
POWER SUPPLY	AC100 - 240V
POWER CONSUMPTION	< 15W (WITHOUT HDD)
OPERATING CONDITIONS	-10 °C ~ 50 °C (14 °F ~ 122 °F)
STORAGE CONDITIONS	LESS THAN 90% RH
CERTIFICATIONS	CE/FCC
DIMENSIONS	440× 368.3× 70 MM (17.32 × 14.5 × 2.76 INCH)
NET WEIGHT	4.65 KG (10.25 LB) WITHOUT HDD

**FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.**