

BNC CONNECTORS

ADAPTER, BNC PLUG TO F JACK

ADI
PRO

The ADI PRO BNC Plug to F Jack Adapter is designed to quickly convert an F-type coaxial cable to a BNC coaxial cable while maintaining optimal signal quality. Ideal for HD digital or analog audio and video installations.



FEATURES

Indoor, commercial and residential applications

Convert an F-type coaxial cable to a BNC coaxial cable quickly and securely

Corrosion resistant, with nickel-plated body and gold-plated contact

Limited Lifetime Warranty

RECOMMENDED TOOLS



0E-BNCCMPTL
Universal Compression Tool
BNC, F and RC



0E-BNCCRTOOL
Universal Crimp Tool
BNC, F, N, TNC, UHFST, SC

Product Specifications

PART #: 0E-BNCM2FFTP
UPC: 811914023043

Configuration: BNC plug (male) to F jack (female)

Materials: Nickel-plated zinc (body); Gold-plated brass (contact)

Package Quantity: 10



For more information, contact
your ADI salesperson or visit
adiglobal.com/adiexclusivebrands

BNC CONNECTORS

ADAPTER, BNC PLUG TO F JACK

BNC CONNECTOR	CABLE TYPE	IMPEDANCE	CABLE DIAMETER		FINISH	QTY.	PART #	
			DIELECTRIC	JACKET				
Twist-On Plug Male		RG58 (PVC) RG59 (Plenum) 20-22 AWG	50Ω	.116" - .146"	.195" - .242"	Nickel (body) Gold (contact)	10-pk	0E-BNC59PTOT
		RG59 (PVC) RG6 (Plenum) 18-22 AWG	50Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCT56PTP
		RG59 (PVC) RG6 (Plenum) 18-22 AWG	75Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCT5675T
Compression Plug Male		RG59 (PVC) 18-22 AWG	50Ω	.146"	.242"	Nickel (body) Gold (contact)	10-pk	0E-BNCCOMPTP
		RG59, RG6 (PVC)	75Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCCOM75T
		RG59 (PVC) 20 AWG	75Ω	.146"	.242"	Nickel (body) Gold (contact)	10-pk	0E-BNCCOMH75
							100 (jar)	0E-BNCCMH75C
Crimp Plug Male		RG59, RG6 (PVC)	50Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNC2UTP
		RG58 (PVC) RG59, RG6 (PVC or Plenum)	50Ω	.116" - .146" - .185"	.195" - .242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCCRIMPT
							100 (jar)	0E-BNCCRIMPC
		RG58 (PVC) RG59, RG6 (PVC or Plenum)	75Ω	.116" - 0.146" - .185"	.195" - .242" - 0.275"	Nickel (body) Gold (contact)	10-pk	0E-BNCCR75TP
							100 (jar)	0E-BNCCRI75C
						10-pk	0E-BNCU75TP	
T-Connector Male/2x Female		--	50Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCM22FTP
Coupler Female/Female		--	50Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCFFTP
		--	75Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCFF75TP
Adapter BNC Plug/F Jack		--	--	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCM2FFTP
Adapter BNC Jack/RCA Plug		--	--	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCFRCAMT

For more information, contact
your ADI salesperson or visit
adiglobal.com/adiexclusivebrands

ADI
PRO