

# DS778 Motion detector, long range, 200ft (60m)

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Motion Analyzer II processing
- ▶ Pointable mirrored optics
- ▶ Q-map signal processing
- ▶ Long range coverage
- ▶ Four mounting options

The wall mount, long range DS778 PIR Detector uses Motion Analyzer II signal processing to reduce false alarms. To aid in walk testing, the DS778 features a high efficiency alarm LED that is visible throughout the coverage pattern. This allows one installer to install and test the detector. The detector's internally pointable optics and mounting options provide installation flexibility.

## Functions

### Signal Processing

Motion Analyzer II uses multiple thresholds and timing windows to analyze timing, amplitude, duration, and polarity of signals to make an alarm decision. Will not alarm on extreme levels of thermal and illumination disturbances caused by heaters and air conditioners, hot and cold drafts, sunlight, lightning, and moving headlights. Two sensitivity settings are provided.

### Test Features

The high efficiency alarm LED can be seen throughout the walk test area. Internal noise voltage test pins provide precise pattern location and background disturbance evaluation using a standard analog meter.


### Insect and Draft Immunity

The sealed optical chamber provides immunity to drafts and insects.

### Certifications and approvals

Region	Regulatory compliance/quality marks	
Russia	GOST	EAC
USA	UL	[DS778]
	UL	UL 639 - Standard for Intrusion Detection Units

### Installation/configuration notes



### Top View

#### Long Range Coverage 60 m x 4.5 m (200 ft x 15 ft)



**Side View****Long Range Coverage 60 m x 4.5 m (200 ft x 15 ft)****Parts included**

Quantity	Component
1	Detector
1	Hardware pack
1	Installation manual

**Technical specifications****Enclosure Design**

Dimensions:	14.6 cm x 9.5 cm x 6.35 cm (5.75 in. x 3.75 in. x 2.5 in.)
Material:	High impact ABS plastic enclosure

**Environmental Considerations**

Operating Temperature:	-40°C to +49°C (-40°F to +120°F) <i>For UL Listed Applications, 0°C to +49°C (+32°F to +120°F)</i>
Radio Frequency Interference (RFI) Immunity:	No alarm or setup on critical frequencies in the range from 26 MHz to 950 MHz at 50 V/m.

Complies with Environmental Class II (EN50130-5)

**Mounting**

Height Range:	Recommended 2 m to 2.6 m (6.5 ft to 8.5 ft)
Internal Pointability:	Coverage is adjustable $\pm 10^\circ$ horizontally, $+2^\circ$ to $-18^\circ$ vertically.

**Outputs**

Alarm:	Form C contacts rated at 3.0 W, 125 mA at 28 VDC for resistive loads.
Tamper:	Normally-closed. Contacts rated at 28 VDC, 125 mA maximum.

**Power Requirements**

Current Draw:	18 mA at 12 VDC
Voltage:	6 VDC to 15 VDC

**Ordering information****DS778 Motion detector, long range, 200ft (60m)**Provides PIR 60 m x 4.5 m (200 ft x 15 ft) coverage.  
Order number **DS778****Accessories****B328 Mounting bracket, gimbal**

Mounts on a single-gang box and allows rotation of a detector. Wires are hidden inside.

Order number **B328****B335-3 Mounting bracket, swivel, low profile**Swiveling, low-profile, universal bracket for wall mounting. The vertical swivel range is  $+10^\circ$  to  $-20^\circ$ , while the horizontal swivel range is  $\pm 25^\circ$ .Order number **B335-3****B338 Mounting bracket, ceiling, universal**Swiveling universal bracket for ceiling mounting. The vertical swivel range is  $+7^\circ$  to  $-16^\circ$ , while the horizontal swivel range is  $\pm 45^\circ$ .Order number **B338****DS951-CHI Motion detector, 50ft (15m)**

Test cord for connecting a compatible detector's test pins to a voltmeter. It is 4.6 m (15 ft.) long.

Order number **TC6000****Represented by:**

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
emea.securitysystems@bosch.com  
emea.boschsecurity.com

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Germany  
www.boschsecurity.com

**North America:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
onlinehelp@us.bosch.com  
www.boschsecurity.us

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia