# Miniature MP Video Balun

## Screw Clamp Terminal to BNC

0E-VBMINIMP



#### PRODUCT DESCRIPTION

0E-VBMINIMP is a miniature, single-channel passive video balun that enables full motion megapixel video transmission over UTP up to 2,000', or 3,000' if used with an active receiver. Easy installation with screw clamp terminals and BNC connector. One pair per package.

## **FEATURES**

- Screw clamp terminal to BNC
- Compatible with standard, HD or 4K resolution
- Full motion video transmission via UTP Cat 5/5e/6/6a/7/8
- Standard resolution: Up to 2,000' (600m)
  HD-TVI 720P/1080P: Up to 820' (250m)

AHD 720P: Up to 1,148' (350m)/1080P: Up to 650' (200m) HD-CVI 720P: Up to 1,000' (300m)/1080P: Up to 820' (250m)

AHD/HD-CVI/TVI 3MP/4MP/5MP: Up to 650' AHD/HD-CVI/TVI 4K/8MP: Up to 328' (100m)



- High transient protection
- No power required
- For indoor use only

### **SPECIFICATIONS**

PART#	0E-VBMINIMP
UPC	840049300392
FREQUENCY RESPONSE	DC to 8MHz
CMRR	60dB
IMPEDANCE	BNC 75 $\Omega$ , terminal 100 $\Omega$
ATTENUATION	0.5dB typical
OPERATING TEMPERATURE	14°F to 158°F (-10°C to 70°C)
DIMENSIONS (EACH) (L x W x H)	1.88" x 0.57" x 0.57" (48 x 15 x 15mm)
WEIGHT (EACH)	0.6 oz. (17g)







