

Push Terminal Pigtail MP Video Balun

Push Terminal to Pigtail BNC

0E-VBPUSHPMP



PRODUCT DESCRIPTION

0E-VBPUSHPMP is a miniature, single-channel passive video balun that enables full motion megapixel video transmission over UTP up to 2,000', or 3,000' if used with an active receiver. Easy installation with push terminals and pigtail BNC connector. One pair per package.

FEATURES

- Push terminal to pigtail BNC
- Compatible with standard, HD or 4K resolution
- Full motion video transmission via UTP Cat 5/5e/6/6a/7/8
- Standard resolution: Up to 2,000' (600m)
HD-TVI 720P/1080P: Up to 820' (250m)
AHD 720P: Up to 1,148' (350m)/1080P: Up to 650' (200m)
HD-CVI 720P: Up to 1,000' (300m)/1080P: Up to 820' (250m)
AHD/HD-CVI/TVI 3MP/4MP/5MP: Up to 650'
AHD/HD-CVI/TVI 4K/8MP: Up to 328' (100m)
- High interference rejection
- High transient protection
- No power required
- For indoor use only



SPECIFICATIONS

PART #	0E-VBPUSHPMP
UPC	840049300439
FREQUENCY RESPONSE	DC to 8MHz
CMRR	60dB
IMPEDANCE	BNC 75Ω, terminal 100Ω
ATTENUATION	0.5dB typical
OPERATING TEMPERATURE	14°F to 158°F (-10°C to 70°C)
DIMENSIONS (EACH W/ PIGTAIL) (L x W x H)	8.2" x 0.63" x 0.69" (208 x 16 x 18mm)
WEIGHT (EACH)	1 oz. (28g)

