

RJ45 to Pigtail BNC MP Video Balun

Video Transmission + Power or Audio



0E-VBRJ45PMP

PRODUCT DESCRIPTION

0E-VBRJ45PMP is a single-channel passive video balun that enables full motion megapixel video transmission and power or audio transmission over UTP up to 2,000', or 3,000' if used with an active receiver. Easy installation with RJ45 jack and pigtail BNC connector. One pair per package.

FEATURES

- RJ45 jack to pigtail BNC
- Compatible with standard, HD or 4K resolution
- Full motion video transmission + power or audio via UTP Cat 5/5e/6/6a/7/8
- Standard resolution: Up to 2,000' (600m)
 - HD-TVI 720P/1080P: Up to 820' (250m)
 - AHD 720P: Up to 1,148' (350m)/1080P: Up to 650' (200m)
 - HD-CVI 720P: Up to 1,000' (300m)/1080P: Up to 820' (250m)
 - AHD/HD-CVI/TVI 3MP/4MP/5MP: Up to 650'
 - AHD/HD-CVI/TVI 4K/8MP: Up to 328' (100m)
- High interference rejection
- High transient protection
- No power required
- For indoor use only



SPECIFICATIONS

PART #	0E-VBRJ45PMP
UPC	840049300415
FREQUENCY RESPONSE	DC to 8MHz
CMRR	60dB
IMPEDANCE	BNC 75Ω, terminal 100Ω
ATTENUATION	0.5dB typical
OPERATING TEMPERATURE	14°F to 158°F (-10°C to 70°C)
DIMENSIONS (EACH W/ PIGTAIL) (L x W x H)	8.2" x 0.63" x 0.69" (208 x 16 x 18mm)
WEIGHT (EACH)	1 oz. (28g)

