

Product data sheet

Specifications



Galaxy VS Maintenance Bypass Cabinet, UL, Single-Unit 10-40kW 208V, 20-80kW 480V

GVSBPUSU80G

Overview

Presentation	Maintenance bypass cabinet for complete isolation of the UPS during service operations.
Lead time	Usually Ships within 2 Weeks

Main

Product or Component Type	Cabinet
---------------------------	---------

Physical

Color	White
Height	58.5 in (148.5 cm)
Width	12.5 in (31.8 cm)
Depth	33.5 in (85 cm)
Net Weight	242.5 lb(US) (110 kg)

Environmental

Ambient Air Temperature for Operation	32.0000000000...104.0000000000 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	-13.0000000000...131.0000000000 °F (-25...55 °C)
Storage Relative Humidity	0...95 % non-condensing

Ordering and shipping details

GTIN	731304342588
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	65.4 in (166 cm)
Package 1 Width	39.0 in (99 cm)
Package 1 Length	25.0000000000 in (63.5 cm)
Package 1 Weight	275.6 lb(US) (125 kg)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)
