



SHB-9000H

Box Camera Housing

FC | UL LISTED | CE | ENEC

Key Features

- Compatible camera: TNB-9000
- Material
 - Body/Sun shield : Aluminum
 - Front & Rear cap : ABS
 - Wall Mount : SUS304
- Operating Temperature: -50°C ~ +60°C(-58°F ~ +140°F) / 10-95% RH (condensing)
- Weight: 10.5kg (23 lb)
- Color: White
- IP66, UL, FCC, NDA
- Camera internally powered via 12v DC or HPOE

Compatible Accessories (Optional)



SBP-300KMW1

SHB-9000H

Box Camera Housing



Specifications

Environmental

Operating Temperature / Humidity	-50°C ~ +60°C(-58°F ~ +140°F) / 10-95% RH (condensing)
Storage Temperature / Humidity	-50°C ~ +60°C(-58°F ~ +140°F) / Less than 90% RH
Fan/Heater	Built-in thermostatically controlled, Heating & Cooling Are Independently Thermostat Controlled (FAN ON 45°C (113°F) / FAN OFF 35°C (95°F), HEATER ON 5°C (41°F) / OFF 15°C (59°F))
Certification	IP66, UL 62368-1 FCC, CE, RCM, KC

Electrical

Input Voltage	100-220VAC
Power Consumption	Maximum Total 62W - AC FAN (8.8W) : 4.4W*2EA , AC PTC HEATER (7.4W) : 3.7W*2EA, - DC Glass Heater (10W): 10W *1EA, TNB-9000 Camera (30W) : 30W *1EA (TNB-9000 can also be powered via HPOE)

Mechanical

Color	White, RAL9003
Material	Body/Sun shield : Aluminum Front & Rear cap : ABS Wall Mount Arm : SUS304
Product dimensions / weight	300(W)x184(H)x700(D)mm(11.81x7.24x27.56"), 10.5 kg(23 lb) excluding camera / lens
Supported products	Camera : TNB-9000 Lens : Canon 24mm f1.4L, Auto-Iris, Canon 35mm f1.4L, Auto-Iris, Canon 50mm f1.4, Auto-Iris, Canon 85mm f1.2L, Auto-Iris, Canon 100mm f2.0, Auto-Iris, Canon 200mm f2.8L, Auto-Iris

SHB-9000H

Box Camera Housing



DIMENSIONS

Unit: mm [inch]

