

All Products

Category	Item #	Item Type	Description
8K Cameras			
Camera - Network	TNB-9000	8K Network Box Camera	43.3mm full-frame CMOS Image Sensor, Max.15fps@8K, 20fps@24MP, 30fps@15MP, 60fps@4K, Compatible with Canon EF mount Lens, Intelligent video analytics based on AI (Object detection/classification, Attribute, BestShot), HDMI (1080p 30fps) Video Output, H.265/H.264 : Main/High, MJPEG, Single Micro SD slot (Up to 256GB), WiseStream II support, RJ-45, SFP slot(100/1000Mbps), HPOE(IEEE802.3bt, Class5), 12VDC, AI based analytics
4K Cameras & up			
Camera - Network	PNM-C34404RQPZ	5 CH, AI, IR, PTRZ Multi-directional outdoor camera with PTZ / 4K x 4 PTRZ + 2MP 40x PTZ	Wisenet P series network vandal outdoor Multi-Directional camera with PTZ, [AI ON] 4CH x 8MP @ 15FPS / [AI OFF] 4CH x 8MP @ 20FPS + PTZ 40x 2MP @ 60FPS, 4CH Remote PTRZ Lens 3.3-5.7mm (FoV H: 109°-56°, V: 55°-31°), triple codec H.265/H.264/MJPEG, 120dB WDR; IR viewable [4CH] length 20m (65ft) / [PTZ] WiselR 200m (656ft), Analytics events based on AI engine: Object detection (Person/Vehicle (Car/Bus/Truck/Motorcycle/Bicycle)), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Appear/Disappear, WiseNR II (using AI engine), WiseStream III (Based on AI engine), I/O Box compatibility: TPM with FIPS 140-2 level2, micro SD card 512GB x2, IP66, IK10, NEMA4X, Operating Temperature: -40°C~+50°C(-40°F~+122°F), HPOE (injector included), Hard-coated dome bubble
Camera - Network	PNM-9322VQP	5 Channel 2MP / 5MP X 4 + 2MP 32x PTZ	Network vandal outdoor camera that combines Multi-sensor Multi-Directional camera, (2MP/5MP X 4 sensors sold separately) 8MP ~20MP (2MP @ 60fps or 5MP @30fps) fixed focal lens modules and 2MP 32x optical zoom PTZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 150dB @ 2MP or 120dB @ 5MP, defocus detection, built in analytics, 4x SD card, hallway view, HLC, defog detection, DIS(Gyro Sensor), Audio I/O (PTZ ch only), HPOE injector (included), IP66/IK10, -40°C ~ +55°C (-40°F ~ +131°F), White color, 2MP Lens modules: SLA-2M2400P (2.4mm), SLA-2M2800P (2.8mm), SLA-2M3600P (3.6mm), SLA-2M6000P (6mm), SLA-2M1200P (12mm) 5MP Lens modules: SLA-5M3700P (3.7mm), SLA-5M4600P (4.6mm), SLA-5M7000P (7.0mm)
Camera - Network	PNM-9084QZ1	2MP X 4 outdoor Dome, PTRZ	Wisenet P series network vandal outdoor Multi-sensor Multi-Directional dome camera, (2MP X 4 sensors) 8MP @ 60fps, motorized vari-focal lens 2x (3.0-6.0mm) (107°-56.3°), PTRZ (Pan/Tilt/Rotate/Zoom) remote adjustment, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, defocus detection, built in analytics, true D/N, 4x SD card, hallway view, HLC, defog detection, Bi-Directional Audio, Alarm I/O 1/1, IP66, IK10, NEMA4X, -40°C ~ +55°C (-40°F ~ +131°F), White, DIS, HPOE Injector included
Camera - Network	PNM-C16083RVQ	4MP x 4, AI, IR Multi-directional outdoor camera	Wisenet P series network vandal outdoor Multi-Directional camera 4CH x 4MP @ 30FPS, Motorized Varifocal Lens 3.3-5.7mm (FoV H: 100°-53°, V: 54°-30°), triple codec H.265/H.264/MJPEG, 120dB WDR; IR viewable length [PoE+] 15m (49ft) / [HPOE] 20m (65ft), USB port for easy installation, Analytics events based on AI engine: Object detection (Person/Vehicle (Car/Bus/Truck/Motorcycle/Bicycle)), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Appear/Disappear, WiseNR II (using AI engine), I/O Box compatibility: TPM with FIPS 140-2 level2, micro SD card 512GB x2, IP66, IK10, NEMA4X, Operating Temperature: -40°C~+55°C(-40°F~+131°F); PoE+ /HPOE, Hard-coated dome bubble
Camera - Network	PNM-C16013RVQ	4MP x 4, AI, IR mini multi-directional camera	Wisenet P series network vandal outdoor mini Multi-Directional camera 4CH x 4MP @ 15FPS, Fix Lens 3.19mm (FoV H: 97°, V: 54°), triple codec H.265/H.264/MJPEG, 120dB WDR; IR viewable length 20m (65.6ft), USB port for easy installation, Analytics events based on AI engine: Object detection (Person/Vehicle (Car/Bus/Truck/Motorcycle/Bicycle)), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Appear/Disappear, WiseNR II (using AI engine), WiseStream III (Based on AI engine), I/O Box compatibility: TPM with FIPS 140-2 level2, micro SD card 512GB x2, IP66, IK09, NEMA4X, Operating Temperature: -40°C~+55°C(-40°F~+131°F); PoE+ /HPOE, Hard-coated dome bubble
Camera - Network	PNM-9084RQZ1	2MP X 4 outdoor Dome, PTRZ w/IR	Wisenet P series network vandal outdoor Multi-sensor Multi-Directional dome camera, 2MP x 4ch multi-directional camera, Motorized PTRZ support, Max. 60fps@2MP(H.265, H.264), 3.2-10mm(3.1x) motorized varifocal, IR viewable length: 30m, H.265, H.264, MJPEG with WiseStream II technology, 120dB WDR, defocus detection, built in analytics, true D/N, 4x SD card, hallway view, HLC, defog detection, Bi-Directional Audio, Alarm I/O 1/1, IP66, IK10, NEMA4X, -40°C ~ +55°C (-40°F ~ +131°F), White, DIS, HPOE Injector included
Camera - Network	PNM-C32083RVQ	4K x 4, AI, IR Multi-directional outdoor camera	Wisenet P series network vandal outdoor Multi-Directional camera [AI ON] 4CH x 8MP @ 15FPS / [AI OFF] 4CH x 8MP @ 20FPS, Motorized Varifocal Lens 3.3-5.7mm (FoV H: 109°-56°, V: 55°-31°), triple codec H.265/H.264/MJPEG, 120dB WDR; IR viewable length [PoE+] 15m (49ft) / [HPOE] 20m (65ft), USB port for easy installation, Analytics events based on AI engine: Object detection (Person/Vehicle (Car/Bus/Truck/Motorcycle/Bicycle)), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Appear/Disappear, WiseNR II (using AI engine), WiseStream III (Based on AI engine), I/O Box compatibility: TPM with FIPS 140-2 level2, micro SD card 512GB x2, IP66, IK10, NEMA4X, Operating Temperature: -40°C~+55°C(-40°F~+131°F), PoE+ /HPOE, Hard-coated dome bubble
Camera - Network	PNM-9085RQZ1	5MP X 4 outdoor Dome, PTRZ w/IR	Wisenet P series network vandal outdoor Multi-sensor Multi-Directional dome camera, 5MP x 4ch multi-directional camera, Motorized PTRZ support, Max. 30fps@5MP(H.265, H.264), 4.13-9.4mm(2.3x) motorized varifocal lens, IR viewable length: 30m, H.265, H.264, MJPEG with WiseStream II technology, 120dB WDR, defocus detection, built in analytics, true D/N, 4x SD card, hallway view, HLC, defog detection, Bi-Directional Audio, Alarm I/O 1/1, IP66, IK10, NEMA4X, -40°C ~ +55°C (-40°F ~ +131°F), White, DIS, HPOE Injector included
Camera - Network	PNM-9000QB	Remote head 2MP x 4CH camera	WN7 multi head camera, 4 x 2MP @ 30fps, triple codec H.265/H.264/MJPEG, extreme WDR 150dB, dual SD cards slots, Wisestream II, hallway view, HLC, defog detection, audio In/out, HDMI out 12VDC/PoE+, DIS support, analytics-defocus, directional, motion, enter/exit, tampering, virtual line, I/O in/out. Compatible with SLA-T4680A/T4680VA, SLA-T2480A/T2480VA, SLA-T1080FA
Camera - Network	PNM-9002VQ	2MP / 5MP X 4	Network vandal outdoor Multi-sensor Multi-Directional dome camera, (2MP/5MP X 4 sensors sold separately) 8MP ~20MP (2MP @ 60fps or 5MP @ 30fps), fixed focal lens modules, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR @ 2MP or 120dB @ 5MP, defocus detection, built in analytics, PTZ handover, 4x SD card, hallway view, HLC, defog detection, DIS(Gyro Sensor), PoE+, IP66/IK10, -40°C ~ +55°C (-40°F ~ +131°F) 2MP Lens modules: SLA-2M2400Q (2.4mm), SLA-2M2800Q (2.8mm), SLA-2M3600Q (3.6mm), SLA-2M6000Q (6mm) 5MP Lens modules: SLA-5M3700Q (3.7mm), SLA-5M4600Q (4.6mm), SLA-5M7000Q (7.0mm). WHITE COLOR
Camera - Network	PNM-C12083RVD	6MP X 2 AI, IR outdoor Dome	Network vandal outdoor 2CH AI IR dome camera, (6MP X 2 sensors) 12MP @ 15fps, 3.4-6.8mm(2x) (95.08°-47.64°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 25m (82ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS, Handover, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Audio detection, Sound classification, Appear/Disappear, FIPS 140-2, micro SD card 512GB, IP66, NEMA4X, IK10, Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE+, Metal shielded RJ-45, Hard-coated dome bubble
Camera - Network	PNM-12082RVD	6MP X 2, IR outdoor Dome	Network vandal outdoor 2CH IR dome camera, (6MP X 2 sensors) 12MP @ 15fps, 3.4-6.8mm(2x) (95.08°-47.64°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 25m (82ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS, Handover, Analytics events: Defocus detection, Directional Detection, Motion detection, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection, Sound classification, FIPS 140-2, micro SD card 512GB, IP66, NEMA4X, IK10, Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE+, Metal shielded RJ-45, Hard-coated dome bubble
Camera - Network	PNM-9000VD	5MP X 2 outdoor Dome	Network vandal outdoor Multi-sensor Multi-Directional dome camera, (5MP X 2 sensors sold separately) 10MP @ 30fps, modular lenses from 3.7, 4.6 and 7.0mm lenses, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, built in analytics, 2x SD card, hallway view, HLC, defog detection, DIS, PoE, IP66/IK10, -40°C ~ +55°C (-40°F ~ +131°F). Lens modules: SLA-5M3700D (3.7mm), SLA-5M4600D (4.6mm), SLA-5M7000D (7.0mm)
Camera - Network	PNM-8082VT	3CH x 2MP	Powered by WN7, 2MP x 3CH @ 30FPS, multi directional camera, 3-6mm motorized varifocal lens, donut shape bubble, max 321° coverage, Triple codec H.264/265 MJPEG, WiseStream II, extreme WDR 150dB, defocus detection, video analytics, 2x microSD card, PoE+, IP66, IK10, NEMA4X, operating temp -40°C~+55°C
Camera - Network	PNM-9031RV	15MP Panoramic Camera	Network vandal outdoor Multi-sensor dome camera, panoramic view with stitched image, (5MP X 4 sensors) 15MP @ 20fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 120dB, IR viewable length 20m (65.5'), built in video analytics and sound classification, Heatmap, Bi-directional audio support, Micro SD 2 slots, IP66/IK10/NEMA4X, TPM 2.0 (FIPS 140-2 level 2), PoE+/12VDC
Camera - Network	PNM-C9022RV	8MP Panoramic Camera with AI and IR	Panoramic Multi-sensor camera, FoV: H:209°, V:60°, 8MP @ 20fps, Alpha Blending, triple codec H.265/H.264/MJPEG with WiseStream III technology, extreme WDR 120dB, Wise NR II, IR viewable length 65' (20m), Analytics events based on AI engine: Object detection (Person/Vehicle), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), defocus detection, Micro USB for easy installation, 2 x Micro SD cards (512GB each), PoE+/12VDC, IP66/IK10/NEMA4X, TPM 2.0 (FIPS 140-2 level 2)
Camera - Network	PNM-9022V	8.3MP Panoramic Camera	WN7 Panoramic Multi-sensor camera, 180° view, (2MP X 4 sensors) 7.3MP @ 30fps, panoramic 209° view, 8.3MP, triple codec H.265/H.264/MJPEG with WiseStream II technology, extreme WDR 120dB, defocus detection, built in analytics, Heatmap, Micro USB for easy installation, 2 x Micro SD cards PoE+, IP66/IK10/NEMA4X
Camera - Network	PND-A9081RF	4K IR Indoor Flush Mount Dome AI Camera	4K Network AI IR Dome Camera, Max. 4K resolution @ 30FPS, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), 4.5-10mm(2.2x) motorized varifocal lens, WDR(120dB), H.265, H.264, MJPEG codec, WiseStream II (Using AI engine), Video Analytics based on AI Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing Detection, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, 2x micro SD card (512GB x2), Operating temperature: -25 °C ~ 50 °C(-13°F ~ +122°F), PoE+/12VDC, IP52, IK10, Plenum rated
Camera - Network	PND-A9081RVX	4K IR Indoor AI Camera Module Only	4K Network AI IR Indoor Camera Module, Max. 4K resolution @ 30FPS, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), 4.5-10mm(2.2x) motorized varifocal lens, WDR(120dB), H.265, H.264, MJPEG codec, WiseStream III (Using AI engine), Video Analytics based on AI Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing Detection, Attribute, BestShot) People counting, Heatmap, Queue management based on AI, Face Mask Detection, Social Distancing Detection, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, 2x micro SD card (512GB x2), Operating temperature (When using the camera with housing): -25 °C ~ 50 °C(-13°F ~ +122°F), PoE+/12VDC

Camera - Network	PND-A9081RV	4K IR Indoor Vandal Dome AI Camera	4K Network AI IR Dome Camera, Max. 4K resolution @ 30FPS, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), 4.5-10mm(2.2x) motorized varifocal lens, WDR(120dB), H.265, H.264, MJPEG codec, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot People counting, Heatmap, Queue management based on AI, Face Mask Detection, Social Distancing Detection, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, 2x micro SD card (512GB x2), Operating Temperature: -25 °C ~ 50 °C(-13°F ~ +122°F), PoE+/12VDC
Camera - Network	PNV-A9081RX	4K IR Outdoor AI Camera Module Only	4K Network AI IR Outdoor Camera Module, Max. 4K resolution @ 30FPS, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), 4.5-10mm(2.2x) motorized varifocal lens, WDR(120dB) H.265, H.264, MJPEG codec, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot People counting, Heatmap, Queue management based on AI, Face Mask Detection, Social Distancing Detection, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, 2x micro SD card (512GB x2), Operating temperature (When using the camera with housing): -40°C~+55°C(-40°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	PNV-A9081R	4K IR Outdoor Vandal Dome AI Camera	4K Network AI IR Vandal Dome Camera, Max. 4K resolution @ 30FPS, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), 4.5-10mm(2.2x) motorized varifocal lens, WDR(120dB) H.265, H.264, MJPEG codec, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot People counting, Heatmap, Queue management based on AI, Face Mask Detection, Social Distancing Detection, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, 2x micro SD card (512GB x2), Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45, IP66/IP67/IP6K9K, IK10+, NEMA4X
Camera - Network	PNO-A9311R	4K Network AI IR Zoom (31x) Bullet Camera	4K Network AI IR Bullet Camera, Max. 4K resolution @ 30FPS, 0.075Lux@F1.36 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), 6.91-214.7mm (31x) zoom lens, WDR(120dB) H.265, H.264, MJPEG codec, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Slip&Fall detection, Attribute, BestShot People counting, Vehicle counting, Crowd counting, Queue management, Heatmap based on AI, TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgery, Modular structure for easy installation, 2x micro SD card (512GB x2), Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45, IP66/IP67, IK10, NEMA4X
Camera - Network	PNO-A9081R	4K IR Bullet AI camera	4K Network AI IR Bullet Camera, Max. 4K resolution @ 30FPS, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), 4.5-10mm(2.2x) motorized varifocal lens, WDR(120dB) H.265, H.264, MJPEG codec, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot People counting, Heatmap, Queue management based on AI, Face Mask Detection, Social Distancing Detection, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, 2x micro SD card (512GB x2), Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45, IP66/IP67/IP6K9K, IK10+, NEMA4X
Camera - Network	PNB-A9001	4K Box AI camera	4K AI Network Box Camera, Max. 4K resolution, 0.03Lux@F1.2(Color), Day & Night(ICR), WDR(120dB) H.265, H.264, MJPEG codec, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot People counting, Heatmap, Queue management based on AI, Face Mask Detection, Social Distancing Detection, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, 2x micro SD card (512GB x2), Power: PoE+/12VDC,
Camera - Network	XNP-C9303RW	4K AI IR, Wiper PTZ	Powered by WN7 PTZ Plus with AI, 4K @ 30FPS resolution, 5mm-150mm (30x) lens, build in wiper and adaptive Wise IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Analytics events based on AI engine: Object detection (Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), Object auto-tracking (Person/Vehicle), Target lock track, BLC, HLC, SSSDR, lens heater for water/snow removal, IP66, IK10, NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), FIPS 140-2, PoE++/HPoE injector included, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-9300RW	4K IR, Wiper PTZ	Powered by WN7, 4K @ 30FPS resolution, 5mm-150mm (30x) lens, build in wiper and adaptive Wise IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), PoE++/HPoE injector included, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-C9253R	4K AI IR, PTZ	Powered by WN7 PTZ Plus with AI, 4K @ 30FPS resolution, 5mm-125mm (25x) lens, adaptive Wise IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Analytics events based on AI engine: Object detection (Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), Object auto-tracking (Person/Vehicle), Target lock track, BLC, HLC, SSSDR, lens heater for water/snow removal, IP66, IK10, NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), FIPS 140-2, PoE++/HPoE injector included, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-9250R	4K, 25x, IR PTZ camera	Powered by WN7, 4K @ 30FPS resolution, 5mm-125mm (25x) lens, adaptive Wise IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), PoE++/HPoE injector included, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-C9310R	4K AI Focus IR, PTZ	Powered by WN7 and AI, 8MP (4K UHD) @ 30FPS resolution, 6.91mm-214.64mm (31x) lens with Wise AI intelligent autofocus, adaptive Wise IR (250m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG triple codec with WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Face/Vehicle/License plate), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), AI object auto-tracking (Person/Vehicle) with target lock tracking, BLC, HLC, SSSDR, lens heater for water/snow removal, IP66, IP67, IK10, NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), FIPS 140-2, PoE++/HPoE injector included, Operating Temperature -50°C~+55°C (-58°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-C9253	4K AI PTZ	Powered by WN7 PTZ Plus with AI, 4K @ 30FPS resolution, 5mm-125mm (25x) lens, extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Analytics events based on AI engine: Object detection (Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), Object auto-tracking (Person/Vehicle), Target lock track, BLC, HLC, SSSDR, lens heater for water/snow removal, IP66, IK10, NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), FIPS 140-2, Power: PoE+, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-9250	4K, 25x PTZ camera	Powered by WN7, 4K @ 30FPS resolution, 5mm-125mm (25x) lens, extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSSDR, IP66, IK10, NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), Power: PoE+, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNO-C9083R	4K IR Bullet AI camera	Powered by WN7, Outdoor Network AI IR Bullet Camera, 4K resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, AU CAP certified, P66, IP67, NEMA4X, IK10, Operating temperature: -40°C~+55°C(-40°F ~ +131°F) Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XNO-9083R	4K IR Bullet AI Camera	Powered by WN7, X-Plus series, Outdoor Network AI IR Bullet Camera, 4K resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10, Operating temperature: -50°C~+60°C(-58°F ~ +140°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNO-9082R	4K IR Bullet Camera	Wisenet 7 X series network IR bullet camera, 4K (8MP Max) @ 30fps, motorized vari-focal lenses 3x (2.8-8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defocus detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP66, IK10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XND-C9083RV	4K IR Indoor Vandal Dome AI Camera	Powered by WN7, Indoor Network AI IR Dome Camera, 4K resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP52, IK08, Operating temperature: -10 °C ~ 50 °C(14°F ~ +122°F), Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XNV-C9083R	4K IR Outdoor Vandal Dome AI Camera	Powered by WN7, Outdoor Network AI IR Vandal Dome Camera, 4K resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, P66, IP67, NEMA4X, IK10, Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45

Camera - Network	XNV-9082R	4K IR Outdoor Vandal Dome	Wisenet 7 X-plus series network IR vandal outdoor camera, 4K (8MP Max) @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamIII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP66/IP6K9K, IK10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XND-9083RV	4K IR Indoor Vandal Dome AI Camera	Powered by WN7, X-Plus series, Indoor Network AI IR Dome Camera, 4K resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), IP52, IK10, Operating temperature: -25 °C ~ 50 °C(-13°F ~ +122°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNV-9083RZ	4K IR Outdoor Vandal Dome AI, PTRZ Camera	Powered by WN7, X-Plus series, Outdoor Network AI IR Vandal Dome Camera, 4K resolution @ 30FPS, 4.4-9.3mm (2.1x) (113°-47°) motorized varifocal lens, Remote lens adjustment (PTRZ), Triple codec (H.265/H.264/MJPEG), IR Viewable Length: 15m(49.21ft) / 30m(98.43ft) based on scene, USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), IP66, IP67, IP6K9K, NEMA4X, IK10+, Operating temperature: -50°C~+55°C(-58°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNV-9083R	4K IR Outdoor Vandal Dome AI Camera	Powered by WN7, X-Plus series, Outdoor Network AI IR Vandal Dome Camera, 4K resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10+, Operating temperature: -50°C~+55°C(-58°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XND-9082RF	4K IR Flush Mount Dome	Wisenet 7 X-plus series network IR flush mount camera (plenum), 4K (8MP Max) @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamIII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, -25°C ~ +60°C (-13°F ~ +140°F)
Camera - Network	XND-9082RV	4K IR Indoor Dome	Wisenet 7 X-plus series network IR vandal indoor camera, 4K (8MP Max) @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamIII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, -25°C ~ +60°C (-13°F ~ +140°F)
Camera - Network	XNB-9003	4K Box AI Camera	Powered by WN7, X-Plus series, Box Camera, 8MP resolution @ 30FPS, Triple codec (H.265/H.264/MJPEG), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), Operating temperature: -10 °C ~ 55 °C(14°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNB-9002	4K Box Camera	Wisenet 7 X series network box camera, 4K (8MP Max) @ 30fps, triple codec H.265/H.264/MJPEG with WiseStreamIII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, -10°C ~ +55°C (+14°F ~ +131°F)
Camera - Network	XNF-9010RS	12MP Stainless Steel IR Fisheye Camera	Stainless steel Fisheye, powered by WN7, 1/2.3" 12MP CMOS, Max resolution 3008x3008 @ 30FPS, 1.08mm fixed focal lens, Stereo graphic type lens, enhanced resolution for the peripheral regions, H.265, H.264, MJPEG codec supported, Fisheye, Single panorama, Double panorama, Quad view, On board dewarping, Digital PTZ, extreme WDR (120dB), WiseStream II support, Wide IR, IR viewable length 26.2' (8m), Virtual channel support, selectable I/O port, Video Analytics, Heatmap, People counting, Queue management, Nylon dome, Handover, IP66/IP67/IP6K9K/IK10/NEMA4X, PoE, 12VDC
Camera - Network	XNF-9013RV	12MP, Fisheye camera with AI and IR	Powered by WN7, 1/2.3" 12MP CMOS, Max resolution 3008x3008 @ 30FPS, 1.08mm fixed focal lens, Stereo graphic type lens, enhanced resolution for the peripheral regions, H.265, H.264, MJPEG codec supported, Fisheye, Single panorama, Double panorama, Quad view, On board dewarping, Digital PTZ, extreme WDR (120dB), WiseStream III support, Wide NR II, IR viewable length 42' (13m), Analytics events based on AI engine: Object detection (Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Virtual channel support, selectable I/O port, Video Analytics, Heatmap, People counting, Queue management, Hard coated dome cover, Handover, IP66/IK10/NEMA4X, PoE+ (Wise Power), 12VDC
Camera - Network	XNF-9010RV	12MP, WN7 Fisheye	Powered by WN7, 1/2.3" 12MP CMOS, Max resolution 3008x3008 @ 30FPS, 1.08mm fixed focal lens, Stereo graphic type lens, enhanced resolution for the peripheral regions, H.265, H.264, MJPEG codec supported, Fisheye, Single panorama, Double panorama, Quad view, On board dewarping, Digital PTZ, extreme WDR (120dB), WiseStream II support, Wide IR, IR viewable length 32.8' (10m), Virtual channel support, Plugin support, selectable I/O port, Video Analytics, Heatmap, People counting, Queue management, Hard coated dome cover, Handover, IP66/IK10/NEMA4X, PoE, 12VDC
Camera - Network	XNF-9010RVM	12MP, WN7 Fisheye	Powered by WN7, 1/2.3" 12MP CMOS, Max resolution 3008x3008 @ 30FPS, 1.08mm fixed focal lens, Stereo graphic type lens, enhanced resolution for the peripheral regions, H.265, H.264, MJPEG codec supported, Fisheye, Single panorama, Double panorama, Quad view, On board dewarping, Digital PTZ, extreme WDR (120dB), WiseStream II support, Wide IR, IR viewable length 32.8' (10m), Virtual channel support, Plugin support, selectable I/O port, Video Analytics, Heatmap, People counting, Queue management, Hard coated dome cover, Handover, IP66/IK10/NEMA4X, EN50155 class T3, PoE, 12VDC, supports M12, Special order
Camera - Network	QNV-C9083R	4K IR Outdoor Vandal Dome AI Camera	Wisenet Q network outdoor vandal dome camera, 4K @ 30fps, motorized vari-focal lens 3.2-10.2mm (H: 104°-31° / V: 55°-17°), triple codec H.265/H.264/MJPEG with Wisestream III (Based on AI engine), WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 30m (98ft), WiseMD based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/Dis)Appear, *Audio: Selectable(mic in/line in), defocus detection, hallway View, SD card, video analytics, USB for easy installation, open platform, IP66, IK10, PoE, Operating temperature -30°C~+55°C(-22°F ~ +131°F) white color. * Alarm I/O and audio is supported through an optional cable (SPP-C7400)
Camera - Network	QNO-C9083R	4K IR Bullet AI camera	Wisenet Q network outdoor vandal bullet camera, 4K @ 30fps, motorized vari-focal lens 3.2-10.2mm (H: 104°-31° / V: 55°-17°), triple codec H.265/H.264/MJPEG with Wisestream III (Based on AI engine), WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 30m (98ft), WiseMD based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/Dis)Appear, Audio: Selectable(mic in/line in), defocus detection, hallway View, SD card, video analytics, USB for easy installation, open platform, IP66, IK10, PoE, Operating temperature -30°C~+55°C(-22°F ~ +131°F) white color
Camera - Network	QNV-C9011R	4K IR Outdoor Vandal Dome AI Camera	Wisenet Q mini network outdoor vandal dome camera, 4K @ 30fps, fix lens 3mm (H:108°/V: 59°), triple codec H.265/H.264/MJPEG with Wisestream III (Based on AI engine), WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 20m(65.62ft), WiseMD based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/Dis)Appear, defocus detection, hallway View, SD card, video analytics, USB for easy installation, open platform, IP66, IK10, NEMA4X, PoE, Operating temperature -40°C~+55°C(-40°F ~ +131°F) white color.
Camera - Network	QNF-9010	12MP Indoor fisheye	Wisenet Q series network Indoor fisheye dome camera, 12MP CMOS sensor, max resolution 3008x3008 @ 30fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 120dB, business analytics (heatmap and people counting), built-in SD card slot, PoE
6MP Cameras			
Camera - Network	XNP-C8303RW	6MP AI IR, Wiper PTZ	Powered by WN7 PTZ Plus with AI, 6MP @ 30FPS resolution, 5mm-150mm (30x) lens, built in wiper and adaptive Wide IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Analytics events based on AI engine: Object detection (Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), Object auto-tracking (Person/Vehicle), Target lock track, BLC, HLC, SSSDR, lens heater for water/snow removal, IP66, IK10, NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), FIPS 140-2, PoE++/HPoE injector included, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-8300RW	6MP IR, Wiper PTZ	Powered by WN7, 6MP @ 30FPS resolution, 5mm-150mm (30x) lens, Wide IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), PoE++/HPoE injector included, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-C8253R	6MP AI IR, PTZ	Powered by WN7 PTZ Plus with AI, 6MP @ 30FPS resolution, 5mm-125mm (25x) lens, adaptive Wide IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Analytics events based on AI engine: Object detection (Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), Object auto-tracking (Person/Vehicle), Target lock track, BLC, HLC, SSSDR, lens heater for water/snow removal, IP66, IK10, NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), FIPS 140-2, PoE++/HPoE injector included, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-8250R	6MP, 25x, IR PTZ camera	Powered by WN7, 6MP @ 30FPS resolution, 5mm-125mm (25x) lens, Wide IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, NEMA-TS 2 (2.2.7, 2.2.8, 2.2.9), PoE++/HPoE injector included, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)

Camera - Network	XNP-C8253	6MP AI PTZ	Powered by WN7 PTZ Plus with AI, 6MP @ 30FPS resolution, 5mm-125mm (25x) lens, extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Analytics events based on AI engine: Object detection (Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), Object auto-tracking (Person/Vehicle), Target lock track, BLC, HLC, SSSR, lens heater for water/snow removal, IP66, IK10, NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), FIPS 140-2, Power: PoE+, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-8250	6MP, 25x PTZ camera	Powered by WN7, 6MP @ 30FPS resolution, 5mm-125mm (25x) lens, extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSSR, IP66, IK10, NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), Power: PoE+, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNO-C8083R	6MP IR Bullet AI camera	Powered by WN7, Outdoor Network AI IR Bullet Camera, 6MP resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, UL CAP certified, P66, IP67, NEMA4X, IK10, Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XNO-8083R	6MP IR Bullet AI Camera	Powered by WN7, X-Plus series, Outdoor Network AI IR Bullet Camera, 6MP resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10, Operating temperature: -50°C~+60°C(-58°F ~ +140°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNO-8082R	6MP IR Bullet Camera	Wisenet 7 X series network IR bullet camera, 6MP @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP66, IK10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XNV-C8083R	6MP IR Outdoor Vandal Dome AI Camera	Powered by WN7, Outdoor Network AI IR Vandal Dome Camera, 6MP resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, P66, IP67, NEMA4X, IK10, Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XNV-8093R	6MP IR Outdoor Vandal Dome AI Camera	Powered by WN7, X-Plus series, Outdoor Network AI IR Vandal Dome Camera, 6MP resolution @ 30FPS, 10.9-29mm(2.7x) (42°-15°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 70m (229.66ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10+, Operating temperature: -50°C~+55°C(-58°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNV-8083RZ	6MP IR Outdoor Vandal Dome AI, PTRZ Camera	Powered by WN7, X-Plus series, Outdoor Network AI IR Vandal Dome Camera, 6MP resolution @ 30FPS, 4.4-9.3mm (4.3x) (113°-47°) motorized varifocal lens, Remote lens adjustment (PTRZ), Triple codec (H.265/H.264/MJPEG), IR Viewable Length: 15m(49.21ft) / 30m(98.43ft) based on scene, USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), IP66, IP67, IP6K9K, NEMA4X, IK10+, Operating temperature: -50°C~+55°C(-58°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNV-8083RX	6MP IR Outdoor AI Camera Module Only	Powered by WN7, X-Plus series, Network AI IR Outdoor Camera Module, 6MP resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), Operating temperature: -50°C~+55°C(-58°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNV-8083R	6MP IR Outdoor Vandal Dome AI Camera	Powered by WN7, X-Plus series, Outdoor Network AI IR Vandal Dome Camera, 6MP resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10+, Operating temperature: -50°C~+55°C(-58°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNV-8082R	6MP IR Outdoor Vandal Dome	Wisenet 7 X-plus series network IR vandal outdoor camera, 6MP @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP66/IP6K9K, IK10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XND-C8083RV	6MP IR Indoor Vandal Dome AI Camera	Powered by WN7, Indoor Network AI IR Dome Camera, 6MP resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP52, IK08, Operating temperature: -10 °C ~ 50 °C(14°F ~ +122°F), Power: PoE/12VDC
Camera - Network	XND-8093RV	6MP IR Indoor Dome AI Camera	Powered by WN7, X-Plus series, Indoor Network AI IR Dome Camera, 6MP resolution @ 30FPS, 10.9-29mm(2.7x) (42°-15°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 70m (229.66ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), IP52, IK10, Operating temperature: -25 °C ~ 50 °C(-13°F ~ +122°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XND-8083RVX	6MP IR Indoor AI Camera Module Only	Powered by WN7, X-Plus series, Network AI IR Indoor Camera Module, 6MP resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), Operating temperature: -25 °C ~ 50 °C(-13°F ~ +122°F), Power: PoE+/12VDC
Camera - Network	XND-8083RV	6MP IR Indoor Vandal Dome AI Camera	Powered by WN7, X-Plus series, Indoor Network AI IR Dome Camera, 6MP resolution @ 30FPS, 4.4-9.3mm(2.1x) (112.1°-47.5°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), IP52, IK10, Operating temperature: -25 °C ~ 50 °C(-13°F ~ +122°F), Power: PoE+/12VDC
Camera - Network	XND-8082RF	6MP IR Flush Mount Dome	Wisenet 7 X-plus series network IR flush mount camera (plenum), 6MP @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, -25°C ~ +60°C (-13°F ~ +140°F)
Camera - Network	XND-8082RV	6MP IR Indoor Dome	Wisenet 7 X-plus series network IR vandal indoor camera, 6MP @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, -25°C ~ +60°C (-13°F ~ +140°F)
Camera - Network	XNB-8003	6MP Box AI Camera	Powered by WN7, X-Plus series, Box Camera, 6MP resolution @ 30FPS, Triple codec (H.265/H.264/MJPEG), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), Operating temperature: -10 °C ~ 55 °C(14°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNB-8002	6MP Box Camera	Wisenet 7 X series network box camera, 6MP @ 30fps, triple codec H.265/H.264/MJPEG with WiseStreamII technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD cards slots, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, -10°C ~ +55°C (+14°F ~ +131°F)

5MP Cameras

Camera - Network	XND-8081REV	5MP Indoor Dome, PoE extender camera	Wisenet X powered by Wisenet 5 network IR indoor dome camera with PoE Extender, PoE+ in PoE out, 5MP @30fps, Motorized Varifocal Lens (3.9mm -9.4mm), triple codec H.265/H.264/MJPEG with WiseStream II technology,WDR 120dB, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), PoE/PoE+ , IP52, IK10, -25°C ~ +60°C (-13°F ~ +140°F)
Camera - Network	XNV-8081RE	5MP Outdoor Dome, PoE extender camera	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera with PoE Extender, PoE+ in PoE out, 5MP @30fps, Motorized Varifocal Lens (3.9mm -9.4mm), triple codec H.265/H.264/MJPEG with WiseStream II technology,WDR 120dB, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), PoE/PoE+ , IP66/IP67/IP6K9K, IK10+, NEMA4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XNV-8081R	5MP IR Outdoor Dome	Wisenet X series Plus powered by Wisenet 5 IR network outdoor vandal dome camera, modular structure, 5MP @ 30fps, motorized vari-focal lens 2.6x (3.6-9.4mm) (102.5°-38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/IP6K9K, IK10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover
Camera - Network	XND-8081RF	5MP IR Flush Mount Dome	Wisenet X series Plus powered by Wisenet 5 IR network indoor flush mount vandal dome camera, modular structure, 5MP @ 30fps, motorized vari-focal lens 2.6x (3.6-9.4mm) (102.5°-38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, plenum housing
Camera - Network	XND-8081RV	5MP IR Indoor Dome	Wisenet X series Plus powered by Wisenet 5 IR network indoor vandal dome camera, modular structure, 5MP @ 30fps, motorized vari-focal lens 2.6x (3.6-9.4mm) (102.5°-38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, built-in mic, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover
Camera - Network	XNV-8081Z	5MP Outdoor PTRZ Dome	Wisenet X series Plus powered by Wisenet 5 network outdoor vandal dome camera, modular structure, 5MP @ 30fps, motorized vari-focal lens 2.6x (3.6-9.4mm) (102.5°-38.7°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/IP6K9K, IK10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover
Camera - Network	XND-8081VZ	5MP Indoor PTRZ Dome	Wisenet X series Plus powered by Wisenet 5 network indoor vandal dome camera, modular structure, 5MP @ 30fps, motorized vari-focal lens 2.6x (3.6-9.4mm) (102.5°-38.7°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, built-in mic, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover
Camera - Network	XND-8081FZ	5MP Flush Mount PTRZ Dome	Wisenet X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, 5MP @ 30fps, motorized vari-focal lens 2.6x (3.6-9.4mm) (102.5°-38.7°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, plenum housing
Camera - Network	XNF-8010R	X-Series Indoor IR Fisheye	Wisenet X powered by Wisenet 5 network indoor fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, HLC, defog detection, DIS, 12VDC/PoE
Camera - Network	XNF-8010RW	X-Series Indoor IR Fisheye (White Color)	Wisenet X powered by Wisenet 5 network indoor fisheye (white color), 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, HLC, defog detection, DIS, 12VDC/PoE, white color
Camera - Network	XNF-8010RV	X-Series Outdoor IR Fisheye	Wisenet X powered by Wisenet 5 network outdoor vandal fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, HLC, defog detection, DIS, 12VDC/PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNF-8010RVM	X-Series Mobile IR Fisheye	Wisenet X powered by Wisenet 5 network mobile vandal fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, HLC, defog detection, DIS, For Mobile Application (M12 Connector) RJ45 to M12 adapter is NOT included, 12VDC/PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-8080RSA	5MP Stainless Steel IR Dome	Wisenet X powered by Wisenet 5 network IR stainless steel dome camera, 5MP @30fps, motorized vari-focal lens 2.4x (3.9-9.4mm) (92.1°-38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/24VAC/PoE, IP67/IP6K9K/ IK10, Nema 4X, IP6K9K, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-8080R	5MP IR Outdoor Dome	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 5MP @30fps, motorized vari-focal lens 2.4x (3.9-9.4mm) (92.1°-38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-8020R	5MP IR Outdoor Dome	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 5MP @30fps, 3.7mm fixed focal lens (97.5°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IP67, IK10
Camera - Network	XNV-8030R	5MP IR Outdoor Dome	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 5MP @30fps, 4.6mm fixed focal lens (77.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IP67, IK10
Camera - Network	XNV-8040R	5MP IR Outdoor Dome	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 5MP @30fps, 7mm fixed focal lens (50.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IP67, IK10
Camera - Network	XNO-8080R	5MP IR Bullet	Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, 5MP @30fps, motorized vari-focal lens 2.4x (3.7-9.4mm) (100.2°-38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNO-8020R	5MP IR Bullet	Wisenet X powered by Wisenet 5 network outdoor vandal bullet camera, 5MP @30fps, 3.7mm fixed lens (97.5°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/PoE, IP67, IK10, Nema 4X
Camera - Network	XNO-8030R	5MP IR Bullet	Wisenet X powered by Wisenet 5 network outdoor vandal bullet camera, 5MP @30fps, 4.6mm fixed lens (77.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/PoE, IP67, IK10, Nema 4X
Camera - Network	XNO-8040R	5MP IR Bullet	Wisenet X powered by Wisenet 5 network outdoor vandal bullet camera, 5MP @30fps, 7mm fixed lens (50.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/PoE, IP67, IK10, Nema 4X
Camera - Network	XND-8080RV	5MP Indoor IR Vandal Dome	Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, 5MP @30fps, motorized vari-focal lens 2.4x (3.9-9.4mm) (92.1°-38.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08
Camera - Network	XND-8020R	5MP Indoor IR Vandal Dome	Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, 5MP @30fps, 3.7mm fixed focal lens (97.5°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08
Camera - Network	XND-8030R	5MP Indoor IR Vandal Dome	Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, 5MP @30fps, 4.6mm fixed focal lens (77.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08
Camera - Network	XND-8040R	5MP Indoor IR Vandal Dome	Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, 5MP @30fps, 7mm fixed focal lens (50.7°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08
Camera - Network	XND-8020F	5MP Flush Mount	Wisenet X powered by Wisenet 5 network flush mount dome camera, 5MP @ 30fps, 3.7mm fixed lens (97.5°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, built-in Mic, magnetic cover, electronic D/N, SD card, hallway view, HLC, defog detection, DIS, PoE only
Camera - Network	XNB-8000	5MP Box	Wisenet X powered by Wisenet 5 network box camera, 5MP @30fps, simple focus, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true D/N, dual SD card, hallway view, HLC, defog detection, DIS using a Gyro sensor, 12VDC/24VAC/PoE
Camera - Network	QNO-8010R	5MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 5MP @ 30fps, 2.8mm fixed focal lens (104°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway view, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE

Camera - Network	QNO-8020R	5MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 5MP @ 30fps, 4.0mm fixed focal lens (79°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE
Camera - Network	QNO-C8083R	5MP IR Bullet AI camera	Wisenet Q network outdoor vandal bullet camera, 5MP @ 30fps, motorized vari-focal lens 3.2-10.2mm (H: 95°-29° / V: 69°-21°), triple codec H.265/H.264/MJPEG with Wisestream III (Based on AI engine), WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 30m (98ft), WiseMD based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/(Dis)Appear), *Audio: Selectable(mic in/line in), defocus detection, hallway View, SD card, video analytics, USB for easy installation, open platform, IP66, IK10, PoE, Operating temperature -30°C+55°C(-22°F +131°F) white color.
Camera - Network	QNO-8080R	5MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 5MP @ 30fps, motorized vari-focal lens 3.1x (3.2 - 10.0mm) (100°-31°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE
Camera - Network	QNV-C8011R	5MP IR Outdoor Vandal Dome AI Camera	Wisenet Q mini network outdoor vandal dome camera, 5MP @ 30fps, fix lens 3mm (H:100°/V: 73°), triple codec H.265/H.264/MJPEG with Wisestream III (Based on AI engine), WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 20m(65.62ft), WiseMD based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/(Dis)Appear), defocus detection, hallway View, SD card, video analytics, USB for easy installation, open platform, IP66, IK10, NEMA4X, PoE, Operating temperature -40°C+55°C(-40°F +131°F) white color.
Camera - Network	QNV-C8012	5MP Outdoor Vandal Dome AI Camera	Wisenet Q mini network outdoor vandal dome camera, 5MP @ 30fps, fix lens 2.4mm (H:123°/V: 91°), triple codec H.265/H.264/MJPEG with Wisestream III (Based on AI engine), WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 20m(65.62ft), WiseMD based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/(Dis)Appear), defocus detection, hallway View, SD card, video analytics, USB for easy installation, open platform, IP66, IK10, NEMA4X, PoE, Operating temperature -40°C+55°C(-40°F +131°F) white color.
Camera - Network	QNV-8010R	5MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 5MP @ 30fps, 2.8mm fixed focal lens (104°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE, white color
Camera - Network	QNV-8020R	5MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 5MP @ 30fps, 4.0mm fixed focal lens (79°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE, white color
Camera - Network	QNV-C8083R	5MP IR Outdoor Vandal Dome AI Camera	Wisenet Q network outdoor vandal dome camera, 5MP @ 30fps, motorized vari-focal lens 3.2-10.2mm (H: 95°-29° / V: 69°-21°), triple codec H.265/H.264/MJPEG with Wisestream III (Based on AI engine), WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 30m (98ft), WiseMD based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/(Dis)Appear), *Audio: Selectable(mic in/line in), defocus detection, hallway View, SD card, video analytics, USB for easy installation, open platform, IP66, IK10, PoE, Operating temperature -30°C+55°C(-22°F +131°F) white color. * Alarm I/O and audio is supported through an optional cable (SPP-C7400)
Camera - Network	QNV-8080R	5MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 5MP @ 30fps, motorized vari-focal lens 3.1x (3.2 - 10.0mm) (100°-31°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE, white color
Camera - Network	QND-8010R	5MP Indoor IR Dome	Wisenet Q network indoor dome camera, 5MP @ 30fps, 2.8mm fixed focal lens (104°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8020R	5MP Indoor IR Dome	Wisenet Q network indoor dome camera, 5MP @ 30fps, 4.0mm fixed focal lens (79°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8080R	5MP Indoor IR Dome	Wisenet Q network indoor dome camera, 5MP @ 30fps, motorized vari-focal lens 3.1x (3.2 - 10.0mm) (100°-31°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8011	5MP Indoor Dome	Wisenet Q mini network indoor dome camera, 5MP @ 30fps, 2.8mm fixed focal lens (104°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, IK08, PoE, white color
Camera - Network	QND-8021	5MP Indoor Dome	Wisenet Q mini network indoor dome camera, 5MP @ 30fps, 4.0mm fixed focal lens (80°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, IK08, PoE, white color
Camera - Network	QNE-C9013RL	4K Dual Light Outdoor Flat-Eye	Wisenet Q network outdoor flat-eye camera, 4K @ 30fps, 3mm fixed focal lens (H: 108° / V: 59°), triple codec H.265/H.264/MJPEG with Wisestream III, 120dB WDR, Dual Light - White LED range 30m (98ft), IR viewable length 30m (98ft), Motion Detection based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/(Dis)Appear), defocus detection, hallway View, SD card, video analytics, IP66/IP67, IK10, PoE, Operating temperature -40°C+60°C(-40°F +140°F) white color
Camera - Network	QNE-C8013RL	5MP Dual Light Outdoor Flat-Eye	Wisenet Q network outdoor flat-eye camera, 5MP @ 30fps, 3mm fixed focal lens (H: 97° / V: 53°), triple codec H.265/H.264/MJPEG with Wisestream III, 120dB WDR, Dual Light - White LED range 30m (98ft), IR viewable length 30m (98ft), Motion Detection based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/(Dis)Appear), defocus detection, hallway View, SD card, video analytics, IP66/IP67, IK10, PoE, Operating temperature -40°C+60°C(-40°F +140°F) white color
Camera - Network	QNE-8011R	5MP IR Outdoor Flat-Eye	Wisenet Q mini network outdoor flat-eye camera, 5MP @ 30fps, 2.8mm fixed focal lens (104°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, open platform, IP67, IK10, PoE, white color
Camera - Network	QNF-8010	6MP Indoor fisheye	Wisenet Q series network indoor fisheye dome camera, 6MP CMOS sensor, max resolution 2048x2048 @ 30fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 120dB, business analytics (heatmap and people counting), built-in SD card slot, PoE
Camera - Network	TNV-C8011RW	5MP AI, IR Wall Mount Panoramic Camera	T Series, wall mount AI panoramic camera, 5MP @ 30 FPS, 1.6mm fixed focal lens (HFoV: 175°, VFoV: 125°), Triple CODEC (H.265/H.264/MJPEG) with WiseStream III (based on AI engine) support, 120dB WDR, IR viewable length 15m (49ft), WiseMD based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/(Dis)Appear), virtual area (intrusion/enter/exit), virtual line (crossing/direction), Business analytics: People Counting, Queue Management, Heatmap, Occupancy, Tamper detection, built-in mic, SD card, IP66, PoE, white color
Camera - Network	TNV-8011C	5MP Compact corner mount camera	Compact corner mount camera, 5MP @ 30fps, triple codec, WDR 120dB, 2.3mm fixed, USB and CVBS, true D/N, SD cards slots, hallway view, HLC, defog detection, PoE, Audio-in/Audio-out, Wisenet open platform IP66, IP6K9K, IK10, video analytics- Defocus, Directional, Motion, Enter/Exit, Tampering, Virtual line, Audio

4MP Cameras

Camera - Network	PNM-C7083RVD	2MP X 2 AI, IR outdoor Dome	Network vandal outdoor 2CH AI IR dome camera, (2MP X 2 sensors) 4MP @ 30fps, 3-6mm(2x) (107°-56.3°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 25m (82ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS, Handover, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Audio detection, Sound classification, Appear/Disappear, FIPS 140-2, micro SD card 512GB, IP66, NEMA4X, IK10, Operating temperature: -40°C+55°C(-40°F +131°F), Power: PoE+, Metal shielded RJ-45, Hard-coated dome bubble
Camera - Network	XNP-C7310R	4MP AI Focus IR, PTZ	Powered by WN7 and AI, 4MP @ 30FPS resolution, 6.91mm-214.64mm (31x) lens with Wise AF intelligent autofocus, adaptive Wise IR (300m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG triple codec with WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Face/ Vehicle/License plate), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), AI object auto-tracking (Person/Vehicle) with target lock tracking, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IP67, IK10, NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), FIPS 140-2, PoE+H/PoE injector included, Operating Temperature -50°C+55°C(-58°F +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	PNM-7082RVD	2MP X 2, IR outdoor Dome	Network vandal outdoor 2CH IR dome camera, (2MP X 2 sensors) 4MP @ 30fps, 3-6mm(2x) (107°-56.3°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 25m (82ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS, Handover, IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Directional detection, Motion detection, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual Line, Audio detection, Sound classification, FIPS 140-2, micro SD card 512GB, IP66, NEMA4X, IK10, Operating temperature: -40°C+55°C(-40°F +131°F), Power: PoE+, Metal shielded RJ-45, Hard-coated dome bubble
Camera - Network	PNM-7002VD	2MP X 2 outdoor Dome	Network vandal outdoor Multi-sensor Multi-Directional dome camera, (2MP X 2 sensors sold separately) 4MP @ 60fps, modular lenses from 2.4, 2.8, 3.6 and 6mm lenses, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, built in analytics, 4x SD card, hallway view, HLC, defog detection, DIS, PoE, IP66/IK10, -40°C +55°C (-40°F +131°F)
Camera - Network	ANO-L7012R	4MP IR Bullet	Wisenet A Series bullet camera, 4MP @ 30 FPS, 3mm fixed focal lens, WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 20m(65.62ft), day & night (ICR), FoV H: 98.3° / V: 54.2°, virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.
Camera - Network	ANO-L7022R	4MP IR Bullet	Wisenet A Series bullet camera, 4MP @ 30 FPS, 4mm fixed focal lens, WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 25m(82.02ft), day & night (ICR), FoV H: 78.3° / V: 42.9°, virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.
Camera - Network	ANO-L7082R	4MP IR Bullet	Wisenet A Series bullet camera, 4MP @ 30 FPS, motorized varifocal lens 3.1x (3.3-10.3mm) (94.8° - 28.1°), WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m (98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.
Camera - Network	ANV-L7012R	4MP IR Vandal Dome	Wisenet A Series outdoor vandal dome camera, 4MP @ 30 FPS, 3mm fixed focal lens, WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 20m(65.62ft), day & night (ICR), FoV H: 98.3° / V: 54.2°, virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, IK10, PoE, white.

Camera - Network	ANV-L7082R	4MP IR Vandal Dome	Wisenet A Series outdoor vandal dome camera, 4MP @ 30 FPS, motorized varifocal lens 3.1x (3.3-10.3mm) (94.8° - 28.1°), WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m (98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, IK10, PoE, white.
Camera - Network	ANE-L7012L	4MP White Light Turret Camera	Wisenet A Series White Light turret camera, 4MP @ 30 FPS, 3mm fixed focal lens, WiseStream II, Triple codec (H.265/H.264/MJPEG), 120dB WDR, 24h Color mode, FoV H: 98.3° / V: 54.2°, virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.
Camera - Network	ANE-L7012R	4MP Turret Camera	Wisenet A Series turret camera, 4MP @ 30 FPS, 3mm fixed focal lens, WiseStream II, Triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 20m(65.62ft), day & night (ICR), FoV H: 98.3° / V: 54.2°, virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.
Camera - Network	QND-7012R	4MP IR Dome	Wisenet Q network indoor dome camera, 4MP @30fps, 2.8mm fixed focal lens (107°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). PoE/12VDC, white color
Camera - Network	QND-7022R	4MP IR Dome	Wisenet Q network indoor dome camera, 4MP @30fps, 4mm fixed focal lens (78°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). PoE/12VDC, white color
Camera - Network	QND-7032R	4MP IR Dome	Wisenet Q network indoor dome camera, 4MP @30fps, 6mm fixed focal lens (49°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). PoE/12VDC, white color
Camera - Network	QDC-7082R	4MP IR Dome	Wisenet Q network indoor dome camera, 4MP @30fps, motorized vari-focal lens 3.1x (3.2 - 10.0mm) (109°-33.2°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 20m (65.62), Motion detection, Tampering, Defocus detection, Hallway view, LDC support, Built-in mic (One way audio), Micro SD/SDHC/SDXC card 1 slot (Max. 128GB), PoE/12VDC (White color)
Camera - Network	QNV-7012R	4MP IR Vandal Dome	Wisenet Q network outdoor vandal dome camera, 4MP @30fps, 2.8mm fixed focal lens (107°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-7022R	4MP IR Vandal Dome	Wisenet Q network outdoor vandal dome camera, 4MP @30fps, 4mm fixed focal lens (78°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-7032R	4MP IR Vandal Dome	Wisenet Q network outdoor vandal dome camera, 4MP @30fps, 6mm fixed focal lens (49°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-7082R	4MP IR Vandal Dome	Wisenet Q network outdoor vandal dome camera, 4MP @30fps, motorized vari-focal lens 3.1x (3.2 - 10.0mm) (109°-33.2°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 30m (98.42), Motion detection, Tampering, Defocus detection, Hallway view, LDC support, One way audio - Line in, Micro SD/SDHC/SDXC card 1 slot (Max. 128GB), IP66, IK10, PoE/12VDC (White color)
Camera - Network	QNO-7012R	4MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 4MP @30fps, 2.8mm fixed focal lens (107°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). IP66, IK10, PoE/12VDC
Camera - Network	QNO-7022R	4MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 4MP @30fps, 4mm fixed focal lens (78°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). IP66, IK10, PoE/12VDC
Camera - Network	QNO-7032R	4MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 4MP @30fps, 6mm fixed focal lens (49°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB). IP66, IK10, PoE/12VDC
Camera - Network	QNO-7082R	4MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 4MP @30fps, motorized vari-focal lens 3.1x (3.2 - 10.0mm) (109°-33.2°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 30m (98.42), Motion detection, Tampering, Defocus detection, Hallway view, LDC support, One way audio - Line in, Micro SD/SDHC/SDXC card 1 slot (Max. 128GB), IP66, IK10, PoE/12VDC
Camera - Network	XND-C7083RV	4MP IR Indoor Vandal Dome AI Camera	Powered by WN7, Indoor Network AI IR Dome Camera, 4MP resolution @ 60FPS (WDR off)/30FPS (WDR on), 2.8-10mm(3.6x) (109.7°-30.4°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP52, IK08, Operating temperature: -10 °C ~ 50 °C(14°F ~ +122°F), Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XNO-C7083R	4MP IR Bullet AI camera	Powered by WN7, Outdoor Network AI IR Bullet Camera, 4MP resolution @ 60FPS (WDR off)/30FPS (WDR on), 2.8-10mm(3.6x) (109.7°-30.4°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, UL CAP certified, P66, IP67, NEMA4X, IK10, Operating temperature 40°C~+55°C(-40°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XNV-C7083R	4MP IR Outdoor Vandal Dome AI Camera	Powered by WN7, Outdoor Network AI IR Vandal Dome Camera, 4MP resolution @ 60FPS (WDR off)/30FPS (WDR on), 2.8-10mm(3.6x) (109.7°-30.4°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (120dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine : Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, P66, IP67, NEMA4X, IK10, Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45

3MP Cameras

Camera - Network	TNV-C7013RC	3MP AI IR Vandal Corner Camera	Wisenet T network outdoor AI, IR corner mount camera, 3MP @ 30fps, fixed lens 2.39mm (H:128°, V:100°), 940nm Wise IR 15m(49.21ft), built-in mic, triple codec H.265/H.264/MJPEG with, extreamWDR 120dB, Improve image quality based on AI (WiseStreamIII, WiseNRII, prefer shutter control) Classified object type: Person/Face/License Plate/Vehicle (car, truck, bus, bicycle, motorcycle), Analytics events based on AI engine: IVA (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Clothes color detection, single SD card, HLC, defog detection, DIS, PoE, IP66, IP6K9K, IK10+, Anti-ligature design, Operating Temperature -10°C ~ +55°C (14°F ~ +131°F)
Camera - Network	TNV-7011RC	3MP IR Vandal Corner Camera	Wisenet T powered by Wisenet 5 network outdoor IR corner mount camera, 3MP, 2048*1536 @ 30fps, 2.8mm fixed lens (102°*75°), 940nm IR 32', built-in mic, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, advanced video analytics and business analytics, single SD card, HLC, defog detection, DIS, PoE, IP66,Nema 4x, IK10

2MP Cameras

Camera - Network	PND-A6081RF	2MP IR Indoor Flush Mount Dome AI Camera	2MP Network AI IR Dome Camera, Max. 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wise IR, Day & Night (ICR), WDR (120dB), WiseNR II (Using AI engine), H.265, H.264, MJPEG, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI [Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot] People counting, Heatmap, Queue management based on AI, TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble, IP52, IK10, Plenum rate, Modular structure for easy Install, PoE+
Camera - Network	PND-A6081RV	2MP IR Indoor Vandal Dome AI Camera	2MP Network AI IR Dome Camera, Max. 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wise IR, Day & Night (ICR), WDR (120dB), WiseNR II (Using AI engine), H.265, H.264, MJPEG, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI [Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot] People counting, Heatmap, Queue management based on AI, TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble, IP52, IK10, Modular structure for easy Install, PoE+
Camera - Network	PNV-A6081R-E2T	2MP IR Outdoor Vandal Dome, SolidEdge Camera with 2TB SSD	2MP Network AI IR Vandal Dome Camera with built-in 2TB SSD and pre-installed WAVE server and ability to record up to 5 additional cameras. Max. 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 4.38-9.33mm(2.13x) motorized varifocal lens, 0Lux (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wise IR, Day & Night (ICR), WDR (120dB), WiseNR II, H.265, H.264, MJPEG, WiseStream II, People counting, Heatmap, Queue management, TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble/IP66, IP67, IP6K9K, IK10+, NEMA4X, Modular structure for easy Install, PoE+; 2TB SSD included, Pre-Installed WAVE server with 1CH Pro license
Camera - Network	PNV-A6081R-E1T	2MP IR Outdoor Vandal Dome, SolidEdge Camera with 1TB SSD	2MP Network AI IR Vandal Dome Camera with built-in 1TB SSD and pre-installed WAVE server and ability to record up to 5 additional cameras. Max. 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 4.38-9.33mm(2.13x) motorized varifocal lens, 0Lux (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wise IR, Day & Night (ICR), WDR (120dB), WiseNR II, H.265, H.264, MJPEG, WiseStream II, People counting, Heatmap, Queue management, TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble/IP66, IP67, IP6K9K, IK10+, NEMA4X, Modular structure for easy Install, PoE+; 1TB SSD included, Pre-Installed WAVE server with 1CH Pro license
Camera - Network	PNV-A6081R	2MP IR Outdoor Vandal Dome AI Camera	2MP Network AI IR Vandal Dome Camera, Max. 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wise IR, Day & Night (ICR), WDR (120dB), WiseNR II (Using AI engine), H.265, H.264, MJPEG, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI [Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot] People counting, Heatmap, Queue management based on AI, TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble/IP66, IP67, IP6K9K, IK10+, NEMA4X, Modular structure for easy Install, PoE+
Camera - Network	PNO-A6081R	2MP IR Bullet AI camera	2MP Network AI IR Bullet Camera, Max. 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wise IR, Day & Night (ICR), WDR (120dB), WiseNR II (Using AI engine), H.265, H.264, MJPEG, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI [Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot] People counting, Heatmap, Queue management based on AI, TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgery, IP66, IP67, IK10, NEMA4X, PoE+

Camera - Network	PNB-A6001	2MP Box AI camera	2MP Network AI Box Camera, Max. 2MP resolution, Up to 120fps, 0.006Lux@F1.2, (Color), 0.0006Lux@F1.2, 1/30sec. (B/W), Day & Night (ICR), WDR (120dB), WiseNR II (Using AI engine), H.265, H.264, MJPEG, WiseStream II, WiseStream II (Using AI engine), Video Analytics based on AI (Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot) People counting, Heatmap, Queue management based on AI, TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgerv, PoE+
Camera - Network	XND-C6083RV	2MP IR Indoor Vandal Dome AI Camera	Powered by WN7, Indoor Network AI IR Dome Camera, 2MP resolution @ 60FPS, 2.8-12mm(4.3x) (119.5°-27.9°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP52, IK08, Operating temperature: -10 °C ~ 50 °C(14°F ~ +122°F), Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XNV-C6083R	2MP IR Outdoor Vandal Dome AI Camera	Powered by WN7, Outdoor Network AI IR Vandal Dome Camera, 2MP resolution @ 60FPS, 2.8-12mm(4.3x) (119.5°-27.9°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, P66, IP67, NEMA4X, IK10, Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XND-6083RV	2MP IR Indoor Vandal Dome AI Camera	Powered by WN7, X-Plus series, Indoor Network AI IR Dome Camera, 2MP resolution @ 120FPS, 2.8-12mm(4.3x) (119.5°-27.9°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), IP52, IK10, Operating temperature: -25 °C ~ 60 °C(-13°F ~ +140°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNV-6083RZ	2MP IR Outdoor Vandal Dome AI, PTRZ Camera	Powered by WN7, X-Plus series, Outdoor Network AI IR Vandal Dome Camera, 2MP resolution @ 120FPS, 2.8-12mm (4.3x) (120°-27°) motorized varifocal lens, Remote lens adjustment (PTRZ), Triple codec (H.265/H.264/MJPEG), IR Viewable Length: 15m(49.21ft) / 30m(98.43ft) based on scene, USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), IP66, IP67, IP6K9K, NEMA4X, IK10+, Operating temperature: -50°C~+55°C(-58°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNV-6083R	2MP IR Outdoor Vandal Dome AI Camera	Powered by WN7, X-Plus series, Outdoor Network AI IR Vandal Dome Camera, 2MP resolution @ 120FPS, 2.8-12mm(4.3x) (119.5°-27.9°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10+, Operating temperature: -50°C~+55°C(-58°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNB-6003	2MP Box AI Camera	Powered by WN7, X-Plus series, Box Camera, 2MP resolution @ 120FPS, Triple codec (H.265/H.264/MJPEG), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), Operating temperature: -10 °C ~ 55 °C(14°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNP-C6403RW	2MP AI IR, Wiper PTZ	Powered by WN7 PTZ Plus with AI, 2MP @ 60FPS resolution, 4.25mm-170mm (40x) lens, built in wiper and adaptive Wise IR (200m), extreme WDR 150dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Analytics events based on AI engine: Object detection (Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), Object auto-tracking (Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IK10, NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), FIPS 140-2, PoE++/HPoE injector included, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-6400RW	2MP IR, Wiper PTZ	Powered by WN7, 2MP @ 60FPS resolution, 4.25mm-170mm (40x) lens, built in wiper and Wise IR (200m), extreme WDR 150dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking(Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), PoE++/HPoE injector included, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-C6403R	2MP AI IR PTZ	Powered by WN7 PTZ Plus with AI, 2MP @ 60FPS resolution, 4.25mm-170mm (40x) lens, adaptive Wise IR (200m), extreme WDR 150dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Analytics events based on AI engine: Object detection (Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), Object auto-tracking (Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IK10, NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), FIPS 140-2, PoE++/HPoE injector included, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-6400R	2MP, 40x, IR PTZ camera	Powered by WN7, 2MP @ 60FPS resolution, 4.25mm-170mm (40x) lens, Wise IR (200m), extreme WDR 150dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking(Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, NEMA-TS 2 (2.2.7, 2.2.8, 2.2.9), PoE++/HPoE injector included, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-C6403	2MP AI PTZ	Powered by WN7 PTZ Plus with AI, 2MP @ 60FPS resolution, 4.25mm-170mm (40x) lens, extreme WDR 150dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Analytics events based on AI engine: Object detection (Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), Object auto-tracking (Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IK10, NEMA4X, NEMA-TS 2(2.2.7, 2.2.8, 2.2.9), FIPS 140-2, Power: PoE+, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XNP-6400	2MP, 40x PTZ camera	Powered by WN7, 2MP @ 60FPS resolution, 4.25mm-170mm (40x) lens, extreme WDR 150dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, IK10, NEMA4X, NEMA-TS 2 (2.2.7, 2.2.8, 2.2.9), Power: PoE+, Operating Temperature -40°C~+55°C(-40°F ~ +131°F), (Compatible with I/O Box SPM-4210)
Camera - Network	XND-6081REV	2MP Indoor Dome, PoE extender camera	Wisenet X powered by Wisenet 5 network IR indoor dome camera with PoE Extender, PoE+ in PoE out, 2MP @60fps, Motorized Varifocal Lens (2.8mm -12mm), triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 150dB, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), PoE/PoE+, IP52, IK10, -25°C ~ +60°C (-13°F ~ +140°F)
Camera - Network	XNV-6081RE	2MP Outdoor Dome, PoE extender camera	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera with PoE Extender, PoE+ in PoE out, 2MP @60fps, Motorized Varifocal Lens (2.8mm -12mm), triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 150dB, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), PoE/PoE+, IP66/IP67/IP6K9K, IK10+, NEMA4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XNV-6081R	2MP IR Outdoor Dome	Wisenet X series Plus powered by Wisenet 5 IR network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/IP6K9K, IK10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover
Camera - Network	XND-6081RF	2MP IR Flush Mount Dome	Wisenet X series Plus powered by Wisenet 5 IR network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, plenum housing
Camera - Network	XND-6081RV	2MP IR Indoor Dome	Wisenet X series Plus powered by Wisenet 5 IR network indoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, built-in mic, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover
Camera - Network	XNV-6081	2MP Outdoor Dome	Wisenet X series Plus powered by Wisenet 5 network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/IP6K9K, IK10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover
Camera - Network	XND-6081V	2MP Indoor Vandal Dome	Wisenet X series Plus powered by Wisenet 5 network indoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, built-in mic, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover
Camera - Network	XNV-6081Z	2MP Outdoor PTRZ Dome	Wisenet X series Plus powered by Wisenet 5 network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/IP6K9K, IK10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover

Camera - Network	XND-6081VZ	2MP Indoor PTRZ Dome	Wisenet X series Plus powered by Wisenet 5 network indoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, built-in mic, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover
Camera - Network	XND-6081FZ	2MP Flush Mount PTRZ Dome	Wisenet X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, plenum housing
Camera - Network	XNP-6550RH	2MP IR 55x PTZ	Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 55X optical zoom lens (4.75mm ~ 261.4mm) (58.6° ~ 1.23°), Pan: 360° endless. Tilt: -5° ~ 185°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, built-in IR 1640ft (500m), USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, HLC, defog (optical) DIS(Gyro), 24VAC/HPoE, IP66/IK10, -58°F ~ +131°F W/ 24VAC power supply
Camera - Network	XNP-6120H	2MP 12X PTZ	Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 12X optical zoom lens (5.2mm ~ 62.4mm) (54.58° ~ 5.30°), Pan: 360° endless. Tilt: -5° ~ 185°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, HLC, defog detection, DIS(Gyro), 12VDC/PoE, IP66, IK10, -22°F ~ 131°F
Camera - Network	XNP-6040H	2MP 4.3X PTZ	Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 4.3X optical zoom lens (2.8mm ~ 12mm) (119.5° ~ 27.9°), Pan: 0°-350°. Tilt: 0° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, HLC, defog detection, DIS(Gyro), 12VDC/PoE, IP66, IK10, -22°F ~ 131°F
Camera - Network	XNO-6085R	eXtraLUX IR Bullet	Wisenet X powered by Wisenet 5 network IR outdoor vandal bullet camera, eXtraLUX features 1/2" sensor with F0.94 Lens, back box, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.0x (4.1-16.4mm) (100°-26.2.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 229', true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), backbox included, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6085	eXtraLUX Outdoor PTRZ Dome	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, eXtraLUX features 1/2" sensor with F0.94 Lens, PTRZ, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.0x (4.1-16.4mm) (100°-26.2.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNB-6005	eXtraLUX Box Camera	Wisenet X powered by Wisenet 5 network box camera, eXtraLUX features 1/2" sensor, 2MP, Full HD(1080p) @60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true D/N, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE
Camera - Network	XNV-6123R	2MP 12X IR outdoor Dome	Powered by WN7, Outdoor Network AI IR 12x Zoom Vandal Dome Camera, 2MP @ 120 FPS, 5.2-62.4mm(12x) (54.58°-5.30°) zoom lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 90m (295.28ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2 certified, P66, IP67, NEMA4X, IK10, Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XNV-6120R	2M 12X IR outdoor Dome	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 12X optical zoom lens (5.2mm ~ 62.4mm) (54.58° ~ 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 229', true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6120R/LPR	Low Speed LPR Outdoor IR Dome	Wisenet X powered by Wisenet 5 network IR outdoor Low Speed LPR dome camera for Parking Lots; Drive-thrus; and Entry Gates up to 35MPH, 2MP, Full HD(1080p) @60fps, 12X optical zoom lens (5.2mm ~ 62.4mm) (54.58° ~ 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, backbox included, 12VDC/24VAC/PoE, IP67, IK10, NEMA4X, -40°C ~ +55°C (-40°F ~ +131°F) CARE IS RECOMMENDED IN SELECTING MOUNTING LOCATION - See Quick Start Guide Step 1. DEALER TRAINING OR HANWHHA ENGINEER CONSULT RECOMMENDED BEFORE INSTALLING.
Camera - Network	XNV-6120	2M 12X Outdoor Dome	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 12X optical zoom lens (5.2mm ~ 62.4mm) (54.58° ~ 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNO-6123R	2MP 12X IR Bullet	Powered by WN7, Outdoor Network AI IR 12x Zoom Bullet Camera, 2MP @ 120 FPS, 5.2-62.4mm(12x) (54.58°-5.30°) zoom lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 90m (295.28ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2 certified, P66, IP67, NEMA4X, IK10, Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XNO-6120R	2M 12X IR Bullet	Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, 2MP, Full HD(1080p) @60fps, 12X optical zoom lens (5.2mm ~ 62.4mm) (54.58° ~ 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 229', true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), backbox included, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNO-6120R/LPR	Low Speed LPR IR Bullet	Wisenet X powered by Wisenet 5 network IR outdoor Low Speed LPR bullet camera for Parking Lots; Drive-thrus; and Entry Gates up to 35MPH, 2MP, Full HD(1080p) @60fps, 12X optical zoom lens (5.2mm ~ 62.4mm) (54.58° ~ 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, backbox included, 12VDC/24VAC/PoE, IP67, IK10, NEMA4X, -40°C ~ +55°C (-40°F ~ +131°F) CARE IS RECOMMENDED IN SELECTING MOUNTING LOCATION - See Quick Start Guide Step 1. DEALER TRAINING OR HANWHHA ENGINEER CONSULT RECOMMENDED BEFORE INSTALLING.
Camera - Network	XNV-6080RSA	2MP Stainless Steel IR Dome	Wisenet X powered by Wisenet 5 network IR stainless steel dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, IP68, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6080R	2MP IR Outdoor Dome	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6080	2MP Outdoor Dome	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6010	2MP Outdoor Dome	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (139°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IP67, IK10
Camera - Network	XNV-6020R	2MP IR Outdoor Dome	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 4mm fixed lens (88.6°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IP67, IK10
Camera - Network	XNV-6011	2MP Compact Vandal Dome	Wisenet X powered by Wisenet 5 network outdoor compact vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.8mm fixed lens (112°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and business analytics, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, Nema 4X, IK10
Camera - Network	XNV-6011W	2MP Compact Vandal Dome (White Color)	Wisenet X powered by Wisenet 5 network outdoor compact vandal dome camera (white color), 2MP, Full HD(1080p) @60fps, 2.8mm fixed lens (112°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and business analytics, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, Nema 4X, IK10, white color
Camera - Network	XNO-C6083R	2MP IR Bullet AI camera	Powered by WN7, Outdoor Network AI IR Bullet Camera, 2MP @ 60FPS, 2.8-12mm(4.3x) (119.5°-27.9°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, UL CAP certified, P66, IP67, NEMA4X, IK10, Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XNO-6083R	2MP IR Bullet AI Camera	Powered by WN7, X-Plus series, Outdoor Network AI IR Bullet Camera, 2MP @ 120FPS, 2.8-12mm(4.3x) (119.5°-27.9°) motorized varifocal lens, Triple codec (H.265/H.264/MJPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coated window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FIPS 140-2, 2x micro SD card (512GB x2), P66, IP67, NEMA4X, IK10, Operating temperature: -50°C~+60°C(-58°F ~ +140°F), Power: PoE+/12VDC, Metal shielded RJ-45
Camera - Network	XNO-6080R	2MP IR Bullet	Wisenet X powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)

Camera - Network	XNO-6010R	2MP IR Bullet	Wisenet X powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed focal lens (139"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 65', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/PoE, IP67, IK10, Nema 4X
Camera - Network	XNO-6020R	2MP IR Bullet	Wisenet X powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP, Full HD(1080p) @60fps, 4mm fixed focal lens (88.6"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/PoE, IP67, IK10, Nema 4X
Camera - Network	XND-6080RV	2MP Indoor IR Vandal Dome	Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5"-27.9"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08
Camera - Network	XND-6080V	2MP Indoor Vandal Dome	Wisenet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 4.3x (2.8-12mm) (119.5"-27.9"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08
Camera - Network	XND-6010	2MP Indoor Vandal Dome	Wisenet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (139"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08
Camera - Network	XND-6020R	2MP Indoor IR Vandal Dome	Wisenet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 4mm fixed lens (88.6"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics and business analytics, high powered IR LEDs range of 98', true D/N, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IK08
Camera - Network	XND-6011F	2MP Flush Mount	Wisenet X powered by Wisenet 5 network flush mount dome camera, 2MP, Full HD(1080p) @60fps, 2.8mm fixed lens (112"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, built-in Mic, magnetic cover, electronic D/N, SD card, hallway view, HLC, defog detection, DIS, PoE only
Camera - Network	XNV-6013M	2MP Mobile Vandal Dome	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.8mm fixed lens (107.4"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, electrical D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X, -40°C ~ +60°C (-40°F ~ +140°F) This camera was designed to be mounted outside of the vehicle, M12 connector (M12 to RJ45 is not included)
Camera - Network	XNV-6012	2MP Mobile Vandal Dome	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (135.4"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, electrical D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X
Camera - Network	XNV-6012M	2MP Mobile Vandal Dome	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (135.4"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, electrical D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X, M12 connector (M12 to RJ45 is not included)
Camera - Network	XNV-6022R	2MP Mobile Vandal Dome	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 3.6mm fixed lens (94.8"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, IR LEDs range of 49', true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X
Camera - Network	XNV-6022RM	2MP Mobile Vandal Dome	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 3.6mm fixed lens (94.8"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, IR LEDs range of 49', true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X, M12 connector (M12 to RJ45 is not included)
Camera - Network	XNZ-6320A	2MP 32x Zoom Box	Wisenet X powered by Wisenet 5 network zoom box camera, 2MP, Full HD(1080p) @60fps, 32X optical zoom lens (4.44mm ~ 142.6mm) (61.8" ~ 2.19"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, SFP slot, advanced video analytics and sound classification, true D/N, dual SD card, HLC, defog detection, DIS(Gyro), 12VDC/PoE
Camera - Network	XNZ-L6320A	2MP 32x Zoom Box	Wisenet X powered by Wisenet 5 network zoom box camera, 2MP, Full HD(1080p) @60fps, 32X optical zoom lens (4.44mm ~ 142.6mm) (61.8" ~ 2.19"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, advanced video analytics and sound classification, true D/N, built in SD card slot, HLC, defog detection, 12VDC/PoE
Camera - Network	XNB-6000	2MP Box	Wisenet X powered by Wisenet 5 network box camera, 2MP, Full HD(1080p) @60fps, simple focus, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true D/N, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), 12VDC/24VAC/PoE
Camera - Network	XNB-6002	2MP Covert Camera Main Module	Powered by Wisenet 7 covert camera body, 2MP, full HD (1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F ~ 131°F, lens module is not included, TPM 2.0 (FIPS 140-2 level 2) Compatible lens modules (SLA-T2480A, SLA-T2480AV, SLA-T4680A, SLA-T4680AV, SLA-T1080FA)
Camera - Network	XNB-6001	2MP Covert Camera Main Module	Wisenet X powered by Wisenet 5 covert camera body, 2MP, full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F ~ 131°F, lens module is not included compatible lens modules (SLA-T2480, SLA-T2480V, SLA-T4680, SLA-T4680V, SLA-T1080F, SLA-T4680D, SLA-T4680DS, SLA-T4680DW)
Camera - Network	XNV-L6080R	2MP IR Outdoor Dome	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 3.1x (3.2-10mm) (109"-33.2"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 98.43', true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-L6080	2MP Outdoor Dome	Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 3.1x (3.2-10mm) (109"-33.2"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XND-L6080RV	2MP Indoor IR Vandal Dome	Wisenet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 3.1x (3.2-10mm) (109"-33.2"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 98.43', true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IK08
Camera - Network	XND-L6080V	2MP Indoor Vandal Dome	Wisenet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 3.1x (3.2-10mm) (109"-33.2"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IK08
Camera - Network	XNO-L6080R	2MP IR Bullet	Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 3.1x (3.2-10mm) (109"-33.2"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 98.43', true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	TNB-6030	PVM Camera	PVM camera powered by Wisenet 5, 1080p (1920x1080), micro HDMI output, 16:9 aspect ratio, face detection display for visual deterrent, customizable text overlay, 4.6mm fixed lens(73.8"H), 150dB WDR, H.265/H.264/MJPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode
Camera - Network	TNO-6010M	Front Facing Mobile Camera	Wisenet T network mobile front facing camera, 2MP @ 60fps, 2.8mm fixed focal lens (113"), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, true D/N, SD card, hallway view, HLC, defog detection, DIS (Gyro), PoE, IP66, IK10, M12 connector (M12 to RJ45 is not included)
Camera - Network	QNO-6012R	2MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, 2.8mm fixed focal lens (113"), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNO-6012R1	2MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, 2.8mm fixed focal lens (113"), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNO-6022R	2MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, 4.0mm fixed focal lens (87"), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNO-6022R1	2MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, 4.0mm fixed focal lens (87"), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNO-6082R	2MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109"-33"), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNO-6082R1	2MP IR Bullet	Wisenet Q network outdoor vandal bullet camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109"-33"), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNV-6012R	2MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113"), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-6012R1	2MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113"), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color

Camera - Network	QNV-6022R	2MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-6022R1	2MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-6024RM	2M Mobile IR Flat Camera	Wisenet Q network Mobile IR vandal dome camera, 2MP, Full HD(1080p) 30fps, triple codec H.265/H.264/MJPEG with Wisestream technology, Fixed focal Lens 3.6mm, Built in Mic, M12 Network connectors (M12 connector to RJ-45 adaptor is not included), hallway View, 120dB WDR, built-in IR range of 32.8', true D/N, built-in SD card slot, IP66, IK10
Camera - Network	QNV-6082R	2MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 – 10.0mm) (109°-33°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-6082R1	2MP IR Outdoor Dome	Wisenet Q network outdoor vandal dome camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 – 10.0mm) (109°-33°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QND-6012R	2MP IR Indoor Dome	Wisenet Q network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC, white color
Camera - Network	QND-6012R1	2MP IR Indoor Dome	Wisenet Q network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, PoE/12VDC, white color
Camera - Network	QND-6022R	2MP IR Indoor Dome	Wisenet Q network indoor dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC, white color
Camera - Network	QND-6022R1	2MP IR Indoor Dome	Wisenet Q network indoor dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, PoE/12VDC, white color
Camera - Network	QND-6082R	2MP IR Indoor Dome	Wisenet Q network indoor dome camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 – 10.0mm) (109°-33°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC, white color
Camera - Network	QND-6082R1	2MP IR Indoor Dome	Wisenet Q network indoor dome camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.2 – 10.0mm) (109°-33°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, no audio in/out, SD card, video analytics, CVBS, open platform, PoE/12VDC, white color
Camera - Network	QND-6011	2MP Indoor Dome	Wisenet Q mini network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, IK08, PoE, white color
Camera - Network	QND-6021	2MP Indoor Dome	Wisenet Q mini network indoor dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265/H.264/MJPEG with Wisestream II, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, IK08, PoE, white color
Camera - Network	LNV-6072R	2MP IR Vandal Dome	L series outdoor vandal dome camera, 2MP @ 30fps, vari-focal lens 3.1x (3.2 – 10mm) (101.6° – 31.3°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White
Camera - Network	LNV-6012R	2MP IR Vandal Dome	L series outdoor vandal dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (102°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White
Camera - Network	LNV-6022R	2MP IR Vandal Dome	L series outdoor vandal dome camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White
Camera - Network	LND-6072R	2MP IR Dome	L series indoor dome camera, 2MP @ 30fps, vari-focal lens 3.1x (3.2 – 10mm) (101.6° – 31.3°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	LND-6012R	2MP IR Dome	L series indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (102°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	LND-6022R	2MP IR Dome	L series indoor dome camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	LNO-6072R	2MP IR Bullet	L series outdoor bullet camera, 2MP @ 30fps, vari-focal lens 3.1x (3.2 – 10mm) (101.6° – 31.3°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, PoE, White
Camera - Network	LNO-6012R	2MP IR Bullet	L series outdoor bullet camera, 2MP @ 30fps, 2.8mm fixed focal lens (102°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, PoE, White
Camera - Network	LNO-6022R	2MP IR Bullet	L series outdoor bullet camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, PoE, White
Camera - Network	ANO-L6012R	2MP IR Bullet	Wisenet A Series bullet camera, 2MP @ 30 FPS, 2.8mm fixed focal lens, FoV H: 113.7° / V: 61.5°, WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m(98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.
Camera - Network	ANO-L6022R	2MP IR Bullet	Wisenet A Series bullet camera, 2MP @ 30 FPS, 4mm fixed focal lens, FoV H: 84.3° / V: 45.6° WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m(98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.
Camera - Network	ANO-L6082R	2MP IR Bullet	Wisenet A Series bullet camera, 2MP @ 30FPS, motorized varifocal lens 3.1x (3.3-10.3mm) (105.2°- 30.6°), WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m(98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.
Camera - Network	ANV-L6012R	2MP IR Vandal Dome	Wisenet A Series outdoor vandal dome camera, 2MP @ 30 FPS, 2.8mm fixed focal lens, FoV H: 113.7° / V: 61.5°. WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m(98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, IK10, PoE, white.
Camera - Network	ANV-L6023R	2MP IR Vandal Dome	Wisenet A Series outdoor vandal mini dome camera, 2MP @ 30 FPS, 3.6mm fixed focal lens, FoV H: 94.8° / V: 49.3°. WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 15m(49.21ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.
Camera - Network	ANV-L6082R	2MP IR Vandal Dome	Wisenet A Series outdoor vandal dome camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.3-10.3mm) (105.2°- 30.6°), WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m(98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, IK10, PoE, white.
Camera - Network	ANE-L6012R	2MP Turret Camera	Wisenet A Series turret camera, 2MP @ 30 FPS, 3mm fixed focal lens, FoV H: 107.7° / V: 59.0°. WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 20m(65.62ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.
Camera - Network	XNB-H6241A	2MP Network ATM Camera Kit	Wisenet X powered by Wisenet 5 network ATM camera, 2MP, Full HD(1080p) 60fps, 2.4mm fixed lens (138°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F - 131°F, cable Length is 8m (26 feet).
Camera - Network	XNB-H6244A	2MP Network ATM Camera Kit	Wisenet X Powered by Wisenet 7 network camera, ATM kit, 2MP, Full HD(1080p) 60fps, 2.4mm fixed lens (138°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F - 131°F, TPM 2.0 (FIPS 140-2 level 2), cable Length is 1.5m (4.9 feet). (Package includes XNB-6002+SLA-T2415A+STB-2000)
Camera - Network	XNB-H6240A	2MP Network ATM Camera Kit	Wisenet X powered by Wisenet 5 network ATM camera, 2MP, Full HD(1080p) 60fps, 2.4mm fixed lens (138°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F - 131°F, cable Length is 1.5m (4.9 feet).
Camera - Network	XNB-H6461H	2MP Pinhole Height Strip Camera Kit	Wisenet X powered by Wisenet 5 network pinhole camera with height strip housing, 2MP, Full HD(1080p) 60fps, 4.6mm fixed lens (73°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F - 131°F, cable Length is 8m (26 feet).
Camera - Network	XNB-H6282B	2MP Bandit Barrier	Wisenet X Powered by Wisenet 7 network Bandit Barrier camera, 2MP, Full HD(1080p) 60fps, 2.8mm fixed lens (107.4°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F - 131°F, TPM 2.0 (FIPS 140-2 level 2), cable Length is 8m (26 feet). (Package includes XNB-6002 and SLA-T2680BA)
Camera - Network	XNB-H6280B	2MP Bandit Barrier	Wisenet X powered by Wisenet 5 network Bandit Barrier camera, 2MP, Full HD(1080p) 60fps, 2.8mm fixed lens (107.4°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F - 131°F, cable Length is 1.5m (4.9 feet).
Camera - Network	QNP-6230	2MP 23x PTZ	Wisenet Q network indoor PTZ camera, 2MP, Full HD(1080p) 30fps, H.265/H.264/MJPEG, Optical Zoom Lens 23x (4.4-102.1mm), 120dB WDR, true D/N, 500°/sec Pan, SD/SDHC/SDXC, 24VAC/PoE+
Camera - Network	QNP-6250	2MP 25x PTZ	Wisenet Q network indoor PTZ camera, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44-111mm (25x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, white color
Camera - Network	QNP-6250H	2MP 25x PTZ	Wisenet Q network outdoor PTZ camera, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44-111mm (25x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, IP66, IK10, NEMA4X, white color
Camera - Network	QNP-6250R	2MP IR 25x PTZ	Wisenet Q network IR PTZ camera, IR range of up to 328ft, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44-111mm (25x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, IP66, IK10, NEMA4X, white color

Camera - Network	QNP-6320	2MP 32x PTZ	Wisenet Q network indoor PTZ camera, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44-142.6mm (32x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, white color
Camera - Network	QNP-6320H	2MP 32x PTZ	Wisenet Q network outdoor PTZ camera, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44-142.6mm (32x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, IP66, IK10, NEMA4X, white color
Camera - Network	QNP-6320R	2MP IR 32x PTZ	Wisenet Q network IR PTZ camera, IR range of up to 328ft, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44-142.6mm (32x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, IP66, IK10, NEMA4X, white color
Camera - Network	QNP-6320HS	2MP 32x PTZ	Wisenet Q stainless steel PTZ camera, 2MP, Full HD(1080p) 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 4.44-142.6mm (32x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Directional detection, Motion detection, Enter/Exit, Tampering, Virtual line, Audio detection* (with NW I/O Box), Micro SD/SDHC/SDXC 1slot 256GB, Focus Save, IP66/IP67, IK10, NEMA4X, PoE+
Camera - Network	TNU-6321	2MP 32x Positioning Camera	2MP Network Positioning Camera (1920 x 1080) resolution, 4.44 - 142.6mm (32x) varifocal lens, 60fps@2MP (H.264), 30fps@2MP (MJPEG), H.265, H.264, MJPEG codec support, 360° Endless, Tilt -90°~40°, Day & Night (ICR), WDR (120dB), Defog, Tampering, Virtual line, Enter / Exit, (Dis)Appear, Audio detection, Face detection, Motion detection, micro SD / SDHC / SDXC slot, Power 24VAC (Optional IR illuminators: SPI-50)

Wisenet Road AI

Network - Camera	PNB-A9091RLPH	4K AI LPR Box Camera Kit with Enclosure and IR	4K Moderate Speed (up to 75MPH) LPR Box Camera Kit with Enclosure and IR, Licensed with Wisenet Road AI. Max. 4K resolution, 12-50 mm lens, H.265, H.264, MJPEG codec, WiseStream III, Includes PoE+ Camera enclosure with Wall mount and IR LPR + MMCR: Make, Model & Color* Recognition on the Edge. 32GB Micro SD storage for up to 10,000 LPR/Vehicle images, Licensed open platform application for multiple regions/countries (USA, Canada, Mexico, Brazil, Uruguay, Paraguay, Argentina, Colombia, Chile) (* Color recognition only during day time)
Network - Camera	PNV-A9081RLP	4K IR Vandal Dome AI camera with Wisenet Road AI	4K Low-Moderate Speed LPR Vandal Dome Camera with Wisenet Road AI. Max. 4K resolution, 4.5-10mm(2.2x) M-Varifocal(4K) lens, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream III, POE+, IP66/67/IP6K9K, IK10+, NEMA4X LPR + MMCR: Make, Model & Color* Recognition on the Edge. 32GB Micro SD storage for up to 10,000 LPR/Vehicle images, Licensed open platform application for multiple regions/countries. (* Color recognition only during day time)
Camera - Network	TNO-7180RLP	3MP Global shutter LPR camera	High Speed Global Shutter Camera with Road AI 3MP, Max 60fps @3MP, 6.8-1220mm (18x) motorized varifocal lens, 32GB industrial Micro SD, Embedded Wisenet Road AI application, Adaptive IR, IP66, IK10, NEMA 4X, NEMA TS. (No PoE switch included)
Camera - Network	PNO-A9311RLP	4K, AI IR Zoom (31x), Bullet Camera with Wisenet Road AI	4K Low-Moderate Speed dedicated LPR Bullet Camera with Wisenet Road AI, Max. 4K resolution @ 30FPS, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), WiseIR for LPR plate reads for approx. 200ft (61m), Day & Night(ICR), 6.91-214.64mm (31x) zoom lens, WDR(120dB) H.265, H.264, MJPEG codec, WiseStream II, WiseStream III (Using AI engine). Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45, IP66/IP67, IK10, NEMA4X Road AI, LPR application is pre-installed and licensed on the camera that provides LPR + MMCR (Make, Model & Color*) Recognition on the Edge. (* Color recognition only during day time)
Network - Camera	PNO-A9081RLP	4K IR Bullet AI camera with Wisenet Road AI	4K Low-Moderate Speed LPR Bullet Camera with Wisenet Road AI. Max. 4K resolution, 4.5-10mm(2.2x) M-Varifocal(4K) lens, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream III, POE+, IP66/67/IP6K9K, IK10+, NEMA4X LPR + MMCR: Make, Model & Color* Recognition on the Edge. 32GB Micro SD storage for up to 10,000 LPR/Vehicle images, Licensed open platform application for multiple regions/countries. (* Color recognition only during day time)

Thermal Cameras (Note: Thermal cameras are non-returnable products)

Camera - Network	TNM-C4960TD	Bi-spectrum AI Thermal Camera VGA thermal / 4K visible	Wisenet T network Bi-spectrum AI Thermal Camera (uncooled), Dual sensor camera with VGA thermal and 4K visible video output, built-in 25mm fixed lens (FoV: 17.4° thermal) & 10.9-29mm motorized varifocal lens (FoV: 42°-15° visible), Triple codec (H.265/H.264/MJPEG), WiseStream II (thermal), WDR 120dB, Features Based on AI engine: WisenR II, Wise Stream III (visible only), Analytics events based on AI engine (visible only): Object detection (Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Stopped vehicle, Traffic jam, FIPS 140-2, 2x micro SD card (512GB x2), IP66/IP67, IK10, NEMA4X, NEMA TS 2(2.2.8, 2.2.9), PoE+/12VDC This product is subject to the Thermal agreement.
Camera - Network	TNM-C4950TD	Bi-spectrum AI Thermal Camera VGA thermal / 4K visible	Wisenet T network Bi-spectrum AI Thermal Camera (uncooled), Dual sensor camera with VGA thermal and 4K visible video output, built-in 13.5mm fixed lens (FoV: 31.9° thermal) & 10.9-29mm motorized varifocal lens (FoV: 42°-15° visible), Triple codec (H.265/H.264/MJPEG), WiseStream II (thermal), WDR 120dB, Features Based on AI engine: WisenR II, Wise Stream III (visible only), Analytics events based on AI engine (visible only): Object detection (Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Stopped vehicle, Traffic jam, FIPS 140-2, 2x micro SD card (512GB x2), IP66/IP67, IK10, NEMA4X, NEMA TS 2(2.2.8, 2.2.9), PoE+/12VDC This product is subject to the Thermal agreement.
Camera - Network	TNM-C4940TD	Bi-spectrum AI Thermal Camera VGA thermal / 4K visible	Wisenet T network Bi-spectrum AI Thermal Camera (uncooled), Dual sensor camera with VGA thermal and 4K visible video output, built-in 9.1mm fixed lens (FoV: 50° thermal) & 4.4-9.3mm motorized varifocal lens (FoV: 112.1°~47.5° visible), Triple codec (H.265/H.264/MJPEG), WiseStream II (thermal), WDR 120dB, IR viewable length 30m (98ft), Features Based on AI engine: WisenR II, Wise Stream III (visible only), Analytics events based on AI engine (visible only): Object detection (Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Stopped vehicle, Traffic jam, FIPS 140-2, 2x micro SD card (512GB x2), IP66/IP67, IK10, NEMA4X, NEMA TS 2(2.2.8, 2.2.9), PoE+/12VDC This product is subject to the Thermal agreement.
Camera - Network	TNO-4040T	VGA Thermal Bullet	Wisenet T network outdoor vandal thermal bullet camera (uncooled), 640x480 @ 30fps, 19mm fixed focal lens (32°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color This product is subject to the Thermal agreement.
Camera - Network	TNO-4030T	VGA Thermal Bullet	Wisenet T network outdoor vandal thermal bullet camera (uncooled), 640x480 @ 30fps, 13mm fixed focal lens (48.6°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color This product is subject to the Thermal agreement.
Camera - Network	TNO-4050T	VGA Thermal Bullet	Wisenet T network outdoor vandal thermal bullet camera (uncooled), 640x480 @ 30fps, 35mm fixed focal lens (17.2°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color This product is subject to the Thermal agreement.
Camera - Network	TNU-4041T	VGA Thermal Positioning	Wisenet T network outdoor thermal positioning camera (uncooled), 640x480 @ 30fps, 19mm fixed focal lens (32°), pan: 360° endless, Tilt: -90°~40°, triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, 24VAC, white color This product is subject to the Thermal agreement.
Camera - Network	TNU-4051T	VGA Thermal Positioning	Wisenet T network outdoor thermal positioning camera (uncooled), 640x480 @ 30fps, 35mm fixed focal lens (17.2°), pan: 360° endless, Tilt: -90°~40°, triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, 24VAC, white color This product is subject to the Thermal agreement.
Camera - Network	TNO-4030TR	VGA Radiometric Bullet	Wisenet T network outdoor vandal Radiometric bullet camera (uncooled), 640x480 @ 30fps, 13mm fixed focal lens (48.6°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 6 user programmable temperature detection areas, temperature detection range is from (-4°F ~ 266°F) , open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color This product is subject to the Thermal agreement.
Camera - Network	TNO-L4030TR	VGA Radiometric Bullet	Wisenet T network outdoor vandal Radiometric bullet camera (uncooled), 640x480 @ 8.3fps, 13mm fixed focal lens (48.6°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 6 user programmable temperature detection areas, temperature detection range is from (-4°F ~ 266°F) , open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-L4030T	VGA Thermal Bullet	Wisenet T network outdoor vandal thermal bullet camera (uncooled), 640x480 @ 8.3fps, 13mm fixed focal lens (48.6°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4040TR	VGA Radiometric Bullet	Wisenet T network outdoor vandal Radiometric bullet camera (uncooled), 640x480 @ 30fps, 19mm fixed focal lens (32°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 6 user programmable temperature detection areas, temperature detection range is from (-4°F ~ 266°F) , open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color This product is subject to the Thermal agreement.
Camera - Network	TNM-3620TDY	EBT camera	Wisenet T network indoor body temperature detection camera (uncooled), dual sensor camera with QVGA thermal (320x240) & 2MP (1920x1080) visible video outputs, built-in 4.7mm fixed lens (50°) (thermal), 4mm fixed lens (87.6°) (visible), AI Face & temperature detection, Estimated Body Temperature Mode: +30°C~+45°C (+86°F~+113°F), accuracy ±0.5°C (±0.9°F) / with blackbody ±0.3°C (±0.54°F), normal radiometric mode temperature detection range from (-4°F ~ +266°F), triple codec H.265/H.264/MJPEG with Wisestream II, 150dB WDR, USB and CVBS port for easy installation, advanced video analytics, micro SD, DIS, PoE+/12VDC This product is subject to the Thermal agreement.

Camera - Network	TNO-L3030T	QVGA Thermal Bullet	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 13.7mm fixed lens, H.265, H.264, MJPEG codec, Max. 8.3fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiseStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10
Camera - Network	TNO-3010T	QVGA Thermal Bullet	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 2.7mm fixed lens, H.265, H.264, MJPEG codec, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiseStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10 This product is subject to the Thermal agreement.
Camera - Network	TNO-3020T	QVGA Thermal Bullet	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 4.3mm fixed lens, H.265, H.264, MJPEG codec, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiseStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10 This product is subject to the Thermal agreement.
Camera - Network	TNO-3030T	QVGA Thermal Bullet	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 13.7mm fixed lens, H.265, H.264, MJPEG codec, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiseStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10 This product is subject to the Thermal agreement.
Camera - Network	TNO-3040T	QVGA Thermal Bullet	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 19mm fixed lens, H.265, H.264, MJPEG codec, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiseStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10 This product is subject to the Thermal agreement.
Camera - Network	TNO-C3032TRA	AI QVGA Radiometric Bullet	Wisenet T network AI Radiometric compact bullet camera (uncooled), 384 x 288 @ 8fps, <30mK (NETD), 9.7mm fixed focal lens (HFOV: 37.9°), Triple triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Vehicle), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), PTZ handover, Radiometrics: whole FoV area or up to 10 user programmable polygonal ROIs, temperature detection range from -40°C to 550°C (-40°F to 1022°F), SD card, integrated back box, IP66, NEMA4X, IK10, PoE/12VDC, white color
Camera - Network	TNO-C3022TRA	AI QVGA Radiometric Bullet	Wisenet T network AI Radiometric compact bullet camera (uncooled), 384 x 288 @ 8fps, <30mK (NETD), 6.6mm fixed focal lens (HFOV: 60.0°), Triple triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Vehicle), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), PTZ handover, Radiometrics: whole FoV area or up to 10 user programmable polygonal ROIs, temperature detection range from -40°C to 550°C (-40°F to 1022°F), SD card, integrated back box, IP66, NEMA4X, IK10, PoE/12VDC, white color
Camera - Network	TNO-C3012TRA	AI QVGA Radiometric Bullet	Wisenet T network AI Radiometric compact bullet camera (uncooled), 384 x 288 @ 8fps, <30mK (NETD), 4.4mm fixed focal lens (HFOV: 90.0°), Triple triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Vehicle), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), PTZ handover, Radiometrics: whole FoV area or up to 10 user programmable polygonal ROIs, temperature detection range from -40°C to 550°C (-40°F to 1022°F), SD card, integrated back box, IP66, NEMA4X, IK10, PoE/12VDC, white color
Camera - Network	TNO-C3030TRA	AI QVGA Radiometric Bullet	Wisenet T network AI Radiometric compact bullet camera (uncooled), 384 x 288 @ 30fps, <30mK (NETD), 9.7mm fixed focal lens (HFOV: 37.9°), Triple triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Vehicle), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), PTZ handover, Radiometrics: whole FoV area or up to 10 user programmable polygonal ROIs, temperature detection range from -40°C to 550°C (-40°F to 1022°F), SD card, integrated back box, IP66, NEMA4X, IK10, PoE/12VDC, white color This product is subject to the Thermal agreement.
Camera - Network	TNO-C3020TRA	AI QVGA Radiometric Bullet	Wisenet T network AI Radiometric compact bullet camera (uncooled), 384 x 288 @ 30fps, <30mK (NETD), 6.6mm fixed focal lens (HFOV: 60.0°), Triple triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Vehicle), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), PTZ handover, Radiometrics: whole FoV area or up to 10 user programmable polygonal ROIs, temperature detection range from -40°C to 550°C (-40°F to 1022°F), SD card, integrated back box, IP66, NEMA4X, IK10, PoE/12VDC, white color This product is subject to the Thermal agreement.
Camera - Network	TNO-C3010TRA	AI QVGA Radiometric Bullet	Wisenet T network AI Radiometric compact bullet camera (uncooled), 384 x 288 @ 30fps, <30mK (NETD), 4.4mm fixed focal lens (HFOV: 90.0°), Triple triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Vehicle), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), PTZ handover, Radiometrics: whole FoV area or up to 10 user programmable polygonal ROIs, temperature detection range from -40°C to 550°C (-40°F to 1022°F), SD card, integrated back box, IP66, NEMA4X, IK10, PoE/12VDC, white color This product is subject to the Thermal agreement.
Camera - Network	TNO-3050T	QVGA Thermal Bullet	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 35mm fixed lens, H.265, H.264, MJPEG codec, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiseStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10 This product is subject to the Thermal agreement.

Explosion Proof (Note: There is a 15% cancellation fee for any Explosion Proof camera orders)

Camera-Network	TNU-X6320A2WT1-Z	Explosion Proof Positioning Camera	Explosion proof positioning camera XP40B using the XNZ-6320A 110VAC Only, with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-Z" for cLCus C1/D1
Camera-Network	TNU-X6320A2WT2-C	Explosion Proof Positioning Camera	Explosion proof positioning camera XP40B using the XNZ-6320A 110VAC Only, with Wiper, cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67, "-C" for cLC CSA
Camera-Network	TNU-X6320A2F2WT1-Z	Explosion Proof Positioning Camera	Explosion proof positioning camera XP40B using the XNZ-6320A 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-Z" for cLCus C1/D1
Camera-Network	TNU-X6320A2F2WT2-C	Explosion Proof Positioning Camera	Explosion proof positioning camera XP40B using the XNZ-6320A, 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67, "-C" for cLC CSA
Camera-Network	TNU-X6320A2F2WT1-M	Explosion Proof Positioning Camera	Explosion proof positioning camera XP40B using the XNZ-6320A, 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-M" for INMETRO
Camera-Network	TNU-X6320A1WT1-Z	Explosion Proof Positioning Camera	Explosion proof positioning camera XP40B using the XNZ-6320A, 24VAC Only, with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-Z" for cLCus C1/D1
Camera-Network	TNU-X6320A1WT2-C	Explosion Proof Positioning Camera	Explosion proof positioning camera XP40B using the XNZ-6320A, 24VAC Only, with Wiper, cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67, "-C" for cLC CSA
Camera-Network	TNU-X6320A1WT1-M	Explosion Proof Positioning Camera	Explosion proof positioning camera XP40B using the XNZ-6320A, 24VAC Only, with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-M" for INMETRO
Camera-Network	TNU-X6320A1F2WT1-Z	Explosion Proof Positioning Camera	Explosion proof positioning camera XP40B using the XNZ-6320A, 24VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-Z" for cLCus C1/D1
Explosion Proof Positioning	TNU-X6320A1F2WT2-C	Explosion proof	Explosion proof positioning camera XP-40B using the XNZ-6320A, 24VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67, "-C" for cLC CSA
Explosion Proof Positioning	TNU-X6320A1F2WT1-M	Explosion proof	Explosion proof positioning camera XP40B using the XNZ-6320A, 24VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-M" for INMETRO
Camera-Network	TNO-X6320EPT0-Z	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A PoE Only (No Wiper), cLCus C1/D1 certification, -10°C ~ +55°C (+14°F ~ +131°F), IP66/IP67, IP68, "-Z" for cLCus C1/D1
Camera-Network	TNO-X6320EPT0-C	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A PoE Only (No Wiper), cLCus C1/D1 certification, -10°C ~ +55°C (+14°F ~ +131°F), IP66/IP67, IP68, "-C" for cLC CSA
Camera-Network	TNO-X6320EPT0-M	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A PoE Only (No Wiper), cLCus C1/D1 certification, -10°C ~ +55°C (+14°F ~ +131°F), IP66/IP67, IP68, "-M" for INMETRO
Camera-Network	TNO-X6320E1WT1-Z	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A 24VAC Only with wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, IP68, "-Z" for cLCus C1/D1
Camera-Network	TNO-X6320E1WT1-C	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320 24VAC Only with wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, IP68, "-C" for cLC CSA
Camera-Network	TNO-X6320E1WT2-C	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A 24VAC Only with wiper, cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67, IP68, "-C" for cLC CSA
Camera-Network	TNO-X6320E1WT1-M	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A 24VAC Only with wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, IP68, "-M" for INMETRO
Camera-Network	TNO-X6320E2F2T1-Z	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A 110VAC Only, Single Mode Fiber (No Wiper), cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, IP68, "-Z" for cLCus C1/D1
Camera-Network	TNO-X6320E2F2T1-C	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A 110VAC Only, Single Mode Fiber (No Wiper), cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, IP68, "-C" for cLC CSA
Camera-Network	TNO-X6320E2F2T2-C	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A 110VAC Only, Single Mode Fiber (No Wiper), cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67, IP68, "-C" for cLC CSA
Camera-Network	TNO-X6320E2F2T1-M	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A 110VAC Only, Single Mode Fiber (No Wiper), cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, IP68, "-M" for INMETRO
Camera-Network	TNO-X6320E2F2WT1-Z	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, IP68, "-Z" for cLCus C1/D1
Camera-Network	TNO-X6320E2F2WT1-C	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, IP68, "-C" for cLC CSA

Camera-Network	TNO-X6320E2F2WT2-C	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -60°C ~ +40°C (-67°F ~ +104°F), IP66/IP67/IP68, "-C" for cLC CSA
Camera-Network	TNO-X6320E2F2WT1-M	Explosion Proof Fixed Camera	Explosion proof housing using the XNZ-6320A 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67/IP68, "-M" for INMETRO
Camera-Network	TNU-X6320E2WT1-C	Explosion Proof Positioning Camera	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-C" for cLC CSA
Camera-Network	TNU-X6320E2F2WT1-C	Explosion Proof Positioning Camera	Explosion proof positioning camera using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-C" for cLC CSA
Camera-Network	TNU-X6320E1WT1-C	Explosion Proof Positioning Camera	Explosion proof positioning camera using the XNZ-6320 24VAC Only, with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-C" for cLC CSA
Camera-Network	TNU-X6320E1F2WT1-C	Explosion Proof Positioning Camera	Explosion proof positioning camera using the XNZ-6320 24VAC Only, Single Mode Fiber with Wiper, cLCus C1/D1 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP66/IP67, "-C" for cLC CSA
Explosion Proof - Accessory	HT-E-XWP10UL	Explosion Proof Accessories Washer Tank	Stainless steel Washer tank for cameras with Wiper model (TNP-6320E2W, TNP-6320E1W, TNP-6320E1WF, TNU positioning camera, TNO-6070E2WF, TNO-6320E2WF, TNO-6070E1W)
Explosion Proof - Accessory	HT-E-BFP00SW	Explosion Proof Accessories Mounting Bracket	Stainless steel Top mounting bracket
Explosion Proof - Accessory	HT-E-BFW320SW	Explosion Proof Accessories Wall Mount	Stainless steel wall mount for (TNO-6070EP, TNO-6320EP, TNO-6070EW2, TNO-6320EW2)
Explosion Proof - Accessory	HT-E-BPW6800	Explosion Proof Accessories PTZ wall Mount	Stainless steel Wall mount for (TNP-xxx, TNU-xxxx)
Explosion Proof - Accessory	HT-E-BFW50SW	Explosion Proof Accessories Wall Mount	Stainless steel wall mount for (TNO-6070EF2, TNO-6320EF2, TNO-6070EWF2, TNO-6320EWF2)
Explosion Proof - Accessory	HT-E-BFP00CL	Explosion Proof Accessories Pole Adaptor	Stainless steel pole mount adaptor
Camera - Network	TNO-X6072EPT1-Z	Explosion Proof Fixed Camera	Explosion proof camera using the XNB-6000 (2MP @ 60fps) + 2.8-9mm Lens PoE Only (No Wiper), -40°C ~ +55°C (-40°F ~ +131°F), type 4x, IP66, FM (Factory Mutual), C1/D1 certification
Camera - Network	TNO-X8072EPT1-Z	Explosion Proof Fixed Camera	Explosion proof camera using the XNB-8000 (5MP @ 30fps) + 4.1-9mm Lens PoE Only (No Wiper), -40°C ~ +55°C (-40°F ~ +131°F), type 4x, IP66, FM (Factory Mutual), C1/D1 certification
Camera - Network	TNO-X6322EPT1-Z	Explosion Proof Zoom Camera	Explosion proof zoom camera using the XNZ-L6320 (2MP @ 60fps) with 32x optical zoom, PoE Only (No Wiper), -40°C ~ +55°C (-40°F ~ +131°F), type 4x, IP66, FM (Factory Mutual), C1/D1 certification
Camera - Network	TNM-XNF9013EPT3-Z	Explosion proof Camera	Explosion proof Fisheye camera using the XNF-9013RV (12 MP, AI 360° camera, Stereographic fish eye lens PoE+ (No Wiper), -40°C ~ +60°C (-40°F ~ +140°F), type 4x, IP66, FM (Factory Mutual), C1/D1, CA/CE, and Inmetro certifications
Camera - Network	TNP-X6322EPT3-Z	Explosion Proof PTZ	Explosion proof PTZ using the XNP-6320 (2MP @ 60fps) +with 32x optical zoom PoE+ (No Wiper), -20°C ~ +55°C (-4°F ~ +131°F), type 4x, IP66, FM (Factory Mutual), C1/D1 certification
Camera - Network	TNO-P9072EPT1-Z	Explosion Proof Fixed Camera	AI 4K Explosion proof camera using the PNB-A9001 (8MP @ 30fps) + 3.9-10mm f1.5 Varifocal I-CS Lens PoE+ (No Wiper), -40°C ~ +55°C (-40°F ~ +131°F), type 4x, IP66, FM (Factory Mutual), cLCus C1/D1 certification
Camera - Network	TNM-P9022EPT3-Z	Explosion Proof Panoramic Camera	WN7 Panoramic Multi-sensor explosion proof camera, 180° view, (2MP X 4 sensors) 7.3MP @ 30fps, panoramic 209° view, 8.3MP, triple codec H.265/H.264/MJPEG with WiseStream II technology, extreme WDR 120dB, defocus detection, built in analytics, Heatmap, Micro USB for easy installation, 2 x Micro SD cards PoE+, IP66/IK10/NEMA4X; FM (Factory Mutual), cLCus C1/D1 certification
Explosion Proof - Accessory	HT-F1XX-WM	Wall Mount	Wall mount for the (TNO-X6072EPT1-Z, TNO-X8072EPT1-Z, and TNO-X6322EPT1-Z)
Explosion Proof - Accessory	HT-SD-FP	Protection Kit	Protection kit for the (TNP-X6322EPT3-Z, TNP-Q6232EPT3-Z)
Explosion Proof - Accessory	HT-SD-WM	Wall Mount	Wall mount for the (TNP-X6322EPT3-Z, TNP-Q6232EPT3-Z)
Explosion Proof - Accessory	HT-SF-FP	Protection Kit	Protection kit for the (TNO-X6072EPT1-Z, TNO-X8072EPT1-Z and TNO-X6322EPT1-Z)
Explosion Proof - Accessory	HT-SPMA-SD	Pole Mount	Pole mount for the (TNO-X6072EPT1-Z, TNO-X8072EPT1-Z and TNO-X6322EPT1-Z, TNP-X6322EPT3-Z, TNP-Q6232EPT3-Z) requires a wall mount
Explosion Proof - Accessory	HT-SD-CM	Corner Mount	Corner mount for the (TNO-X6072EPT1-Z, TNO-X8072EPT1-Z and TNO-X6322EPT1-Z, TNP-X6322EPT3-Z, TNP-Q6232EPT3-Z) requires a wall mount

Audio

IP Audio System	SPA-W100W	IP Wall Speaker	IP Audio Speaker, Two-way audio, Scheduler, Background Music, Text To Speech, 10W Amp, 101dB Output, Freq. Range 120Hz-20kHz, 1GB Internal Storage, Single Micro SD slot (Up to 32GB), Built in Relay, SUNAPI, Onvif, SIP, P2P-SIP, IP54, PoE, PoE+, White Color
IP Audio System	SPA-W100B	IP Wall Speaker	IP Audio Speaker, Two-way audio, Scheduler, Background Music, Text To Speech, 10W Amp, 101dB Output, Freq. Range 120Hz-20kHz, 1GB Internal Storage, Single Micro SD slot (Up to 32GB), Built in Relay, SUNAPI, Onvif, SIP, P2P-SIP, IP54, PoE, PoE+, Black Color
IP Audio System	SPA-S1000	IP Audio Server	IP Audio Server, Scheduler, Background Music, Text To Speech, SUNAPI, Onvif
IP Audio System	SPA-P100W	IP Pendant Speaker	IP Audio Speaker, Two-way audio, Scheduler, Background Music, Text To Speech, 10W Amp, 101dB Output, Freq. Range 130Hz-20kHz, 1GB Internal Storage, Single Micro SD slot (Up to 32GB), Built in Relay, SUNAPI, Onvif, SIP, P2P-SIP, PoE, PoE+, White Color
IP Audio System	SPA-P100B	IP Pendant Speaker	IP Audio Speaker, Two-way audio, Scheduler, Background Music, Text To Speech, 10W Amp, 101dB Output, Freq. Range 130Hz-20kHz, 1GB Internal Storage, Single Micro SD slot (Up to 32GB), Built in Relay, SUNAPI, Onvif, SIP, P2P-SIP, PoE, PoE+, Black Color
IP Audio System	SPA-H100W	IP Horn Speaker	IP Audio Speaker, Two-way audio, Scheduler, Background Music, Text To Speech, 10W Amp, 124dB Output, Freq. Range 650Hz-5.3kHz, 1GB Internal Storage, Single Micro SD slot (Up to 32GB), Built in Relay, SUNAPI, Onvif, SIP, P2P-SIP, IP66, PoE, PoE+, White Color
IP Audio System	SPA-H100B	IP Horn Speaker	IP Audio Speaker, Two-way audio, Scheduler, Background Music, Text To Speech, 10W Amp, 124dB Output, Freq. Range 650Hz-5.3kHz, 1GB Internal Storage, Single Micro SD slot (Up to 32GB), Built in Relay, SUNAPI, Onvif, SIP, P2P-SIP, IP66, PoE, PoE+, Black Color
IP Audio System	SPA-D1000	IP Audio Module	IP Audio Module, Scheduler, Background Music, Text To Speech, 10W / 8 Ohm Analog Speaker Output, 1GB Internal Storage, Single Micro SD slot (Up to 32GB), Built in Relay, SUNAPI, Onvif, SIP, P2P-SIP, PoE, PoE+
IP Audio System	SPA-C110W	IP Ceiling Speaker	IP Audio Speaker, Two-way audio, Scheduler, Background Music, Text To Speech, 10W, 100dB Output, Freq. Range 120Hz-20kHz, 1GB Internal Storage, Single Micro SD slot (Up to 32GB), Built in Relay, SUNAPI, Onvif, SIP, P2P-SIP, PoE, PoE+, White Color
IP Audio System	SPA-C110B	IP Ceiling Speaker	IP Audio Speaker, Two-way audio, Scheduler, Background Music, Text To Speech, 10W, 100dB Output, Freq. Range 120Hz-20kHz, 1GB Internal Storage, Single Micro SD slot (Up to 32GB), Built in Relay, SUNAPI, Onvif, SIP, P2P-SIP, PoE, PoE+, Black Color

Intercoms

Intercoms	TCIS-2	Outdoor Audio Intercom	Zenitel Turbine Intercom, Audio only, Full Duplex, Group call, AVC, AEC, HD voice, Outdoor IP66, IK10, 95dB at 1 m (Open Duplex), 105 dB at 1m(Half Duplex) PoE, 6 x I/O, 12mA LED driver output, SIP, UL, Cisco Certified, Avaya Certified, NEC Certified, -40° to 70° C (-40° to 158 ° F), UV Resistance, 10 W Amp, Audio out 600 Ohm
Intercoms	TCIS-3	Outdoor Audio Intercom	Zenitel Turbine Intercom, Audio only, Full Duplex, Group call, AVC, AEC, HD voice, Outdoor IP66, IK08, 95dB at 1 m (Open Duplex), 105 dB at 1m(Half Duplex) PoE, 6 x I/O, 12mA LED driver output, SIP, UL, Cisco Certified, Avaya Certified, NEC Certified, -40° to 70° C (-40° to 158 ° F), UV Resistance, 10 W Amp, Audio out 600 Ohm
Intercoms	TMIS-1	Indoor Audio Intercom	Zenitel Turbine Mini Intercom, Audio only, Full Duplex, Group call, AVC, AEC, HD voice, Indoor IP42, 90dB at 1 m (Open Duplex), PoE, 6 x I/O, 12mA LED driver output, SIP, UL, Cisco Certified, Avaya Certified, -25° to 70° C (-13° to 158 ° F), 10 W Amp
Intercoms	TID-600R	Video Intercom	Video Intercom Station, 2MP@60fps, 1.6mm fixed lens (180° x 114°), triple codec H.265/H.264/MJPEG with Wisestream II, 150dB WDR, IR LEDs range 16', Touchless call, Tow-way (Full duplex) audio, 85dB@0.5m, Echo cancellation and noise reduction, Built in tamper switch, Built in Relay, SIP 2.0, P2P-SIP, SIPS, IP65, IK08, NEMA4X, PoE, 12VDC

PC based Solution

Wisenet WAVE Software	WAVE-PRO-01	WAVE, 1x IP camera license	WAVE Professional License. Enables one (1) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.
Wisenet WAVE Software	WAVE-PRO-04	WAVE, 4x IP camera license	WAVE Professional License. Enables four (4) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.
Wisenet WAVE Software	WAVE-PRO-05	WAVE, 5x IP camera license	WAVE Professional License. Enables five (5) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.
Wisenet WAVE Software	WAVE-PRO-08	WAVE, 8x IP camera license	WAVE Professional License. Enables eight (8) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.
Wisenet WAVE Software	WAVE-PRO-16	WAVE, 16x IP camera license	WAVE Professional License. Enables sixteen (16) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.
Wisenet WAVE Software	WAVE-PRO-24	WAVE, 24x IP camera license	WAVE Professional License. Enables twenty-four (24) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.
Wisenet WAVE Software	WAVE-PRO-48	WAVE, 48x IP camera license	WAVE Professional License. Enables forty-eight (48) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.
Wisenet WAVE Software	WAVE-VW-02	WAVE, Video Wall license	WAVE Video Wall License. Enables up to two (2) monitors, includes life-time SW upgrade. No annual & maintenance cost required.
Wisenet WAVE Software	WAVE-ENC-04	WAVE, 4 channel encoder license	WAVE Encoder License. Enables up to four (4) recording channels, includes life-time SW upgrade. No annual & maintenance cost required.
Wisenet WAVE Software	WAVE-IO-01	WAVE, I/O module license	WAVE I/O License. Enables one (1) I/O module, includes life-time SW upgrade. No annual & maintenance cost required.
Wisenet WAVE Software	WAVE-EMB-04	WAVE, 4 channel embedded recorder	WAVE Embedded Recorder License. Enables four (4) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.
Wisenet WAVE Software	WAVE-EMB-08	WAVE, 8 channel embedded recorder	WAVE Embedded Recorder License. Enables eight (8) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.
Wisenet WAVE Software	WAVE-EMB-16	WAVE, 16 channel embedded recorder	WAVE Embedded Recorder License. Enables sixteen (16) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.
Wisenet WAVE Software	WAVE-EMB-32	WAVE, 32 channel embedded recorder	WAVE Embedded Recorder License. Enables thirty-two (32) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.

WAVE - Appliance	WRT-P-5202L-24TB	WAVE Recording Server (Linux OS)	Mini-tower form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 24TB raw, 470 Mbps recording B/W, (3) 3.5" HDD, (Gen 12) Intel Core i5, 16GB RAM, 256 GB SSD OS Drive, Ubuntu Linux 20.04 LTS, (2) DisplayPort output, (1) DisplayPort to HDMI adapter included, Dual GbE NICs, Single 550W power supply, Keyboard and mouse included
WAVE - Appliance	WRT-P-5202L-36TB	WAVE Recording Server (Linux OS)	Mini-tower form factor Wisenet WAVE Network Video Recorder with 4 Professional licenses, Wisenet WAVE pre-installed, 36TB raw, 470 Mbps recording B/W, (3) 3.5" HDD, (Gen 12) Intel Core i5, 16GB RAM, 256 GB SSD OS Drive, Ubuntu Linux 20.04 LTS, (2) DisplayPort output, (1) DisplayPort to HDMI adapter included, Dual GbE NICs, Single 550W power supply, Keyboard and mouse included

Software Solutions

WAVE Integration	WAVE-S2NETBOX-INT	WAVE Plugin for LenelS2 NetBox	Plugin to bring WAVE video and events into LenelS2 NetBox Access Control. License is valid for one NetBox server and unlimited WAVE connections.
WAVE Integration	WAVE-AMAG-INT	WAVE Plugin for AMAG	Plugin to bring WAVE video and events into AMAG Symmetry Access Control. License is valid for one AMAG server and unlimited WAVE connections.

Wisenet SKY (Wisenet SKY products are only available for Wisenet SKY certified partners)

Wisenet SKY - Hardware	SKY-SU301-0	Bridge 301	Location Setup Fee Bridge 301 (Rack Form Factor) 1MP: 25CH, 4MP: 20CH, Analytics: 5CH, up to 2 days of local video buffering, 1TB HDD, VGA, DVI This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-SU304p-0	Bridge 304+	Location Setup Fee Bridge 304+ (Compact and Ruggedized Form Factor) 1MP: 25CH, 4MP: 20CH, Analytics: 5CH, up to 2 days of local video buffering, 1TB SSD, VGA, HDMI This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-SU305-0	Bridge 305	Location Setup Fee Bridge 305 (Compact and Ruggedized Form Factor with 4 PoE Ports) 1MP: 15CH, 4MP: 12CH, Analytics: 5CH, up to 2 days of local video buffering, 1TB HDD, HDMI, DP, 4PoE ports This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-SU401-0	Bridge 401	Location Setup Fee Bridge 401 (Rack Form Factor) 1MP: 42CH, 4MP: 35CH, Analytics: 10CH, up to 2 LPR cameras, up to 2 days of local video buffering, 1TB HDD, VGA, HDMI, DP This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-SU406p-0	Bridge 406+	Location Setup Fee Bridge 406+ (Compact Form Factor) 1MP: 44CH, 4MP: 35CH, Analytics: 15CH, up to 2 LPR cameras, up to 2 days of local video buffering for 35CH @ 4MP, 2x HDMI This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-SU501-0	Bridge 501	Location Setup Fee Bridge 501 (Rack Form Factor) 1MP: 72CH, 4MP: 50CH, Analytics: 10CH, up to 4 LPR cameras, up to 2 days of local video buffering, 1TB HDD, VGA, HDMI, DP This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-SU504p-0	Bridge 504+	Location Setup Fee Bridge 504+ Compact and Ruggedized Form Factor) 1MP: 72CH, 4MP: 50CH, Analytics: 20CH, up to 4 LPR cameras, up to 2 days of local video buffering 50CH @ 4MP, HDMI, DP This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-BR320-0	CMVR 320	CMVR 320 with 4TB (Rack Form Factor) 1MP: 25CH, 4MP: 20CH, Analytics: 5CH, 4TB HDD (35 days for 20 cameras @ 1MP), VGA, DVI This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-BR324p-0	CMVR 324+	CMVR 324+ with 4TB (Compact and Ruggedized Form Factor) 1MP: 12CH, 4MP: 8CH, Analytics: 5CH, 4TB HDD (60 days for 12 cameras @ 1MP), VGA, HDMI This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-BR325-0	CMVR 325	CMVR 325 with 2TB (Compact and Ruggedized Form Factor with 4 PoE Ports) 1MP: 12CH, 4MP: 8CH, Analytics: 5CH, 2TB HDD (45 days for 8 cameras @ 1MP), HDMI, DP, 4PoE ports This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-BR426p-0	CMVR 426+	CMVR 426+ with 4TB (Compact and Ruggedized Form Factor) 4MP: 20CH, Analytics: 15CH, up to 2 LPR cameras, 16TB HDD (35 days for 20 cameras @ 4MP), 2x HDMI This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-BR524p-0	CMVR 524+	CMVR 524+ with 4TB (Compact and Ruggedized Form Factor) 4MP: 25CH, Analytics: 20CH, up to 4 LPR cameras, 16TB HDD (30 days for 25 cameras @ 4MP), HDMI, DP This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-BR420-0	CMVR 420	CMVR 420 with 10TB (Rack Form Factor) 1MP: 42CH, 4MP: 35CH, Analytics: 10CH, up to 2 LPR Cameras, 10TB HDD (50 days for 35 camera @ 1MP), VGA, HDMI, DP This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-BR520-0	CMVR 520	CMVR 520 with 40TB (raw) 30TB (useable) RAID 5 (Enterprise Rack Form Factor) 1MP: 62CH, 4MP: 50CH, Analytics: 20CH, up to 4 LPR cameras, 40TB (raw) 30TB (useable) RAID 5, (30 days for 40 cameras @ 4MP), VGA, HDMI, DP This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-BR620-0	CMVR 620	CMVR 620 with 64TB (raw) 48TB (useable) RAID 5 (Enterprise Rack Form Factor) 1MP: 125CH, 4MP: 100CH, Analytics: 30CH, 64TB (raw) 48TB (useable) RAID 5, (30 days for 60 cameras @ 4MP), VGA, HDMI, DP This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-BR820-0	CMVR 820	CMVR 820 with 120TB (raw) 100TB (usable) Raid 6 (Enterprise Rack Form Factor) 1MP: 195CH, 4MP: 165CH, Analytics: 40CH, 120TB (raw) 100TB (useable) Raid 6, (30 days for 130 cameras @ 4MP), VGA, HDMI, DP This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-DS200-0a	Local Display Station DS200	Local Display Station DS200 (Dual Monitor Output with 4K support) 4K or 2x 1080p, 2x HDMI, Throughput 160Mbps, 64CH This product is subject to the Wisenet SKY agreement.
Wisenet SKY - Hardware	SKY-SW10g-001	Network Switch SW10g	Switch SW10g (8 Port Gigabit PoE+ Switch with 2xSFP, 802.3af (max 15.4W), 802.3at (max 30W), max power budget 125W, 10/100/1000 Mbps)
Wisenet SKY - Hardware	SKY-SW20g-001	Network Switch SW20g	Switch SW20g (16 Port Gigabit PoE+ Switch with 2xUplink and 2xSFP, 802.3af (max 15.4W), 802.3at (max 30W), max power budget 250W, 10/100/1000 Mbps)
Wisenet SKY - Hardware	SKY-SW28g-001	Network Switch SW28g	Switch SW28g (24 Port Gigabit PoE+ Switch with 2xUplink and 2xSFP, 802.3af (max 15.4W), 802.3at (max 30W), max power budget 370W, 10/100/1000 Mbps)
Wisenet SKY - Hardware	SKY-SWSFP-002	Network Module	Switch SFP Copper MMF Module
Wisenet SKY - Hardware	SKY-SWSFP-001	Network Module	Switch SFP Optical MMF Module (850nm, 1.25Gbps, 550m)

Embedded NVR

Recording - Network	PRN-6400DB4	NVR	8K NVR (Intel based), No HDD, 64 channels, H.265, H.264, MJPEG, 16 fixed internal SATA HDDs (10TB max per HDD), RAID 5 & 6, ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping, add AI to some P, X and Q series Hanwha Cameras, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code, NDAA & FCC Compliant Model.
Recording - Network	PRN-6400DB4-12TB	NVR	8K NVR (Intel based), 12TB RAW, 64 channels, H.265, H.264, MJPEG, 16 fixed internal SATA HDDs (10TB max per HDD), RAID 5 & 6, ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping, add AI to some P, X and Q series Hanwha Cameras, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code, NDAA & FCC Compliant Model.
Recording - Network	PRN-6400DB4-16TB	NVR	8K NVR (Intel based), 16TB RAW, 64 channels, H.265, H.264, MJPEG, 16 fixed internal SATA HDDs (10TB max per HDD), RAID 5 & 6, ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping, add AI to some P, X and Q series Hanwha Cameras, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code, NDAA & FCC Compliant Model.
Recording - Network	PRN-6400DB4-20TB	NVR	8K NVR (Intel based), 20TB RAW, 64 channels, H.265, H.264, MJPEG, 16 fixed internal SATA HDDs (10TB max per HDD), RAID 5 & 6, ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping, add AI to some P, X and Q series Hanwha Cameras, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code, NDAA & FCC Compliant Model.
Recording - Network	PRN-6400DB4-24TB	NVR	8K NVR (Intel based), 24TB RAW, 64 channels, H.265, H.264, MJPEG, 16 fixed internal SATA HDDs (10TB max per HDD), RAID 5 & 6, ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping, add AI to some P, X and Q series Hanwha Cameras, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code, NDAA & FCC Compliant Model.
Recording - Network	PRN-6400DB4-32TB	NVR	8K NVR (Intel based), 32TB RAW, 64 channels, H.265, H.264, MJPEG, 16 fixed internal SATA HDDs (10TB max per HDD), RAID 5 & 6, ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping, add AI to some P, X and Q series Hanwha Cameras, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code, NDAA & FCC Compliant Model.
Recording - Network	PRN-6400DB4-40TB	NVR	8K NVR (Intel based), 40TB RAW, 64 channels, H.265, H.264, MJPEG, 16 fixed internal SATA HDDs (10TB max per HDD), RAID 5 & 6, ARB (Automatic Recovery Backup), 400 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/VGA dual display, max. resolution of 32MP recording/display and fisheye dewarping, add AI to some P, X and Q series Hanwha Cameras, web UI 2.0 (no plugins required), AI search (Wisenet AI cameras only), QR Code, NDAA & FCC Compliant Model.

Recording - Network	QRN-1630S	NVR	16CH NVR with 16 PoE Ports (POE Budget 130W) with 8MP Camera Support. H.265, H.264, MJPEG, 2 fixed internal SATA HDDs (10TB each or 20TB Total). 128Mbps Network camera recording, Dual Stream recording option, 2 HDMI Outputs with local 4K display resolution (HDMI1: 3840x2160(30Hz), HDMI2: 1920x1080(60Hz)) - Automatic Recovery Back up (ARB) feature (A.K.A Edge recording retrieval). Four (4) Alarm In/ Two(2) Alarm out and Audio Output (RCA). Easy connection using P2P service (QR code connect) with Wisenet Mobile APP (for Android and IOS) and the free of charge Wisenet Viewer. NDA & FCC Compliant Model.
Recording - Network	QRN-1630S-2TB	16 CH NVR	16CH NVR 2TB with 16 PoE Ports (POE Budget 130W) with 8MP Camera Support. H.265, H.264, MJPEG, 2 fixed internal SATA HDDs (10TB each or 20TB Total). 128Mbps Network camera recording, Dual Stream recording option, 2 HDMI Outputs with local 4K display resolution (HDMI1: 3840x2160(30Hz), HDMI2: 1920x1080(60Hz)) - Automatic Recovery Back up (ARB) feature (A.K.A Edge recording retrieval). Four (4) Alarm In/ Two(2) Alarm out and Audio Output (RCA). Easy connection using P2P service (QR code connect) with Wisenet Mobile APP (for Android and IOS) and the free of charge Wisenet Viewer. NDA & FCC Compliant Model.
Recording - Network	QRN-1630S-4TB	16 CH NVR	16CH NVR 4TB with 16 PoE Ports (POE Budget 130W) with 8MP Camera Support. H.265, H.264, MJPEG, 2 fixed internal SATA HDDs (10TB each or 20TB Total). 128Mbps Network camera recording, Dual Stream recording option, 2 HDMI Outputs with local 4K display resolution (HDMI1: 3840x2160(30Hz), HDMI2: 1920x1080(60Hz)) - Automatic Recovery Back up (ARB) feature (A.K.A Edge recording retrieval). Four (4) Alarm In/ Two(2) Alarm out and Audio Output (RCA). Easy connection using P2P service (QR code connect) with Wisenet Mobile APP (for Android and IOS) and the free of charge Wisenet Viewer. NDA & FCC Compliant Model.
Recording - Network	QRN-1630S-6TB	16 CH NVR	16CH NVR 6TB with 16 PoE Ports (POE Budget 130W) with 8MP Camera Support. H.265, H.264, MJPEG, 2 fixed internal SATA HDDs (10TB each or 20TB Total). 128Mbps Network camera recording, Dual Stream recording option, 2 HDMI Outputs with local 4K display resolution (HDMI1: 3840x2160(30Hz), HDMI2: 1920x1080(60Hz)) - Automatic Recovery Back up (ARB) feature (A.K.A Edge recording retrieval). Four (4) Alarm In/ Two(2) Alarm out and Audio Output (RCA). Easy connection using P2P service (QR code connect) with Wisenet Mobile APP (for Android and IOS) and the free of charge Wisenet Viewer. NDA & FCC Compliant Model.
Recording - Network	QRN-1630S-8TB	16 CH NVR	16CH NVR 8TB with 16 PoE Ports (POE Budget 130W) with 8MP Camera Support. H.265, H.264, MJPEG, 2 fixed internal SATA HDDs (10TB each or 20TB Total). 128Mbps Network camera recording, Dual Stream recording option, 2 HDMI Outputs with local 4K display resolution (HDMI1: 3840x2160(30Hz), HDMI2: 1920x1080(60Hz)) - Automatic Recovery Back up (ARB) feature (A.K.A Edge recording retrieval). Four (4) Alarm In/ Two(2) Alarm out and Audio Output (RCA). Easy connection using P2P service (QR code connect) with Wisenet Mobile APP (for Android and IOS) and the free of charge Wisenet Viewer. NDA & FCC Compliant Model.
Recording - Network	QRN-1630S-10TB	16 CH NVR	16CH NVR 10TB with 16 PoE Ports (POE Budget 130W) with 8MP Camera Support. H.265, H.264, MJPEG, 2 fixed internal SATA HDDs (10TB each or 20TB Total). 128Mbps Network camera recording, Dual Stream recording option, 2 HDMI Outputs with local 4K display resolution (HDMI1: 3840x2160(30Hz), HDMI2: 1920x1080(60Hz)) - Automatic Recovery Back up (ARB) feature (A.K.A Edge recording retrieval). Four (4) Alarm In/ Two(2) Alarm out and Audio Output (RCA). Easy connection using P2P service (QR code connect) with Wisenet Mobile APP (for Android and IOS) and the free of charge Wisenet Viewer. NDA & FCC Compliant Model.
Recording - Network	QRN-1630S-12TB	16 CH NVR	16CH NVR 12TB with 16 PoE Ports (POE Budget 130W) with 8MP Camera Support. H.265, H.264, MJPEG, 2 fixed internal SATA HDDs (10TB each or 20TB Total). 128Mbps Network camera recording, Dual Stream recording option, 2 HDMI Outputs with local 4K display resolution (HDMI1: 3840x2160(30Hz), HDMI2: 1920x1080(60Hz)) - Automatic Recovery Back up (ARB) feature (A.K.A Edge recording retrieval). Four (4) Alarm In/ Two(2) Alarm out and Audio Output (RCA). Easy connection using P2P service (QR code connect) with Wisenet Mobile APP (for Android and IOS) and the free of charge Wisenet Viewer. NDA & FCC Compliant Model.
Recording - Network	QRN-1630S-16TB	16 CH NVR	16CH NVR 16TB with 16 PoE Ports (POE Budget 130W) with 8MP Camera Support. H.265, H.264, MJPEG, 2 fixed internal SATA HDDs (10TB each or 20TB Total). 128Mbps Network camera recording, Dual Stream recording option, 2 HDMI Outputs with local 4K display resolution (HDMI1: 3840x2160(30Hz), HDMI2: 1920x1080(60Hz)) - Automatic Recovery Back up (ARB) feature (A.K.A Edge recording retrieval). Four (4) Alarm In/ Two(2) Alarm out and Audio Output (RCA). Easy connection using P2P service (QR code connect) with Wisenet Mobile APP (for Android and IOS) and the free of charge Wisenet Viewer. NDA & FCC Compliant Model.
Recording - Network	QRN-1630S-20TB	16 CH NVR	16CH NVR 20TB with 16 PoE Ports (POE Budget 130W) with 8MP Camera Support. H.265, H.264, MJPEG, 2 fixed internal SATA HDDs (10TB each or 20TB Total). 128Mbps Network camera recording, Dual Stream recording option, 2 HDMI Outputs with local 4K display resolution (HDMI1: 3840x2160(30Hz), HDMI2: 1920x1080(60Hz)) - Automatic Recovery Back up (ARB) feature (A.K.A Edge recording retrieval). Four (4) Alarm In/ Two(2) Alarm out and Audio Output (RCA). Easy connection using P2P service (QR code connect) with Wisenet Mobile APP (for Android and IOS) and the free of charge Wisenet Viewer. NDA & FCC Compliant Model.
Recording - Network	QRN-830S	8 CH PoE NVR	8CH NVR with 8 PoE Ports (PoE Budget 65W) with 8MP Camera Support. H.265, H.264, MJPEG, 1 fixed internal SATA HDDs (up to 6TB). 80Mbps Network camera recording, Dual Stream recording option, HDMI Outputs with local 4K display resolution (HDMI1: 3840x2160(30Hz), Automatic Recovery Back-up (ARB) feature (A.K.A Edge recording retrieval). Easy connection using P2P service (QR code connect) with Wisenet Mobile APP (for Android and IOS) and the free of charge Wisenet Viewer. NDA & FCC Compliant Model.
Recording - Network	QRN-830S-2TB	8 CH NVR	8CH NVR 2TB with 8 PoE Ports (PoE Budget 65W) with 8MP Camera Support. H.265, H.264, MJPEG, 1 fixed internal SATA HDDs (up to 6TB). 80Mbps Network camera recording, Dual Stream recording option, HDMI Outputs with local 4K display resolution (HDMI1: 3840x2160(30Hz), Automatic Recovery Back-up (ARB) feature (A.K.A Edge recording retrieval). Easy connection using P2P service (QR code connect) with Wisenet Mobile APP (for Android and IOS) and the free of charge Wisenet Viewer. NDA & FCC Compliant Model.
Recording - Network	QRN-830S-4TB	8 CH NVR	8CH NVR 4TB with 8 PoE Ports (PoE Budget 65W) with 8MP Camera Support. H.265, H.264, MJPEG, 1 fixed internal SATA HDDs (up to 6TB). 80Mbps Network camera recording, Dual Stream recording option, HDMI Outputs with local 4K display resolution (HDMI1: 3840x2160(30Hz), Automatic Recovery Back-up (ARB) feature (A.K.A Edge recording retrieval). Easy connection using P2P service (QR code connect) with Wisenet Mobile APP (for Android and IOS) and the free of charge Wisenet Viewer. NDA & FCC Compliant Model.
Recording - Network	QRN-830S-6TB	8 CH NVR	8CH NVR 6TB with 8 PoE Ports (PoE Budget 65W) with 8MP Camera Support. H.265, H.264, MJPEG, 1 fixed internal SATA HDDs (up to 6TB). 80Mbps Network camera recording, Dual Stream recording option, HDMI Outputs with local 4K display resolution (HDMI1: 3840x2160(30Hz), Automatic Recovery Back-up (ARB) feature (A.K.A Edge recording retrieval). Easy connection using P2P service (QR code connect) with Wisenet Mobile APP (for Android and IOS) and the free of charge Wisenet Viewer. NDA & FCC Compliant Model.
Recording - Network	XRN-420S	NVR with PoE+	4K NVR (Intel based), 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H.265, H.264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 8MP recording/display, AI search (Wisenet AI cameras only), QR Code
Recording - Network	XRN-420S-2TB	NVR with PoE+	4K NVR (Intel based) 2TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H.265, H.264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 8MP recording/display, AI search (Wisenet AI cameras only), QR Code
Recording - Network	XRN-420S-4TB	NVR with PoE+	4K NVR (Intel based) 4TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H.265, H.264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 8MP recording/display, AI search (Wisenet AI cameras only), QR Code
Recording - Network	XRN-420S-6TB	NVR with PoE+	4K NVR (Intel based) 6TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H.265, H.264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 8MP recording/display, AI search (Wisenet AI cameras only), QR Code
Recording - Network	QRN-430S	NVR with PoE+	4K NVR (Intel based), 4CH with 4 PoE/PoE+ ports (PoE Budget 35W), H.265, H.264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 40 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, 4K HDMI display, max. resolution of 8MP recording/display, QR Code
Recording - Network	QRN-430S-2TB	4 CH NVR	4K NVR (Intel based), 2TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 35W), H.265, H.264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 40 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, 4K HDMI display, max. resolution of 8MP recording/display, QR Code
Recording - Network	QRN-430S-4TB	4 CH NVR	4K NVR (Intel based), 4TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 35W), H.265, H.264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 40 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, 4K HDMI display, max. resolution of 8MP recording/display, QR Code
Recording - Network	QRN-430S-6TB	4 CH NVR	4K NVR (Intel based), 6TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 35W), H.265, H.264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 40 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiseStream technology, 4K HDMI display, max. resolution of 8MP recording/display, QR Code

Encoders and Decoders

Network - Encoder	SPE-1630	16 Channel Encoder	Encoder, 16CH H.265/H.264/MJPEG, Supports: AHD, CVI, TVI and CVBS (AUTO), Up to 5MP@12fps, 4MP@15fps, 2MP@30fps, RS-485Interface, Coaxial Control: Pelco C when using CVBS or ACP up-coax protocol @ AHD, ONVIF Profile S support, 1 HDMI OUT (16 multi Image, 1920x1080), I/O 16/4, Audio in/out 4/1
Network - Encoder	SPE-420	4 Channel Encoder	Encoder, 4CH H.265/H.264/MJPEG, 5MP : 12fps/CH, 4MP : 15fps/CH, 1080p : 30fps/CH, 720p/WD/14CIF/CIF: 30fps, AHD/CVI/TVI/CVBS compatible, RS-485/422 Interface, Pelco C when using CVBS or ACP up-coax protocol @ AHD, ONVIF protocol support, HDMI output, I/O 4/2, Audio in/out 4/1, DC12V, PoE(IEEE 802.3af)
Decoder - Network	SPD-152	64CH Network Video Decoder	Video decoding up to 64 cameras, Dual HDMI output (HDMI#1 UHD, HDMI#2 FHD), Supported resolution: 4K@60FPS ~ 2M@360FPS, ONVIF, SUNAPI, RTSP, H.265 / H.264 / MJPEG codec, up to 20 Layout, Sequence Support, 12V DC, PoE

Network Switches and Transmission Devices

Switch	AT-GS970M/10PS-R-10	8 x Gigabit Ethernet PoE+ 124W	AT 8 x Gigabit Ethernet managed switch, 2 x SFP Uplink, PoE+ 124W total PoE budget
Switch	AT-GS970M/18PS-R-10	16 x Gigabit Ethernet PoE+ 247W	AT 16 x Gigabit Ethernet managed switch, 2 x SFP Uplink, PoE+ 247W total PoE budget
Switch	AT-GS970M/28PS-10	24 x Gigabit Ethernet PoE+ 370W	AT 24 x Gigabit Ethernet managed switch, 4x SFP uplink ports, PoE+ 370W total PoE budget
Switch	AT-GS980M/52PS-10	48 x Gigabit Ethernet PoE+ 740W	AT 48 x Gigabit Ethernet managed Switch, 4x SFP uplink port, PoE+ 740W total PoE budget
Switch	AT-x530L-28GPX-901	24 x Gigabit Ethernet PoE+ 740W	AT 24 x Gigabit Ethernet PoE+ with advanced management features, 4x10 GB(SFP+) uplink ports, PoE+ 740W total PoE budget
Switch	AT-x530L-52GPX-901	48 x Gigabit Ethernet PoE+ 740W	AT 48 x Gigabit Ethernet PoE+ with advanced management features, 4x10GB (SFP+) uplink, 740W total PoE budget
Switch	AT-x530L-10GHXm-10	8 x 1/2.5/5 Gigabit Ethernet PoE++ 500W	8 x 1/2.5/5 Gigabit Ethernet PoE++ switch with advanced management features, 2x 10GB (SFP+) uplink, 500W total PoE budget
Switch	AT-x530L-18GHXm-10	16 x 1/2.5/5 Gigabit Ethernet PoE++ 720W	16 x 1/2.5/5 Gigabit Ethernet PoE++ switch with advanced management features, 2x 10GB (SFP+) uplink, 720W total PoE budget
Switch	AT-x530DP-28GHXm-10	20 x Gigabit Ethernet 4 x 1/2.5/5 Gigabit Ethernet dual hot swap psu's PoE++ 1480 W, not included	AT 20 x Gigabit Ethernet 4 x 1/2.5/5 Gigabit Ethernet PoE++ switch with advance management features 4 x 10GB (SFP+) uplink. PoE++ 1480 W total PoE budget. * hot swap psu's sold separately, can take two psu.
Switch	AT-PWR1200	Secondary Hot swap power supply	Hot swap power supply for AT-x530DP-28GHXm-10 switch.
Switch	AT-IE220-6GHX-980	4 x Gigabit Ethernet PoE++ 180W	AT Industrial rugged switch with 4 x Gigabit Ethernet DIN Rail Mount, optional PoE++ and optional 2x 10G (SFP+). 180W total PoE budget *Power supply sold separately

Switch	AT-IE220-10GHX-980	8 x Gigabit Ethernet PoE++ 240W	AT Industrial rugged switch with 8 x Gigabit Ethernet, optional PoE++ and optional 2x 10G (SFP+), 240W total PoE budget *Power supply sold separately
Switch	AT-IE340-12GP-980	8 x Gigabit Ethernet PoE++ 240W (8 + 8 PoE at/af)	AT Industrial rugged switch with 8 x Gigabit Ethernet 4x 1G SFP. PoE+ 240W (8 + 8 PoE at/af) *Power supply sold separately
Switch	AT-IE340-20GP-980	16 x Gigabit Ethernet PoE++ 240W	AT Industrial rugged switch with 16 x Gigabit Ethernet 4x 1G SFP. PoE+ 240W (8 + 8 PoE at/af) *Power supply sold separately
Switch	AT-IE048-480	480W @48Vdc, Industrial AC/DC power supply, DIN rail mount	AT Power supply for Rugged switches, 480W @48Vdc, Industrial AC/DC power supply, DIN rail mount
Switch	AT-IE048-240	240W @48Vdc, Industrial AC/DC power supply, DIN rail mount	AT Power supply for Rugged switches, 240W @48Vdc, Industrial AC/DC power supply, DIN rail mount
Switch	SWT-G11MGHP	11 Port Hardened Managed Gigabit Ethernet Switch with 60W PoE	Hardened 11 Port - 2 x 100/1000/2500FX + 1 x 100/1000FX SFP Ports and 8 x 10/100/1000TX Ports Managed Switch, four 1000Mbps TX with 30W PoE, four 1000Mbps TX Combo Ports with 60W PoE, Hardened 48VDC 480Watt (10A) DIN Rail High Temp Power Supply (-40°C to +71°C With -40°C Start-Up) Included
Switch	SWT-F11MGHP	11 Port Hardened Managed Megabit Ethernet Switch with 60W PoE	Hardened 3 FX SFP 100/1000/2500Mbps FX + 8 Port With 100Mbps TX Ports Managed Switch 60 Watt PoE, Hardened 48VDC 480Watt (10A) DIN Rail High Temp Power Supply (-40°C to +71°C With -40°C Start-Up) Included
Transmission-Fiber	SBP-303HF	Fiber Optic for PTZ	RJ-45 to Fiber mounting accessory for PTZ XNP-6320H/6321H, XNP-6550RH and QNP-6230H
Transmission-Fiber	TMC-FSTM1ACM-A	Mini 100M Media Converter (A)	Hardened mini media fiber converter (A), 100Mbps, ST connector, single-mode, 1 fiber, power supply included (not hardened), TMC-FSTM1-B required to work as a pair
Transmission-Fiber	TMC-FSTS1ACM-A	Mini 100M Media Converter (A)	Hardened mini media fiber converter (A), 100Mbps, ST connector, multi-mode, 1 fiber, power supply included (not hardened), TMC-FSTS1-B required to work as a pair
Transmission-Fiber	TMC-FSTM1PoE-M-A	100M Media Converter (A)	Hardened media fiber converter (A), 100Mbps, ST Connector, multi-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FSTM1-B required to work as a pair
Transmission-Fiber	TMC-FSTS1PoE-M-A	100M Media Converter (A)	Hardened media fiber converter (A), 100Mbps, ST Connector, single-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FSTS1-B required to work as a pair
Transmission-Fiber	TMC-FSTM1-B	100M Media Converter (B)	Hardened media fiber converter (B), cage mountable, 100Mbps, ST connector, multi-mode, 1 fiber, power supply included, TMC-FSTM1ACM-A or TMC-FSTM1PoE-M-A required to work as a pair
Transmission-Fiber	TMC-FSTS1-B	100M Media Converter (B)	Hardened media fiber converter (B), cage mountable, 100Mbps, ST connector, single-mode, 1 fiber, power supply included, TMC-FSTS1ACM-A or TMC-FSTS1PoE-M-A required to work as a pair
Transmission-Fiber	TMC-FSCM1ACM-A	Mini 100M Media Converter (A)	Hardened mini media fiber converter (A), 100Mbps, SC connector, multi-mode, 1 fiber, power supply included (not hardened), TMC-FSCM1-B required to work as a pair
Transmission-Fiber	TMC-FSCS1ACM-A	Mini 100M Media Converter (A)	Hardened mini media fiber converter (A), 100Mbps, SC connector, single-mode, 1 fiber, power supply included (not hardened), TMC-FSCS1-B required to work as a pair
Transmission-Fiber	TMC-FSCM1PoE-M-A	100M Media Converter (A)	Hardened media fiber converter (A), 100Mbps, SC Connector, multi-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FSCM1-B required to work as a pair
Transmission-Fiber	TMC-FSCS1PoE-M-A	100M Media Converter (A)	Hardened media fiber converter (A), 100Mbps, SC Connector, single-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FSCS1-B required to work as a pair
Transmission-Fiber	TMC-FSCM1-B	100M Media Converter (B)	Hardened media fiber converter (B), cage mountable, 100Mbps, SC connector, multi-mode, 1 fiber, power supply included, TMC-FSCM1ACM-A or TMC-FSCM1PoE-M-A required to work as a pair
Transmission-Fiber	TMC-FSCS1-B	100M Media Converter (B)	Hardened media fiber converter (B), cage mountable, 100Mbps, SC connector, single-mode, 1 fiber, power supply included, TMC-FSCS1ACM-A or TMC-FSCS1PoE-M-A required to work as a pair
Transmission-Fiber	TMC-GSFPM	Mini 1000M Multi-Rate Media Converter	10/100/1000Mbps Multi-Rate media converter, SFP, 100FX/1000FX selectable, small size, SFP module required
Transmission-Fiber	TMC-GSFP	1000M Multi-Rate Media Converter	10/100/1000Mbps Multi-Rate media converter, SFP, 100FX/1000FX selectable, SFP module required
Transmission-Fiber	TMC-GSFPPEM	Mini 1000M Multi-Rate Media Converter	10/100/1000Mbps Multi-Rate media converter, SFP, 100FX/1000FX selectable, small size, PoE+, SFP module required
Transmission-Fiber	TMC-GSFPPE30M	Mini 100M Media Converter	Hardened 100Mbps Media Converter, SFP, 48V PoE, Power Supply Included, 30w output, SFP module required
SFP Module	SFP-GRJC	SFP to RJ45	Copper 10/100/1000Mbps RJ45, MSA Compliant
SFP Module	SFP-FLCM202	Multi Mode SFP module	100Mbps, 1310nm, 2km, LC, 2 Fiber, Multi Mode, MSA Compliant
SFP Module	SFP-FLCS220	Single Mode SFP module	100Mbps, 1310nm, 20km, LC, 2 Fiber, Single Mode, MSA Compliant
SFP Module	SFP-FSCM102-A	Multi Mode SFP module A	100Mbps, 1310nm, 2km, SC, 1 Fiber, Pair with SFP-FSCM102-B, Multi Mode, MSA Compliant
SFP Module	SFP-FSCM102-B	Multi Mode SFP module B	100Mbps, 1550nm, 2km, SC, 1 Fiber, Pair with SFP-FSCM102-A, Multi Mode, MSA Compliant
SFP Module	SFP-FSCS120-A	Single Mode SFP module A	100Mbps, 1310nm, 20km, SC, 1 Fiber, Pair with SFP-FSCM102-B, Single Mode, MSA Compliant
SFP Module	SFP-FSCS120-B	Single Mode SFP module B	100Mbps, 1550nm, 20km, SC, 1 Fiber, Pair with SFP-FSCM102-A, Single Mode, MSA Compliant
SFP Module	SFP-GLCS215	Single Mode SFP module	100Mbps, 1310nm, 15km, LC, 2 Fiber, Single Mode, MSA Compliant
SFP Module	SFP-GLCS120-A	Single Mode SFP module A	100Mbps, 1310nm, 20km, LC, 1 Fiber, Pair with SFP-GLCS120-B, Single Mode, MSA Compliant
SFP Module	SFP-GLCS120-B	Single Mode SFP module B	100Mbps, 1550nm, 20km, LC, 1 Fiber, Pair with SFP-GLCS120-A, Single Mode, MSA Compliant
SFP Module	SFP-GLCM202	Multi Mode SFP module	100Mbps, 1310nm, 2km, 2 Fiber, LC, Multi Mode, MSA Compliant
Transmission-Accessory	SBP-C14	Card Cage Rack Mount	14 slot card cage rack, power supply included
Transmission-Accessory	SBP-C03	3 Unit Card Cage	3 slot card cage rack, power supply included
Transmission-Accessory	SBP-C14PS1	Rack Mount Power Supply	90-264 VAC 50/60hz power supply for SBP-C14
Transmission-Accessory	SBP-C14BP1	1 Slot Blank Filler Panel	1 slot blank filler panel for SBP-C14 card cage
Transmission-Accessory	SBP-C14BP3	3 Slot Blank Filler Panel	3 slot blank filler panel for SBP-C14 card cage
Transmission-Accessory	SEB-UDR	Universal Din Rail Adapter	Universal DIN-Rail mount adapter kit that allow the Hanwha product to be mounted on the adaptor in a vertical axis configuration
Transmission-Network	TEU-F01	Single Channel over UTP	Single-Channel Ethernet over UTP with Pass-through PoE
Transmission-Network	TEC-F01	Single Channel over COAX	Single-Channel Ethernet over COAX with Pass-through PoE
Transmission-Network	TEU-F04	Four Channels over UTP	Four-Channel Ethernet over UTP with Pass-through PoE
Transmission-Network	TEC-F04	Four Channels over COAX	Four-Channel Ethernet over COAX with Pass-through PoE
Transmission-Network	TEU-F16	16 Channels over UTP	Sixteen-Channel Ethernet over UTP with Pass-through PoE
Transmission-Network	TEC-F16	16 Channels over COAX	Sixteen-Channel Ethernet over COAX with Pass-through PoE
Transmission-Network	TER-F01	Ethernet Repeater	100 Meter Ethernet Repeater Pass-Through PoE Power
Transmission-Network	TER-F01PD	Ethernet Repeater	100 Meter Ethernet Repeater External Power

Analog High Definition Cameras

Camera - Analog HD	HCF-8011RV	5MP IR Analog HD Fisheye Camera	5MP (2560x1944) resolution, 20FPS @5MP, IR Viewable Length: 10m(32.8ft), BLC, Day & Night (ICR), WDR 120dB, Coaxial communication (ACP / Coaxint), Selectable universal output (AHD / CVBS), IP66, IK10, Power 12VDC/24VAC, Operating Temperature -30°C ~ +55°C(-22°F ~ +131°F), hard coated dome bubble, white color
Camera - Analog HD	HCF-8010V	5MP Analog HD Fisheye Camera	5MP (2560x1944) resolution, 20FPS @5MP, BLC, Day & Night (ICR), Digital Wide Dynamic Range, Coaxial communication (HD / SD mode), Selectable universal output (TVI / AHD / CVBS), IP66, IK10, Power 12VDC/24VAC
Camera - Analog HD	HCB-7000A	4MP Wisenet HD+ Box Camera	Wisenet HD+ 4MP box camera, AHD or CVBS formats are available, RS485 /Coaxial Control, true D/N, 24VAC/12VDC (Require 4MP or higher CS Mount Lens)
Camera - Analog HD	HCO-7070RA	4MP Wisenet HD+ Bullet Camera	Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, manual vari-focal Lens (3.1X) (3.2-10mm), true D/N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10
Camera - Analog HD	HCO-7010RA	4MP Wisenet HD+ Bullet Camera	Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, 2.8 mm fixed lens, true D/N, 12VDC, IR distance 65 feet, IP66/IK10
Camera - Analog HD	ACO-8020R	5MP Analog HD IR Bullet	Wisenet A Series 5MP IR bullet camera, AHD / TVI / CVI / CVBS formats are available, 5MP @ 30 FPS, (CVI supports up to 4M), 3.6mm fixed focal lens, FOV H: 94° / V: 54°, DWDR, IR distance 20m(65.6 ft), day & night, IP67, IK10, 12VDC, Analog, white
Camera - Analog HD	ACE-8020R	5MP Turret Camera	Wisenet A Series 5MP IR turret camera, AHD / TVI / CVI / CVBS formats are available, 5MP @ 30 FPS, (CVI supports up to 4M), 3.6mm fixed focal lens, FOV H: 94° / V: 54°, DWDR, IR distance 20m(65.6 ft), day & night, IP67, IK10, 12VDC, Analog, white
Camera - Analog HD	HCO-7020RA	4MP Wisenet HD+ Bullet Camera	Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, 4.0 mm fixed lens, true D/N, 12VDC, IR distance 82 feet, IP66/IK10
Camera - Analog HD	HCO-7030RA	4MP Wisenet HD+ Bullet Camera	Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, 6.0 mm fixed lens, true D/N, 12VDC, IR distance 98 feet, IP66/IK10
Camera - Analog HD	ACV-8080R	5MP Analog HD IR Outdoor Dome	Wisenet A Series 5MP IR vandal dome camera, AHD / TVI / CVI / CVBS formats are available, 5MP @ 30fps (CVI supports up to 4M), motorized vari-focal lens 3x (3.5-10.5mm) (114°~ 33.9°), DWDR, IR distance 20m(65.6 ft), day & night, IP66, IK10, 12VDC, Analog, white
Camera - Analog HD	ACV-8081R	5MP Analog HD IR Outdoor Dome	Wisenet A Series 5MP IR vandal dome camera, AHD / TVI / CVI / CVBS formats are available, 5MP @ 30fps, motorized vari-focal lens 3x (3.5-10.5mm) (99.1°~ 30.3°), WDR, IR distance 20m(65.6 ft), day & night, IP66, IK10, 12VDC, Analog, white
Camera - Analog HD	HCV-7070RA	4MP Wisenet HD+ Outdoor Dome Camera	Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, manual vari-focal Lens (3.1X) (3.2-10mm), true D/N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10
Camera - Analog HD	HCV-7010RA	4MP Wisenet HD+ Outdoor Dome Camera	Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, 2.8 mm fixed lens, true D/N, 12VDC, IR distance 65 feet, IP66/IK10
Camera - Analog HD	HCV-7020RA	4MP Wisenet HD+ Outdoor Dome Camera	Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, 4.0 mm fixed lens, true D/N, 12VDC, IR distance 82 feet, IP66/IK10
Camera - Analog HD	HCV-7030RA	4MP Wisenet HD+ Outdoor Dome Camera	Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, 6.0 mm fixed lens, true D/N, 12VDC, IR distance 98 feet, IP66/IK10
Camera - Analog HD	HCD-7070RA	4MP Wisenet HD+ Indoor Dome Camera	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, manual vari-focal Lens (3.1X) (3.2-10mm), true D/N, 24VAC/12VDC, IR distance 65 feet
Camera - Analog HD	HCD-7010RA	4MP Wisenet HD+ Indoor Dome Camera	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, 2.8 mm fixed lens, true D/N, 12VDC, IR distance 65 feet
Camera - Analog HD	HCD-7020RA	4MP Wisenet HD+ Indoor Dome Camera	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, 4.0 mm fixed lens, true D/N, 12VDC, IR distance 82 feet
Camera - Analog HD	HCD-7030RA	4MP Wisenet HD+ Indoor Dome Camera	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, 6.0 mm fixed lens, true D/N, 12VDC, IR distance 98 feet
Camera - Analog HD	HCB-6000	2MP Analog HD Box	Wisenet HD+ 2MP, Full HD(1080p) 30fps box camera, AHD/TVI/CVI/CVBS, 120 dB true WDR, RS485 /Coaxial Control, true D/N, 24VAC/12VDC (Require 2MP or higher CS Mount Lens)
Camera - Analog HD	HCB-6001	2MP Analog HD Box	Wisenet HD+ 2MP, Full HD(1080p) 30fps box camera, AHD/TVI/CVI/CVBS, 120 dB true WDR, RS485 /Coaxial Control, simple focus, true D/N, 24VAC/12VDC (Require 2MP or higher CS Mount Lens)
Camera - Analog HD	HCD-6070R	2MP Analog HD IR Indoor Dome	Wisenet HD+ 2MP, Full HD(1080p) 30fps IR indoor dome camera, AHD/TVI/CVI/CVBS, manual Vari-focal Lens (3.1X) (3.2-10mm), 120 dB true WDR, true D/N, 24VAC/12VDC, IR distance 65 feet
Camera - Analog HD	HCD-6080R	2MP Analog HD IR Indoor Dome	Wisenet HD+ 2MP, Full HD(1080p) 30fps IR indoor dome camera, AHD/TVI/CVI/CVBS, motorized vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true D/N, 24VAC/12VDC, IR distance 65 feet
Camera - Analog HD	HCD-6010	2MP Wisenet HD+ Indoor Dome Camera	Wisenet HD+ 2MP indoor dome camera, AHD, CVI, TVI, CVBS formats are available, 2.8 mm fixed lens, true D/N, 12VDC

Recording - Hybrid	ARD-810	8CH AHD, TVI, CVI, CVBS, IP Recorder	A-Series 8CH DVR, AHD / TVI / CVI up to 5MP Half, CVBS (NTSC/Pal), Max. Analog 8CH + NW 2CH(2MP), 12/12fps@5MP(Half), 15/12fps@4MP(Half), 15/12fps@2MP recording, H.265/H.264/MJPEG, Recording Bandwidth Max. 40Mbps. 1CH audio input/ 1CH audio output, 4 alarm input and 1 relay output, coaxial control, HDMI/VGA video output, 1 x spot monitor output, QR code, up to one 6TB SATA HDD (Max. 6TB).
Recording - Hybrid	ARD-810-2TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	A-Series 8CH DVR, 2TB HDD, AHD / TVI / CVI up to 5MP Half, CVBS (NTSC/Pal), Max. Analog 8CH + NW 2CH(2MP), 12/12fps@5MP(Half), 15/12fps@4MP(Half), 15/12fps@2MP recording, H.265/H.264/MJPEG, Recording Bandwidth Max. 40Mbps. 1CH audio input/ 1CH audio output, 4 alarm input and 1 relay output, coaxial control, HDMI/VGA video output, 1 x spot monitor output, QR code, up to one 6TB SATA HDD (Max. 6TB).
Recording - Hybrid	HRX-835	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), Max. Analog 8CH + NW 10CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 32Mbps. 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 4 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-835-4TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 4TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), Max. Analog 8CH + NW 10CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 32Mbps. 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 4 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-835-6TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 6TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), Max. Analog 8CH + NW 10CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 32Mbps. 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 4 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-835-8TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 8TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), Max. Analog 8CH + NW 10CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 32Mbps. 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 4 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-835-12TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 12TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), Max. Analog 8CH + NW 10CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 32Mbps. 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 4 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-835-16TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 16TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), Max. Analog 8CH + NW 10CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 32Mbps. 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 4 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-835-24TB	8CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 24TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), Max. Analog 8CH + NW 10CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 32Mbps. 8CH audio input/ 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 4 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-435	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), • Max. Analog 4CH + NW 6CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 2 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-435-2TB	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 2TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), • Max. Analog 4CH + NW 6CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 2 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-435-4TB	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 4TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), • Max. Analog 4CH + NW 6CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 2 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-435-6TB	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 6TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), • Max. Analog 4CH + NW 6CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 2 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-435-8TB	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 8TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), • Max. Analog 4CH + NW 6CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 2 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-435-12TB	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 12TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), • Max. Analog 4CH + NW 6CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 2 SATA HDDs (6TB/HDD)
Recording - Hybrid	ARD-410	4CH AHD, TVI, CVI, CVBS, IP Recorder	A-Series 4CH DVR, AHD / TVI / CVI up to 5MP Half, CVBS (NTSC/Pal), Max. Analog 4CH + NW 2CH(2MP), 12/12fps@5MP(Half), 15/12fps@4MP(Half), 15/12fps@2MP recording, H.265/H.264/MJPEG, Recording Bandwidth Max. 30Mbps. 1CH audio input/ 1CH audio output, 4 alarm input and 1 relay output, coaxial control, HDMI/VGA video output, 1 x spot monitor output, QR code, up to one 6TB SATA HDD (Max. 6TB).
Recording - Hybrid	ARD-410-2TB	4CH AHD, TVI, CVI, CVBS, IP Recorder	A-Series 4CH DVR, 2TB HDD, AHD / TVI / CVI up to 5MP Half, CVBS (NTSC/Pal), Max. Analog 4CH + NW 2CH(2MP), 12/12fps@5MP(Half), 15/12fps@4MP(Half), 15/12fps@2MP recording, H.265/H.264/MJPEG, Recording Bandwidth Max. 30Mbps. 1CH audio input/ 1CH audio output, 4 alarm input and 1 relay output, coaxial control, HDMI/VGA video output, 1 x spot monitor output, QR code, up to one 6TB SATA HDD (Max. 6TB).
Recording - Hybrid	HRX-434	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), • Max. Analog 4CH + NW 6CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 1 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-434-2TB	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 2TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), • Max. Analog 4CH + NW 6CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 1 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-434-4TB	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 4TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), • Max. Analog 4CH + NW 6CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 1 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-434-6TB	4CH AHD, TVI, CVI, CVBS, IP Recorder	Wisenet HD+ Pentabrid DVR AHD (up to 8MP), - 6TB Raw Storage.TVI (up to 8MP), CVI (up to 5MP), CVBS and IP (up to 8MP), • Max. Analog 4CH + NW 6CH, up to 8MP, 8/8fps@8MP, 12/12fps@5MP recording (frame rate at higher resolutions will vary), triple codec H.265/H.264/MJPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, up to 1 SATA HDDs (6TB/HDD)

DVR's Accessories

Lenses

Lens	SLA-T2480BA	Bandit Barrier	Bandit Barrier 2.4mm fixed lens (138°), compatible with PNM-9000QB, and XNB-6002 (not included), cable length 8m (26 feet), black color
Lens	SLA-C-E24	Canon EF 24mm f/1.4L II USM	Canon 24mm f1.4L, Auto-Iris (EF 24mm f/1.4L II USM) : Horizontal field of view: 8K 62.1° . CarePak 4 Years warranty
Lens	SLA-C-E50	Canon EF 50mm f/1.2L USM	Canon 50mm f1.2, Auto-Iris (EF 50mm f/1.2 USM) : Horizontal field of view: 8K 31.6° . CarePak 4 Years Warranty
Lens	SLA-C-E2470	Canon EF 24-70mm f/2.8L II USM	Canon 24-70mm f/2.8L II USM (EF 24-70mm f/2.8L USM) : Horizontal field of view :8K 62.1° - 23.2° . CarePak 4 Years Warranty
Lens	SLA-C-E70200	Canon EF 70-200mm f/2.8 IS III USM	Canon 70-200mm f2.8L, Auto-Iris, Vari Focal (EF 70-200mm f/2.8L USM) : Horizontal field of view: 8K 23.2° ~ 8.3° , CarePak 4 Years Warranty
Lens	SLA-C-I3910	1/1.8" 3.9-10mm (i-CS Mount)	1/1.8" 3.9-10mm F1.5 Varifocal, HD Series P-iris (i-CS Mount) Day/Night IR (12 MP capable) for AI Box Camera (PNB-A9001)
Lens	SLA-C-I2885	1/2.7" 2.8-8.5mm (i-CS Mount)	1/2.7" 2.8-8.5mm F1.2 Varifocal, HD Series P-iris (i-CS Mount) Day/Night IR (8 MP capable) for WN7 Box Cameras (XNB-9002 and XNB-8002)
Lens	SLA-T1080F	1.6mm Lens/Imager straight body for XNB-6001 (8.0m cable)	1.6mm fixed lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.03 Lux, 120dB WDR, 187° horizontal field of view, 8 meters cable (26 feet cable)

Lens	SLA-T2480	2.4mm Lens/Imager straight body for XNB-6001 (8.0m cable)	2.4mm fixed lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.45 Lux, 120dB WDR, 138° horizontal field of view, 8 meters / 26 feet cable
Lens	SLA-T2480V	2.4mm Lens/Imager right angle body for XNB-6001 (8.0m cable)	2.4mm fixed lens module, compatible with the XNB-6001, right angle body style, 2MP @ 60fps, 0.45 Lux, 120dB WDR, 138° horizontal field of view, 8 meters / 26 feet cable
Lens	SLA-T4680	4.6mm Lens/Imager straight body for XNB-6001 (8.0m cable)	4.6mm pinhole lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.06 Lux, 120dB WDR, 73° horizontal field of view, 8 meters / 26 feet cable
Lens	SLA-T4680V	4.6mm Lens/Imager right angle body for XNB-6001 (8.0m cable)	4.6mm pinhole lens module, compatible with the XNB-6001, right angle body style, 2MP @ 60fps, 0.06 Lux, 120dB WDR, 73° horizontal field of view, 8 meters / 26 feet cable
Lens	SLA-T2480WA	Outdoor 2.4mm Lens/Imager straight body for XNB-6002, and PNM-9000QB (8.0m cable)	Outdoor rated 2.4mm fixed lens module, straight body style, compatible with PNM-9000QB and XNB-6002, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters / 26 feet cable, IP66, NEMA 4X, IK10, Operating temperature -30°C+55°C(-22°F +131°F)
Lens	SLA-T2480WDA	Outdoor 2.4mm Lens/Imager Dome body for XNB-6002, and PNM-9000QB (8.0m cable)	Outdoor rated 2.4mm fixed lens module, Dome style, compatible with PNM-9000QB and XNB-6002, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters / 26 feet cable, IP66, NEMA 4X, IK10, Operating temperature -30°C+55°C(-22°F +131°F)
Lens	SLA-T4680A	4.6mm Lens/Imager straight body for XNB-6002, and PNM-9000QB (8.0m cable)	4.6mm pinhole lens module, compatible with PNM-9000QB and XNB-6002, straight body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters / 26 feet cable
Lens	SLA-T4680VA	4.6mm Lens/Imager right angle body for XNB-6002, and PNM-9000QB (8.0m cable)	4.6mm pinhole lens module, compatible with PNM-9000QB and XNB-6002, right angle body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters / 26 feet cable
Lens	SLA-T2480A	2.4mm Lens/Imager straight body for XNB-6002, and PNM-9000QB (8.0m cable)	2.4mm fixed lens module, compatible with PNM-9000QB and XNB-6002, straight body style, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters / 26 feet cable
Lens	SLA-T2480VA	2.4mm Lens/Imager right angle body for XNB-6002, and PNM-9000QB (8.0m cable)	2.4mm fixed lens module, compatible with PNM-9000QB and XNB-6002, right angle body style, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters / 26 feet cable
Lens	SLA-T1080FA	1.6mm Lens/Imager straight body for XNB-6002, and PNM-9000QB (8.0m cable)	1.6mm fixed lens module, compatible with PNM-9000QB and XNB-6002, straight body style, 2MP @ 30fps, 0.03 Lux, 187° horizontal field of view, 8 meters / 26 feet cable
Lens	SLA-H-4680VA	Height strip with 2MP pinhole lens	Height strip with 4.6mm pinhole lens module, compatible with PNM-9000QB, right angle body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters / 26 feet cable
Lens	SLA-T2880BA	Bandit Barrier	Bandit Barrier 2.8mm fixed lens (107.4°), compatible with PNM-9000QB, and XNB-6002 (not included), cable length 8m (26 feet), black color
Lens	SLA-T4680DA	Door Jamb Lens (black)	Door Jamb head with a 4.6mm lens, compatible with PNM-9000QB, and XNB-6002 (not included), cable length 8m (26 feet), black color
Lens	SLA-T4680DSA	Door Jamb Lens (silver)	Door Jamb head with a 4.6mm lens, compatible with PNM-9000QB, and XNB-6002 (not included), cable length 8m (26 feet), silver color
Lens	SLA-T4680D	Door Jamb Lens (black)	Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, black color
Lens	SLA-T4680DS	Door Jamb Lens (silver)	Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, silver color
Lens	SLA-T4680DW	Door Jamb Lens (white)	Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, white color
Lens	SLA-T-M410DN	Megapixel DC-iris Lens	Megapixel Lens, image sensor from 1/2.3" up to 1/1.7", Up to 12MP resolution, Vari-focal (4~10mm), DC auto iris, CS-Mount, Compatible with: XNB-6005/8000, PNB-A9001
Lens	SLA-T-M1250DN	Megapixel DC-iris Lens	Megapixel Lens, image sensor from 1/2.3" up to 1/1.7", Up to 12MP resolution, Vari-focal (12~50mm), DC auto iris, CS-Mount, Compatible with: XNB-6005/8000, PNB-A9001
Lens	SLA-T-M940DN	Megapixel DC-iris Lens	Lens, 1/2.3", Up to 4K Vari-focal(9~40mm), Auto DC IRIS, CS-Mount, compatible with: XNB-6000, HCB-6000/6001/7000/7000A
Lens	SLA-2M2400P	PNM-9322VQP Lens module	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens. FoV: H: 135.4°, V: 71.2° for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M2800P	PNM-9322VQP Lens module	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens. FoV: H: 107.4°, V: 62.2°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M3600P	PNM-9322VQP Lens module	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens. FoV: H: 94.8°, V: 49.3°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M6000P	PNM-9322VQP Lens module	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens. FoV: H: 50.4°, V: 28.8°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M1200P	PNM-9322VQP Lens module	1/2.8" 2MP CMOS with a 12.0mm fixed focal lens. FoV: H: 26.3°, V: 14.9°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-5M3700P	PNM-9322VQP Lens module	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens. FoV: H: 97.5°, V: 71.9° for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-5M4600P	PNM-9322VQP Lens module	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens. FoV: H: 77.9°, V: 57.9° for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-5M7000P	PNM-9322VQP Lens module	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens. FoV: H: 50.7°, V: 37.8° for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M2400Q	PNM-9000VQ Lens module	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens. FoV: H: 135.4°, V: 71.2° for the PNM-9000VQ
Lens	SLA-2M2800Q	PNM-9000VQ Lens module	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens. FoV: H: 107.4°, V: 62.2°, for the PNM-9000VQ
Lens	SLA-2M3600Q	PNM-9000VQ Lens module	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens. FoV: H: 94.8°, V: 49.3°, for the PNM-9000VQ
Lens	SLA-2M6000Q	PNM-9000VQ Lens module	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens. FoV: H: 50.4°, V: 28.8°, for the PNM-9000VQ
Lens	SLA-5M3700Q	PNM-9000VQ Lens module	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens. FoV: H: 97.5°, V: 71.9° for the PNM-9000VQ
Lens	SLA-5M4600Q	PNM-9000VQ Lens module	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens. FoV: H: 77.9°, V: 57.9° for the PNM-9000VQ
Lens	SLA-5M7000Q	PNM-9000VQ Lens module	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens. FoV: H: 50.7°, V: 37.8° for the PNM-9000VQ
Lens	SLA-5M3700D	PNM-9000VD Lens module	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens. FoV: H: 97.5°, V: 71.9° for the PNM-9000VD
Lens	SLA-5M4600D	PNM-9000VD Lens module	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens. FoV: H: 77.9°, V: 57.9° for the PNM-9000VD
Lens	SLA-5M7000D	PNM-9000VD Lens module	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens. FoV: H: 50.7°, V: 37.8° for the PNM-9000VD
Lens	SLA-2M2402D	PNM-7002VD Lens module	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens. FoV: H: 135.4°, V: 71.2°, for the PNM-7002VD
Lens	SLA-2M2802D	PNM-7002VD Lens module	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens. FoV: H: 107.4°, V: 62.2°, for the PNM-7002VD
Lens	SLA-2M3602D	PNM-7002VD Lens module	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens. FoV: H: 94.8°, V: 49.3°, for the PNM-7002VD
Lens	SLA-2M6002D	PNM-7002VD Lens module	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens. FoV: H: 50.4°, V: 28.8°, for the PNM-7002VD
Lens	SLA-M2890DN	Megapixel DC-iris Lens	Lens, 1/2.8", 3 MP, Vari-focal (2.8-9.0mm), Auto DC Iris, CS-Mount
Lens	SLA-M2890PN	Megapixel P-iris Lens	Lens, 1/2.8", 3 MP, Vari-focal (2.8-9.0mm), Auto P Iris, CS-Mount
Lens	SLA-F-M1550DNL	Megapixel DC-iris Lens	Lens, 1/2.7", 3 MP, Vari-focal (15-50mm), Auto DC Iris, CS-Mount, Tele Range 3.3x

Installation Solution

Accessory	SBP-300BW1	Table top mount for High speed LPR (TNO-7180RLP) camera	Table top mount for (TNO-7180RLP) High Speed Global shutter LPR camera. Includes conduit hole 3/4" (19.1mm) (M25)
Accessory	SBP-187WMW	Wall & Pole Mount for High speed LPR (TNO-7180RLP) camera	Wall & Pole Mount for (TNO-7180RLP) High Speed Global shutter LPR camera (Steel strap sold separately)
Accessory	SBD-137WMA	Wall Adapter Plate	Wall adaptor plate to make a Q-Core camera compatible with SBP-137WMW and SBP-137WMW1
Accessory	SBD-110GP1	Gangbox Plate	Adaptor plate for Single, Double, 4" Octagon, supported cameras: QNV-C8011R/C8012/C9011R, QND-6011/21, 8011/21, QNF-8010, 9010, LND-6012R/22R, QND-6012R/22R, 7012R/22R, QNE-8011R/21R, ANE-L6012R, L7012R
Accessory	SPM-4210	Network I/O Box	Network I/O box for PTZ plus, 4-configurable I/O ports, Audio I/O, PoE. Compatible with XNP-9300R/9250R/9250 XNP-8300R/8250R/8250, XNP-6400R/6400R/6400, PNM-C12083RVD/C7083RVD/12082RVD/7082RVD
Accessory	SBS-165TM	Tilt Mount for Video Intercom TID-600R	Tilt Mount for TID-600R, 30° Tilt angle, Installable on Left or Right
Accessory	SHS-165F	Flush Mount for Video Intercom TID-600R	Flush Mount for TID-600R, 2 Cover plates included (White, Dark Grey)
Accessory	SBC-160BF	Black Skin Cover	Black Skin Cover for XNF-9013RV, QTY of 6
Accessory	SBC-165W	White Cover for Video Intercom TID-600R	White Skin Cover for TID-600R
Accessory	TA-18	Flush Mount for TCIS-2 and TCIS-3	Turbine Compact Flush-Mount Back Box for TCIS-2 and TCIS-3
Accessory	TA-14	Windscreens for TCIS-2 and TCIS-3	Windscreens Microphone for TCIS-2 and TCIS-3
Accessory	TA-13	Onwall Back Box for TMIS-1	Turbine Mini On Wall Back Box White, Compatible with TMIS-1
Accessory	TA-5	Bracket for 2 Gang Back Box for TCIS-2 and TCIS-3	Bracket for US 2 GANG Double Depth back Box, compatible with TCIS-2 and TCIS-3
Accessory	TA-1	Onwall Back Box for TCIS-2 and TCIS-3	Turbine Compact Onwall Back Box, IP66, IK10 Aluminum ally, Grey, Compatible with TCIS-2 and TCIS 3
Accessory	TKIS-2	External Relay for Audio Intercoms	Zenitel Turbine Intercom module used as an external relay for the Zenitel Turbine Intercoms, Ports-I/O, Relay, 10W Audio Out, DIN-rail mountable, Avaya and CISCO Certified, UL
Accessory	SBD-110GP	Gangbox Plate	Adaptor plate for Single, Double, 4" Octagon, supported cameras (HCD-7010R / 7020R / 7030R, XND-6010 / 6020R / 8020R / 8030R / 8040R, 6012R / 6022R / 6032R, HCD-7010RA / 7020RA / 7030RA, LND-6012R / 6022R / 6032R / 6072R, QND-6010R / 6012R / 6020R / 6022R / 6030R / 6032R, QND-7010R / 7012R / 7022R / 7020R / 7030R / 7032R / 7080R, QND-8010R / 8020R / 8030R, SCD-8013 / 6023R) Pack of 5
Accessory	SBP-B-100P	Gang box Plate	Single Gang Box Converter Plate for XNV-6011
Accessory	STB-2000	ATM mounting bracket	ATM mounting bracket for remote head lens, compatible with SLA-T2480, SLA-T2480A, SLA-T4680, SLA-T4680A lenses
Accessory	SBP-329HM	Cap Adapter	Large Cap adapter (outdoor) for the Multi-Directional cameras PNM-9080VQ and PNM-9081VQ (Will fit the following accessories: SBP-300WM, SBP-300LM, SBP-300CM) (Will not fit the SBP-300WM1)
Accessory	SBP-168HM	Cap Adapter	Cap Adapter for the XNP-6120H
Accessory	SBP-140CMT	Tile Grid Ceiling Mount	Tile Grid Ceiling Mount Pack of 4 , Compatible with QND-6011/6021, QND-8011/8021 QNF-8010/9010, QND-6012R/6022R/6082R, QNV-C9011R/C8011R/C8012, LND-6012R/6022R/6072R, QNE-8011R/8021R, ANE-L6012R/L7012R/L7012L, QNV-C8083R/C9083R, XND-8082R/9082RV, X plus indoor dome, P AI indoor dome
Accessory	SBP-140HMW	Cap Adapter	Cap Adapter for QNV-C9083R, QNV-C8083R
Accessory	SBP-200HMW	Cap Adapter	Cap Adapter for the PNM-9000VD, PNM-7002VD and PNM-C16013RVQ Multi-sensor
Accessory	SBP-201HMW	Cap Adapter	Cap Adapter for the PNM-9000VD, PNM-7002VD Multi-sensor
Accessory	SBP-300HM8	Cap Adapter	Cap Adapter for the PND-9080R, XND-6080 / 6080R / 6080R / 6080RV, XND-8080R / 8080RV, XND-L6080R / L6080RV / L6080V

Accessory	SBP-300HM7	Cap Adapter	Small cap adapter (aluminum), accessory for XNV-6011, SCD-6013 / 6023R / 6025R, QND-6010R / 7010R / 7020R / 7030R, XND-6010 / 6020R, XND-8020R / 8030R / 8040R, XNV-6011, HCD-6010 / 6020R / 7010R / 7010RA / 7020R / 7020RA / 7030R / 7030RA, LND-6011R / 6021R / 6031R.
Accessory	SBP-300HMW7	Cap Adapter	Small cap adapter (aluminum), accessory for XNV-6011W, QND-8010R / 8020R / 8030R, QND-6012R / 6022R / 6032R, QND-7012R / 7022R / 7032R, LND-6010R / 6012R / 6020R / 6022R / 6030R / 6032R, HCF-8010V white color.
Accessory	SBP-300HM6	Cap Adapter	Medium Cap Adapter (Aluminum), accessory for PNV-9080R, XNV-6120 / 6120R / 6080 / 6080R / 6085 / 6085V, XNV-8080R, XNV-L6080 / L6080R, PNM-7000VD
Accessory	SBP-300HM5	Cap Adapter	Small cap adapter (aluminum), accessory for 5MP fisheye cameras (SNF-8010, SNF-8010VM, XNF-8010R / 8010RV / 8010RVM, PNF-9010R / 9010RV / 9010RVM), QNE-6080RV, QNV-7080RV, Works with Mounts (SBP-300CM, SBP-300LM, SBP-300WM, SBP-300WMM)
Accessory	SBP-301HM3	Cap Adapter	Medium Cap Adapter Accessory, HCP-6230 / 6320 / 6320A, XNP-6320 / 6321, QNP-6230), (Ivory color).
Accessory	SBP-301HMW3	Cap Adapter	Medium Cap Adapter Accessory, compatible with QNP-6250, QNP-6320, (White color)
Accessory	SBP-301HM5	Cap Adapter	Small Cap Adapter (Aluminum), accessory for SCV-6083R / 6023R / 6085R, LNV-6071R, QNV-6070R / 6071R / 7080R / 7081R, HCV-6070R / 6080R / 6080RSD / 7070R / 7070RA / 7080R / 7080RVP, XNP-6040H, (Ivory color).
Accessory	SBP-099HMW	Cap Adapter	Small cap adapter, accessory for Q-mini cameras: QNF-8010, QNF-9010, QND-6011, QND-6021, QND-8011, QND-8021 (White color)
Accessory	SBP-300HMW5	Cap Adapter	Small cap adapter, accessory for XNF-8010RV / 8010RVV, QNE-6080RVV / 7080RVV (White color).
Accessory	SBP-150CMI	Ceiling mount	Ceiling mount (150mm) (w/o conduit holes), compatible with all 1.5" hanging mounts and extension pipes: SBP-C15P, SBP-150CMP/300CMP/900CMP
Accessory	SBP-300CMI	Ceiling mount	Pendant Mount Accessory, Length: 300mm (11.81") with female 1.5" pipe thread
Accessory	SBP-302CM-06	Extension pendant pipe 6"	Extension pendant pipe 6" long, fit the SBP-302CMB (Mounting backbox), SBP-302CMA (mounting plate), SBP-302CM (telescopic pendant mount) and the extension pipes SBP-302CM-12 and SBP-302CM-36
Accessory	SBP-301HMW2	Cap Adapter	Small cap adapter (aluminum) accessory, (QNV-6072R / 6082R / 8080R / 7082R, LNV-6070R / 6072R), (White color).
Accessory	SBP-317HMWP	Cap Adapter	Hanging Cap Adapter with extra storage space. Can be used with PNM-9084RQZ / PNM-9084RQZ1 / PNM-9085RQZ / PNM-9085RQZ1. Mount screw size : PF 1 1/2", White
Accessory	SBP-315HMW	Cap Adapter	Cap Adapter for PNM-9084RQZ(1), PNM-9085RQZ(1)
Accessories	SBP-317HMW	Cap Adapter	Can be used with PNM-9084RQZ / PNM-9084RQZ1 / PNM-9085RQZ / PNM-9085RQZ1. Mount screw size : PF 1 1/2", (White color).
Accessory	SBP-122HM	Cap Adapter	Small cap adapter for: (QND-7080R / 6070R / 6071R / 7081R), QNV-7010R/20R/30R, QNV-6010R/20R/30R, XNV-6010/20R, XNV-8020R/30R/40R, HCD-6070R / 6080R / 7070R / 7070RA / 7080R, HCV-7010R / 7010RA / 7020R / 7020RA / 7030R / 7030RA, LND-6071R, LNV6011R / 6021R / 6031R, SCD-6083R / 6085R)
Accessory	SBP-122HMW	Cap Adapter	Cap adapter for the (ANV-L6012R / L7012R, QND- 6072R / 7082R / 6082R / 8080R, QNV-6012R / 6022R / 6032R / 7012R / 7022R / 7032R / 8010R / 8020R / 8030R, LND-6070R / 6072R, LNV-6010R / 6012R / 6020R / 6022R / 6030R / 6032R, HCF-8010V), white color
Accessory	SBP-167HM	Cap Adapter	Hanging cap (ivory) for the indoor X Plus dome cameras
Accessory	SBP-250HMW	Cap Adapter	Cap adapter for the PNM-9084QZ1, PNM-9084QZ, PNM-8082VT, PNM-9022V, PNM-C9022RV, PNM-9031RV, PNM-9002VQ, PNM-C16083RV, PNM-C32083RVQ
Accessory	SBP-276HMW	Cap Adapter	Cap adapter for the PNM-9084QZ, PNM-8082VT, PNM-9022V, PNM-9031RV, PNM9002VQ
Accessory	SBP-160HMW1	Cap Adapter	Hanging cap compatible with: XNF-9010RV / 9010RVM, XND-9082RV / 8082RV, XND- 6081V / 6081VZ / 6081RV / 6081REV, XND-8081RV / 8081REV, PND-A9081RV, PND-A6081RV, XND-6083RV / C7083RV / 8081VZ / 8083RV / C8083RV / 8093RV / 9083RV / C9083RV, XNV-C6083R / C7083R / C8083R / C9083R, TNF-9010, white color.
Accessory	SBP-167HMW	Cap Adapter	Hanging cap compatible with: XNF-9010RV / 9010RVM, XND-9082RV / 8082RV, XND- 6081V / 6081VZ / 6081RV / 6081REV, XND-8081RV / 8081REV, PND-A9081RV, PND-A6081RV, XND-6083RV / C7083RV / 8081VZ / 8083RV / C8083RV / 8093RV / 9083RV / C9083RV, XNV-C6083R / C7083R / C8083R / C9083R, TNF-9010, white color.
Accessory	SBP-187HM	Cap Adapter	Hanging cap (ivory) for the outdoor X Plus dome cameras
Accessory	SBP-180HMW1	Cap Adapter	Hanging cap compatible with: XNV-8082R / 8093R / 9082R, XNV- 6083R / 8083R / 9083R, XNV-6123R / 6081 / 6081R / 6081Z / 6081RE / 8081RE / 8081R / 8081Z, PNV-A9081R / A6081R / A9081R / PNV-A6081R-E1T / PNV-A6081R-E2T, XNV-6083RZ / 8083RZ / 9083RZ, white color.
Accessory	SBP-187HMW	Cap Adaptor	Hanging cap XNV-8082R / 8093R / 9082R, XNV- 6083R / 8083R / 9083R, XNV-6123R / 6081 / 6081R / 6081Z / 6081RE / 8081RE / 8081R / 8081Z, PNV-A9081R / A6081R / A9081R / A9081R / A9081R / A9081R / A9081R, white color.
Accessory	SBC-170C	Silver Skin Cover	Silver Skin Cover for TNV-8011C
Accessory	SBC-170CB	Black Skin Cover	Black Skin Cover for TNV-8011C
Accessory	SBC-170CW	White Skin Cover	White Skin Cover for TNV-8011C
Accessory	SBC-160B	Black cover	Black skin cover for indoor X-Plus series domes XND-6081REV / 6081RV / 6081V / 6081VZ / 8081REV / 8081RV / 8081VZ / 9082RV / 8082RV / 6083RV / 8083RV / 8093RV / 9083RV, PND-A9081RV, PND-A6081RV, QTY of 3
Accessory	SBC-180B	Black cover	Black skin cover for outdoor X-Plus series domes XNV-6081 / 6081R / 6081RE / 6081Z / 8081R / 8081RE / 8081Z / 9082R / 8082R / 6083R / 8083R / 8093R / 903R, QTY of 3
Accessory	SBV-160WC	Weather Cap	Weather cap for the following outdoor domes: PNV-9080R, XND-6085 / 6085V / 6080 / 6080R / 6085 / 6120 / 6120R / 8080R / L6080 / L6080R
Accessory	SBV-120WCW	Weather Cap	Weather cap for the following outdoor domes: QNV- 6012R / 6022R / 6032R / 8010R / 8020R / 8030R / 7012R / 7022R / 7032R, ANV-L6012R / L7012R, LNV- 6010R / 6012R / 6020R / 6022R / 6030R / 6032R, white color.
Accessory	SBV-161WCW	Weather Cap	Weather cap compatible with: XNV-C6083R/C7083R/C8083R/C9083R
Accessory	SBV-253WCW	Weather Cap	Weather cap compatible with: PNM-9031RV / PNM-9022V
Accessory	SBV-A14B	Back Box	Back box for A-series cameras
Accessory	SBV-125BW	Back Box	Back box for outdoor Flat-Eye (QNE-8011R and QNE-8021R), white color
Accessory	SBV-180BW	Backbox	Backbox compatible with XND-C9083RV/C8083RV/C7083RV/C6083RV, XND-9083RV/8093RV/8083RV/6083RV, XNV-9083R/8093R/8083R/6083R, XND-9082RV/8082RV, XNV-9082R/8082R
Accessory	SBV-180WW	Back Box	Waterproof Backbox for Vandal X-Core and X-Plus cameras; Compatible models: XNV-6080R/L6080R/6085/6120R/8080R; XNV-6081R/8081R/6083R/8083R/8093R/9083R; XNV-C6083R/C7083R/C8083R/C9083R
Accessory	SBV-215WCW	Weather Cap	Weather cap for PNM-C7083RVD/7082RVD and PNM-C12083RVD/12082RVD
Accessory	SBP-215HMW	Cap Adapter	Handling mount for PNM-C7083RVD/7082RVD and PNM-C12083RVD/12082RVD
Accessory	SBV-140TBW	Tilt Mount	Tilt Mount for TNV-C8011RW - 20° tilt
Accessory	SBV-140TMW	Tilt Mount	Tilt Mount, compatible with: QNV-C8083R/C9083R, QNV-C8011R/C8012/C9011R, QND-6011/6021, QND-8011/8021, QND-6012R/6022R/6082R, QND-7012R/7022R/7082R, QNE-8011R/8021R
Accessory	SBV-138TMW	Tilt mount	23° Tilt mount for Varifocal outdoor dome Q and L series cameras; Compatible models: QNV-6072R/6082R, QNV-7082R, QNV-8080R, LNV-6072R
Accessory	SBP-160TM	Tilted Mount Adapter	23° tilt mount for vandal outdoor domes (XNV-6080R/8080R/L6080/L6080R, PNV-9080R/SNV-8081/8080/7084R/6084R/6085R/5084R, SCV-6081R, XNV-6120/R, XNV-6085)
Accessory	SBP-160TMW1	Tilted Mount Adapter	Tilt Mount, compatible with: XNF-9010RV/RVM, XND-9082RV, XND-8082RV, XND-6081RV/6081REV, XND-8081RV/8081REV, PND-A9081RV
Accessory	SBP-300TM1	Tilted Mount Adapter	20° Tilt Angle Wall Mount Adapter (Poly Carbonate), Accessory for 5MP fisheye cameras (XNF-8010R/RV/RVM, PNF-9010R/RV/RVM), Ivory
Accessory	SPB-IND88W	Tinted Dome Cover	Tinted dome for Indoor dome X-Core cameras
Accessory	SPB-VAN88W	Tinted Dome Cover	Tinted dome for Vandal dome X-Core cameras
Accessory	SPB-VAN89W	Tinted Bubble	Tinted dome cover for: XNV-6083RZ / XNV-8083RZ / XNV-9083RZ
Accessory	SHD-1400FPW	Plenum Flush Mount	Plenum rated flush mount Compatible with QNV-C8083R/C9083R
Accessory	SHD-1400FW	Flush Mount	In-ceiling flush mount Compatible with QNV-C8083R/C9083R
Accessory	SHD-1370FPW	Flush mount	In-ceiling Mount Plenum compatible with XNV-6123R, XNV-6083RZ/8083RZ/9083RZ, XNV-6083Z/8083Z, XNV-6083R/8083R/8093R/9083R, XNV-8082R/9082R, PNV-A6081R/A9081R
Accessory	SHD-1200FPW	Plenum Flush Mount	Plenum In-ceiling Mount compatible with: QNV-C8011R/C8012/C9011R
Accessory	SHD-1350FPW	Flush mount	In-ceiling Housing for X-Plus module cameras
Accessory	SPB-VAN85W	Tinted Bubble	Tinted bubble for outdoor X-Plus cameras, compatible with: XNV-8081RE/8081R/8081Z, XNV-6081RE/6081R/6081Z, PNV-A9081R, XNV-9082R/8082R
Accessory	SPB-IND85W	Tinted Bubble	Tinted bubble for indoor X-Plus cameras, compatible with: XND-8081REV/8081RV/8081VZ, XND-6081REV/6081RV/6081VZ, PND-A9081RV, XND-9082RV/8082RV
Accessory	SPB-FCD85W	Tinted Bubble	Tinted bubble for indoor flush mount X-Plus cameras, compatible with: XND-8081RF/8081FZ, XND-6081RF/6081FZ, PND-A9081RF, XNV-9082R/8082R
Accessory	SPB-PTZ73	Tinted Bubble	Tinted replacement Bubble for XNP-6120H
Accessory	SPB-PTZ85W	Tinted Bubble	Smoked dome cover for PTZ Plus cameras: XNP-6400/6400R, XNP-8250/8250R, XNP-9250/9250R (not compatible with wiper models)
Accessory	SPB-VAN71	Tinted Bubble	Tinted replacement bubble for XNV-6120, XNV-6120R
Accessory	SPB-VAN81	Tinted Bubble	Tinted replacement Bubble for XNV-6085
Accessory	SPB-IND11	Tinted Bubble	Tinted bubble (XND-6010/6020/8020R/8030R/8040R)
Accessory	SPB-IND12	Tinted Bubble	Tinted bubble (QND- 6010R/6020R/6030R / 7010R/7020R/7030R, LND-6011R/6021R/6031R, HCD-7010RA/20RA/30RA)
Accessory	SPB-INW72	Tinted Bubble	Smoked dome cover for White QL varifocal indoor domes, (except QND-8080R)
Accessory	SPB-IND81V	Tinted Bubble	Tinted bubble (XND-6080V/XND-6080RV XND-8080RV)
Accessory	SPB-VAN11	Tinted Bubble	Tinted bubble (XNV- 6010/6020/ 8020R/8030R/8040R)
Accessory	SPB-VAN12	Tinted Bubble	Tinted bubble (QNV- 6010R/6020R/6030R/ 7010R/7020R/7030R, LNV-6011R/6021R/6031R)
Accessory	SPB-VAN72	Tinted Bubble	Tinted bubble (HCV-6070R/6080R/7070RA, SCV-6083R)
Accessories	SPB-VAW12	Tinted Bubble	Smoked dome cover for White QL fixed vandal domes (LNV-6012R/6022R/6032R, QNV-6012R/6022R/6032R/8010R/8020R/8030R)
Accessories	SPB-INW12	Tinted Bubble	Smoked dome cover for White QL fixed indoor domes (LND-6012R/6022R/6032R, QND-6012R/6022R/6032R)
Accessories	SPB-INW13	Tinted Bubble	Smoked dome cover for White 5MP Q series fixed lens (QND-8010R/8020R/8030R)
Accessories	SPB-INW73	Tinted Bubble	Smoked dome cover for White QND-8080R
Accessory	SPB-VAN3	Tinted Bubble	Accessory, tinted replacement Bubble for XNV-6080/6080R/L6080/L6080R, XNV-8080R
Accessory	SPB-IND6	Tinted Bubble	Accessory, tinted replacement Bubble for SCD-6083R/HCD-6080R/6070R
Accessory	SPB-PTZ6	Tinted Bubble	Accessory, tinted replacement Bubble for Indoor PTZ: XNP-6320/6321, QNP-6230/6250/6320, HCP-6320A
Accessory	SPG-VAN13W	Dome Cover	Dome cover with conduit hole access - Compatible with TNV-C7013RC

Accessory	SPB-VAW72	Tinted Bubble	Smoked dome cover for: QNV-8080R, QNV-6082R, LNV-6072R
Accessory	SPG-IND12B	Black cover	Black cover for QND-6010R / 6012R / 6020R / 6022R / 6030R / 6032R, QND-7010R / 7012R / 7020R / 7022R / 7030R / 7032R, LND-6010R / 6011R / 6012R / 6020R / 6021R / 6022R / 6030R / 6031R / 6032R, HCD-6010 / 6020R / 7010R / 7010RA / 7020R / 7020RA / 7030R / 7030RA, SCD-6013 / 6023R / 6025R
Accessory	SPG-IND72B	Black cover	Black cover for LND-6070R / 6071R / 6072R, QND-6070R / 6071R / 6072R, QND-7080R / 7081R / 7082R
Accessory	SPG-IND16B	Black Cover	Black cover for Q-mini cameras QND-6011, QND-6021, QND-8011, QND-8021
Accessory	SHD-315F	Flush mount	2X2 drop ceiling tile flush mount adaptor for the PNM-9084RQZ and PNM-9085ROZ
Accessory	SHD-1198FW	Flush mount	In-ceiling flush mount accessory for indoor dome: QND-8080R, QND-7080R, QND-6070R, HCD-7070RA, HCD-7070R, HCD-6080R, HCD-6070R, HCD-6020R, HCD-6010 (White color)
Accessory	SHF-1500F	Flush Mount	In-ceiling flush mount accessory for XNF-8010R/RV/RVM, PNF-9010R/RV/RVM
Accessory	SHD-400F	Flush mount	In-ceiling flush mount accessory for XNV-6011, Aluminum Body, Ivory
Accessory	SHD-3000F1	Flush mount	In-ceiling flush mount accessory for PNV-9080R, XNV-6080R, XNV-8080R, XNV-L6080/L6080R
Accessory	SHD-3000F2	Flush mount	In-ceiling flush mount accessory for Indoor dome: HCD-6070R/6080R/7070RA, QND-7080R, SCD-6083R
Accessory	SHD-3000F3	Flush mount	In-ceiling flush mount accessory for vandal dome SCV-6083R/6023R, QNV-7080R QNV-6070R, HCV-6070R/6080R, XNP-6040H
Accessory	SHD-3000FW2	Flush mount	In-ceiling flush mount accessory for Indoor dome (QND-6082R, LND-6072R), white color
Accessory	SHD-3000F4	Flush mount	In-ceiling flush mount accessory for PND-9080R, XND-6080RV, XND-6080V & XND-8080RV, XND-L6080/L6080R
Accessory	SHD-3000F5	Flush mount	In-ceiling flush mount accessory for PNM-9000VQ, plenum rated (UL2820)
Accessory	SHP-1680F	Flush mount	In-ceiling flush mount accessory for XNP-6120H, XND-6085V, XNV-6085
Accessory	SHD-B-3100FP1	Flush mount	Plenum rated In-ceiling flush mount accessory for PNV-9080R, XNV-6080R, XNV-8080R
Accessory	SHD-1408FW	Flush mount	In-ceiling flush mount accessory for: HCV-6070R/6080R/7070RA, PND-9080R, QND-6082R/7080R/8080R, XND-6080RV/6080V/8080RV/L6080RV/L6080V (White color)
Accessory	SHD-1408FPW	Plenum flush mount	Plenum rated flush mount, white color. Compatible with HCD-6080R/7070RA, QND-6082R/8080R, XNV-6010/6020R/8020R/8030R/8040R, HCV-7010RA/7020RA/7030RA/6080R/6070R, LNV-6012R/6022R/6032R/6072R, QNV-6012R/6022R/6032R/6082R/8010R/8020R/8030R/8080R, XND-6080V/6080RV/8080RV, XND-L6080V/6080RV, XNP-6040H
Accessory	SHD-1128FPW	Plenum flush mount	Plenum rated flush mount, white color. Compatible with: QNF-8010/9010, HCD-6010/6020R/7010RA/7020RA/7030RA, QND-6011/6021/8011/8021/6012R/6022R/6032R/7010R/7020R/7030R/8010R/8020R/8030R, LND-6012R/6022R/6032R, XND-6010/6020R/8020R/8030R/8040R, XNV-6011/6011W
Accessory	SHP-1520FW	Flush mount	White color PTZ flush mount. Compatible with QNP-6320/6250
Accessory	PTZ-1563FW	Flush mount	PTZ-Plus flush mount, white color. Compatible with XNP-9250/9250R/8250/8250R/6400/6400R, QNP-6320R/6250R, XNP-C6403/C8253/C9253, XNP-C6403R/C8253R/C9253R
Accessory	SHP-1563FPW	Plenum flush mount	Plenum rated PTZ-Plus flush mount, white color. Compatible with XNP-9250/9250R/8250/8250R/6400/6400R, QNP-6320R/6250R, XNP-C6403/C8253/C9253, XNP-C6403R/C8253R/C9253R
Accessory	SHP-1680FPW	Plenum flush mount	White color PTZ flush mount. Compatible with HCP-6320/6320A, QNP-6230/6250/6320, XNP-6320/6321/6120H
Accessory	SHP-1680FW	Flush mount	In-ceiling flush mount accessory for XNP-6120H, XND-6085V, XNV-6085, XNV-6120, XNV-6120R (White color)
Accessory	SBU-500WM	Wall Mount	Wall mount for the TNU-6321
Accessory	SBP-137WM1	Wall Mount	Outdoor wall mount for outdoor domes (QNV-7010R/7020R/7030R, XNV-6010/6020R/8020R/8030R/8040R, HCV-6080R/6070R/7010RA/7020RA/7030RA/7070RA, SCV-6023R/6083R, XNP-6040H)
Accessory	SBP-137WMW1	Wall Mount	Outdoor wall mount for outdoor domes (QNV-6012R/6022R/6032R/8010R/8020R/8030R, 8080R/6082R), white color
Accessory	SBP-125WMW1	Wall/Pole Mount	Wall/Pole mount for: QNV-C8011R/C8012/C9011R, QND-6011/6021/8011/8021, QND-6012R/6022R, QND-6082R, QNE-8011R/8021R, LND-6012R/6022R/6072R, QND-7012R/7022R/7082R (Stainless steel straps are NOT included, compatible with SBP-150S and SBP-060S)
Accessory	SBP-120WM	Wall Mount	Indoor Wall mount for indoor domes (QND-7080R/7030R/7020R/7010R/6070R/6030R/6020R/6010R, XND-6010/6020/8020R/8030R/8040R, SCD-6083R/6023R)
Accessory	SBP-140WMW	Wall mount	Wall/Pole mount. Compatible with: QNV-C8083R/QNV-C9083R (Stainless steel straps are NOT included, compatible with SBP-150S and SBP-060S)
Accessory	SBP-120HWW	Cap Adapter	Cap Adapter for QNV-C9011R/C8011R/C8012
Accessory	SBP-120WMW	Wall Mount	Indoor wall mount for indoor domes (QND-8080R/8030R/8020R/8010R/6082R/6032R/6022R/6012R), white color
Accessory	SBP-160WMW1	Wall mount	Wall mount Compatible models: XND-C6083RV/C7083RV/C8083RV/C9083RV, XND-6083RV/8083RV/9083RV, XNV-C6083R/C7083R/C8083R/C9083R, XND-8082RV/9082RV, XNF-9010RV/9013RV, XND-A6081RV/A9081RV
Accessory	SBP-300CMW1	Ceiling Mount	Ceiling mount with conduit holes compatible with Hanging Adaptor SBP-120HWW/140HWW/160HWW/180HWW1
Accessory	SBP-300MMW	Wall Mount	White Gooseneck mount
Accessory	SBP-390MMW2	Wall Mount	Wall Mount Accessory, 2x knock out built-in, compatible with all full size outdoor PTZs and all caps, White color
Accessory	SBP-300MM1	Wall Mount	Wall Mount Accessory, All caps except SBP-329HM and all outdoor PTZs Ivory
Accessory	SBP-300MMW1	Wall Mount (White)	Wall Mount Accessory (white), Compatible with white hanging caps
Accessory	SBP-300WMS1	Stainless Steel Wall Mount	Stainless Steel wall mount for stainless steel cameras PTZ: XNP-6320HS, QNP-6320HS and dome cameras: XNV-6080RSA, XNV-8080RSA, (need to purchase a separate cap SBP-300HMS6 for the dome cameras)
Accessory	SBP-390WM1	Wall Mount	Wall Mount Accessory, 2x knock out built-in, compatible with all full size outdoor PTZs and all caps, Ivory color
Accessory	SBP-390WM2	Wall Mount	Wall Mount Accessory, 2x knock out built-in, compatible with all full size outdoor PTZs and all caps, Ivory color as well as SBP-300PM pole mount adaptor and SBP-300KM corner mount adaptor
Accessory	SBP-300WM	Wall Mount	Wall Mount Accessory, All caps and all outdoor PTZs Ivory
Accessory	SBP-300WMS	Stainless Steel Wall Mount (Gooseneck)	Stainless Steel wall mount (gooseneck) for stainless steel cameras PTZ: XNP-6320HS, QNP-6320HS and dome cameras: XNV-6080RSA, XNV-8080RSA, PNM-9002VQS (need to purchase a separate cap SBP-300HMS6 for the dome cameras)
Accessory	SBP-300HMS6	Stainless Steel Cap Adaptor	Stainless steel cap adaptor for XNV-6080RSA, XNV-8080RSA
Accessory	SBP-302PM	Pole Mount Base	Pole Mount Adapter Accessory, use with SBO-100B1, PNO-9080R, SNO-8081R SBO-100B1
Installation solution	SBP-300PMW2	Pole Mount Base	Pole Mount Adapter Accessory, use with SBP-300WMW1, White color, made of aluminum
Accessory	SBD-140PMB	Pole Mount	Pole Mount compatible with QNV-C8011R/C8012/C9011R, QNV-C8083R/C9083R, QND-6011/6021, QND-8011/8021, QNF-8010/9010, QND-6012R(1)/6022R(1)/6072R(1)/6082R(1), QND-7012R/7022R/7082R, QNE-8011R/8021R, LND-6012R/6022R/6072R, ANE-L6012R/L7012R
Accessory	SBD-140PMW	Pole Mount	Pole mount base. Compatible with: QNV-C8083R/C9083R, QNV-C8011R/C8012/C9011R, QND-6012R(1)/6022R(1)/6082R(1), QND-7012R/7022R/7082R, QNE-8011R/8021R, LND-6012R/6022R/6072R, ANE-L6012R/L7012R
Accessory	SBD-180PMW	Pole Mount	Pole mount base. Compatible with: PNV-A6081R/A9081R, XNV-8082R/9082R, XNV-6083R/8083R/8093R/9083R, XNV-6123R, XNV-6083Z/8083Z, XNV-6083RZ/8083RZ/9083RZ, PND-A6081RV/A9081RV, XND-8082RV/9082RV, XNF-9010RV/9013RV, XND-6083RV/8083RV/8093RV/9083RV, XNO-6083R/6123R/8083R/9083R, XND-C6083RV/C7083RV/C8083RV/C9083RV, XNO-C6083R/C8083R/C9083R, XNV-C6083R/C7083R/C8083R/C9083R
Installation solution	SBP-300PMW1	Pole Mount Base	Pole Mount Adapter Accessory, use with SBP-300WMW1, White color, made of aluminum
Accessory	SBP-300PMW1	Installation plate	Installation plate for SBP-300PMW1, compatible with Box Camera Housing: SHB-4301HP/SHB-4300H1/SHB-4200/SHB-4200H
Accessory	SBP-300PM1	Pole Mount Base	Pole Mount Adapter Accessory, use with SBP-300WM, SBP-300WM1, SBP-390WMW2, Ivory caps are not included
Accessory	SBP-300PMS	Stainless Steel Pole Mount Adaptor	Pole mount adaptor for the SBP-300WMS and SBP-300WMS1
Accessory	SBP-303PM	Pole Mount Base	Pole mount adapter accessory for thermal bullet cameras, compatible with TNO-4040T, TNO-4030T, TNO-4050T, TNO-4030TR, TNO-4040TR, TNO-3010T/3020T/3030T
Accessory	SBP-300KM1	Corner Mount Base	Corner Mount Adapter Accessory, Ivory color
Accessory	SBP-300KMW1	Corner Mount Base	Corner Mount Adapter Accessory, use with SBP-300WMW1, White color, made of aluminum
Accessory	SBP-300KMS	Stainless Steel Corner Mount Adaptor	Corner mount adaptor for the SBP-300WMS and SBP-300WMS1
Accessory	SBP-300LM	Parapet Mount	Parapet Mount Accessory, compatible with all full size outdoor PTZs and all caps, Ivory color
Accessory	SBP-300LMW	Parapet Mount	Parapet Mount Accessory, compatible with all full size outdoor PTZs and all caps, White
Accessory	SBP-302CM	Pendant Mount	Telescopic ceiling mount Accessory, require a mounting plate SBP-302CMA
Accessory	SBP-300CMTW	Telescopic Ceiling Mount	Telescopic Ceiling Mount with female 1.5" pipe thread and 3/4" conduit access holes, Product dimension: ø180x956.5-1667.5mm (ø7.09x37.66-65.65")
Accessory	SBP-900CMW	Ceiling Mount	Pendant Mount Accessory, Length: 900mm (35.43") with female 1.5" pipe thread and 3/4" conduit access holes
Accessory	SBP-300CMW	Pendant Mount (White)	Pendant Mount Accessory, white
Accessory	SBP-302CMA	Mounting plate	Mounting plate for the telescopic pendant mount SBP-302CM
Accessory	SBP-300CM	Pendant Mount	Pendant Mount Accessory, Ivory
Accessory	SBP-302CM-36	Extension pendant pipe 36"	Extension pendant pipe 36" long, fit the SBP-302CMB (Mounting backbox), SBP-302CMA (mounting plate), SBP-302CM (telescopic pendant mount) and the extension pipes SBP-302CM-12 and SBP-302CM-36
Accessory	SBP-302CM-12	Extension pendant pipe 12"	Extension pendant pipe 12" long, fit the SBP-302CMB (Mounting backbox), SBP-302CMA (mounting plate), SBP-302CM (telescopic pendant mount) and the extension pipes SBP-302CM-12 and SBP-302CM-36
Accessory	SBP-302CMB	Pendant back box	Back box made to fit SBP-302CM telescopic pendant mount and the extension pipes (SBP-302CM-12 and SBP-302CM-36)
Accessory	SBP-302CMAS	Swivel Joint + Telescopic pendant mount	Telescopic pendant mount accessory with 90 degrees swivel joint, 4.5' to 8' adjustable, includes SBP-302CMA for ceiling mount, Ivory color
Accessory	SBP-302CMS	Swivel adapter for pendant mount	Swivel adapter for pendant mount for SBP-302CM, SBP-302CM-12, SBP-302CM-36 and it also requires one mounting option either SBP-302CMA or SBP-302CMB
Accessory	SBP-150S	Stainless steel mount strap	Stainless steel mount strap (QTY of 2) for a wall/pole mount: Length: 1,500mm (59.1"), Width : 12.6mm (0.5")
Accessory	SBP-060S	Stainless steel mount strap	Stainless steel mount strap (QTY of 2) for a wall/pole mount: Length: 600mm (23.6"), Width : 12.6mm (0.5")
Accessory	SBP-156WMW	Wall/Pole mount	Wall/Pole mount, Material : Aluminum, Color : White, Dimensions :135(W)x183(H)x302(D)mm (5.31x7.20x11.89"), Compatible with: XNP-9300RW/8300RW/6400RW, QNP-6320R/6250R/6320H/6250H, Stainless Steel Pole straps are not included.
Accessory	SBP-156HWW	Hanging mount	Hanging mount, Material : Aluminum, Color : White, Dimensions : Ø95.5x77.0 mm(Ø3.76x3.03"), Compatible with: XNP-9300RW/8300RW/6400RW, QNP-6320R/6250R/6320H/6250H
Accessory	SBP-156CMW	Ceiling mount	Ceiling mount, Weight: 4.2 kg (9.3 lb), Material: Aluminum, Color: White, Compatible with: XNP-9300RW/8300RW/6400RW, QNP-6320R/6250R/6320H/6250H
Accessory	SBP-156LMW1	Telescopic Parapet Mount	Telescopic Parapet Mount, White color parapet mount, Weight : 7.1 kg (15.7 lb), Product dimensions: 835-1098x1000x95mm(32.9-43.2x39.4x3.8"), (doesn't include SBP-156HWW)

Accessory	SBP-156LMW	Telescopic Parapet Mount	Telescopic Parapet Mount, White color parapet mount , Weight : 7.1 kg (15.7 lb), Product dimensions: 853-1116x1000x95mm(33.6-43.9x39.4x3.8"), Compatible with: XNP-9300RW/8300RW/6400RW, QNP-6320R/6250R/6320H/6250H, Package includes SBP-156HMW
Accessory	SBD-140KMB	Corner Mount	Light weight stainless steel corner mount compatible with: QNV-C8011R/C8012/C9011R, QNV-C8083R/C9083R, QND-6011/6021, QND-8011/8021, QNF-8010/9010, QND-6012R(1)/6022R(1)/6072R(1)/6082R(1), QND-7012R/7022R/7082R, QNE-8011R/8021R, LND-6012R/6022R/6072R, ANE-L6012R/L7012R
Accessory	SBP-156KMW	Corner mount	Corner mount, Material: Aluminum, Color: White, Dimensions : 276.8(W)x183.0(H)x158.5(D)mm (10.90x7.20x6.24"), Compatible with: XNP-9300RW/8300RW/6400RW, QNP-6320R/6250R/6320H/6250H
Accessory	SBP-099TMW	Tilt mount	Tilt mount for Q fisheye cameras. Compatible with QNF-9010, QNF-8010
Accessory	SBP-125HMW	Small Hanging Cap	Hanging Mount for QNE-8011R/8021R
Accessory	SHD-2500FPW	Plenum Flush Mount	Plenum In-ceiling Mount compatible with: PNM-C16083RVQ/C32083RVQ
Accessory	SHD-2510FPW	Plenum flush mount	Plenum Flush Mount for PNM-9084OZ/8082VT
Accessory	SHD-1600FW	In-ceiling Mount	In-ceiling mount compatible with XND-C6083RV, XND-C7083RV, XND-C8083RV, XND-C9083RV
Accessory	SHD-2000FPW	Flush mount	Plenum rated in-ceiling mount compatible with PNM-C16013RVQ
Accessory	SHD-1600FPW	Plenum flush mount	Plenum Flush Mount for XNF-8010R/8010RV/9010RV/9010RV, XND-6085V, XNV-6080/6080R/8080R/L6080/L6080R/6120/6120R/6085
Accessory	SBL-100D	Remote lens dome bracket	Dome bracket for SLA-T2480A, SLA-T4680A, SLA-T2480, SLA-T4680
Accessory	SBL-101C	Corner bracket for remote head lens	Corner bracket for SLA-T2480A, SLA-T4680A, SLA-T2480, SLA-T4680
Accessory	SCL-30	Extension cable for remote head lens	Extension cable for remote head lens, 3m (9.84Ft), compatible with: PNM-9000QB, XNB-6002, SLA-T4680A, SLA-T4680VA, SLA-T2480A, SLA-T2480VA, SLA-T1080FA, SLA-T2880BA, SLA-T4680DA, SLA-T4680DSA
Accessory	SCL-150	Extension cable for remote head lens	Extension cable for remote head lens, 15m (49.2Ft), compatible with: PNM-9000QB and XNB-6002, SLA-T4680A, SLA-T4680VA, SLA-T2480A, SLA-T2480VA, SLA-T1080FA, SLA-T2880BA, SLA-T4680DA, SLA-T4680DSA
Accessory	STB-1520VW	swivel adapter	Box camera swivel adapter, converting 1.5"NPT to 1/2-20 UNC, Compatible with TMN-3620TDY (body temperature detection camera), SPI-35B (Blackbody), All other box cameras: white color
Accessory	STB-5075W	Floor Stand	Floor stand with adjustable height; compatible with all box cameras, temperature detecting camera [TMN-3620TDY], blackbody [SPI-35B], and all other box cameras, extend between 50 inch to 75 inch: white color
Accessory	STB-4150V	Box Camera Mount	Wall/Ceiling Mount Accessory for Box cameras
Accessory	SBP-300B	Mount Base	Wall Mount Base, Works with Mounts (SBP-300WM/300WM1), Ivory
Accessory	SBP-300BW	Mount Base	Wall Mount Base, Works with Mounts SBP-300WMW1, white
Accessory	SBV-120GW	Back Box	Back Box with knockouts, Compatible with QNV-6012R/6022R/6032R, QNV-8010R/8020R/8030R
Accessory	SBO-090GP	Wall Adapter Plate	Gang plate (for bullet) Adaptor plate for Single, Double, 4" Octagon Compatible with QNO-C8083R / QNO-C9083R / ANO-L6012R / ANO-L6022R / ANO-L6082R / ANO-L7012R / ANO-L7022R / ANO-L7082R
Accessory	SBO-140WW	Back Box for Bullet Cameras	Waterproof Back box for bullet cameras. Compatible with: QNO-C8083R/C9083R, ANO-L6012R/22R/82R, ANO-L7012R/22R/82R
Accessory	SBO-140BW	Back Box for Bullet Cameras	Back box for bullet cameras. Compatible with: QNO-C8083R/C9083R, ANO-L6012R/22R/82R, ANO-L7012R/22R/82R
Accessory	SBO-100B1	Bullet Back Box	IR Bullet camera Back box. (QNO-7030R/7020R/7010R, QNO-7080R, SCO-6083R, HCO-6080R/6070R/7010RA/7020RA/7030RA/7070RA, QNO-8010R/8020R/8030R, QNO-6012R/6022R/6032R/6082R)
Accessory	SBO-126B	Bullet Back Box	IR bullet camera back box. (XNO-L6080R, QNO-8080R)
Accessory	SBP-060BA	Conduit Adapter	Conduit Adapter compatible with PNM-C16013RV, QNV-C8083R/C9083R, XNO-C6083R/C7083R/C8083R/C9083R
Accessory	SBO-147BA	Conduit Hole Adaptor	Conduit Hole Adaptor for X-Core bullet cameras
Accessory	SBO-147B	Bullet Back Box	Water-Proof Back Box for QNO-6082R
Accessory	SBV-140WW	Back Box for Dome Cameras	Waterproof Back box for dome cameras. Compatible with: QNV-C8083R/C9083R, QNV-C8011R/C8012/C9011R, QND-6011/6021, QND-8011/8021, QND-6012R/6022R/6082R, QND-7012R/7022R/7082R, QNE-8011R/8021R
Accessory	SBV-140BW	Back Box for Dome Cameras	Back box for dome cameras. Compatible with: QNV-C8083R/C9083R, QNV-C8011R/C8012/C9011R, QND-6011/6021, QND-8011/8021, QND-6012R/6022R/6082R, QND-7012R/7022R/7082R, QNE-8011R/8021R
Accessory	SBV-160BW	Dome Back Box	White Back Box, Compatible with: XNF-9010RV/RVM, and all indoor X-Plus cameras (XND)
Accessory	SBV-158G	Dome Back box	Vandal dome camera Back box. (PNV-9080R, XNV-6080R, XNV-8080R, XNV-6120R, XNV-6085, PNM-7000VD)
Accessory	SBV-136B	Dome Back Box	Back Box with knockouts and water proof design, Compatible with SCV-6083R/6023R, QNV-7080R, HCV-6070R/6080R, XNP-6040H
Accessory	SBV-136BW	Dome Back Box	Back box with knockouts (QNV-8080R, QNV-6082R), white color
Accessory	SBF-100B1	Fisheye Back Box	Fisheye camera Back box. (XNF-8010R/RV/RVM, PNF-9010R/RV/RVM)
Accessory	SBV-116B	Dome back box	Back box with knockouts, compatible with XNV-6011
Accessory	SBP-300NB	Installation Box	Installation Back box compatible with (SBP-300WM, SBP-300WM1, SBP-300KM, SBP-300PM)
Accessory	SBP-300NBW	Installation Box	Installation Back box compatible with (SBP-300WMW, SBP-300WMW1, SBP-300KMW, SBP-300PMW)
Accessory	SBP-300NM	Mounting accessory for the TNB-6030	PVM camera (TNB-6030) mounting hardware
Accessory	SBP-2CTW1	2'x2' ceiling tile, 1.5" NPT female thread	2'x2' drop ceiling tile (or half of 2'x4' ceiling tile) accessory with 1.5" NPT female thread, includes suspension wire, four turnbuckles, and anchors to suspend from wood or concrete structures, supports up to 50lb, scratch resistant fused epoxy white finish
Accessories	SBP-HCFW	1.5" coupler (White)	1.5" coupler, female thread on both sides, White
Accessory	SBP-HCF	1.5" coupler	1.5" coupler, female thread on both sides, Ivory
Accessory	SBP-35PVMB	PVM Mount	Telescopic PVM uni-strut mount, 3'-5.5' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, black
Accessory	SBP-35PVMW	PVM Mount	Telescopic PVM uni-strut mount, 3'-5.5' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, white
Accessory	SBP-59PVMB	PVM Mount	Telescopic PVM uni-strut mount, 5'-9' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, black
Accessory	SBP-59PVMW	PVM Mount	Telescopic PVM uni-strut mount, 5'-9' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, white
PVM Accessory	SBP-917PVMB1	Telescopic PVM uni-strut mount	Telescopic PVM uni-strut mount, 9.5-17' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, black color. Three piece attachment for standard shipping
Accessory	SBP-917PVMW1	PVM Mount	Telescopic PVM uni-strut mount, 9.5-17' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, white
Accessory	STB-10PVMSC-B	PVM Mount	Self-checkout monitor mount, accommodates one SMT-1030PV 10" PVM, easy height adjustment, angle optimized for best view, all installation hardware and brackets included, Powder coated black color, VESA 75 x 75 mm, product weight 3lbs
Accessories	STB-10PVMCWA-W	PVM Mount	Horizontal gondola monitor mount, accommodates one SMT-1030PV 10" PVM, easy height adjustment, angle optimized for best view, all installation hardware and brackets included, Powder coated white color, VESA 75 x 75 mm, product weight 3lbs
Accessories	STB-10PVMGUX-W	PVM Mount	Gondola upright monitor mount, accommodates one SMT-1030PV 10" PVM, easy height adjustment, angle optimized for best view, all installation hardware and brackets included, Powder coated white color, VESA 75 x 75 mm, product weight 3lbs
Accessory	SPI-35B	Black Body device	Body Temperature Reference (black body), 3", EC 80601-2-59 standard, 30°C to 45°C (86°F to 113°F), Accuracy of ±0.15°C (±0.3°F), 1/4-20" Tripod Mounting, 5% to 95% non-condensing (RH), 18V, 1A, DC max. (Accessory for TMN-3620TDY)
Accessory	SPI-50	IR Illuminators for the TNU-6320	IR emitter up to 200m (656 feet), 25° IR angle, 850nm wave length, 24VAC, IP67, -40°C ~ +60°C (-40°F ~ 140°F). Compatible with the TNU-6321
Accessory	SHD-46VDB	Flush door Jamb Lens Housing (black)	Flush Door Jamb Lens Housing for SLA-T4680V lens (not included) and XNB-6001 (not included), black color
Accessory	SHD-46VDE	Flush door Jamb Lens Housing (silver)	Flush Door Jamb Lens Housing for SLA-T4680V lens (not included) and XNB-6001 (not included), silver color
Housing	SHP-3701H	PTZ Outdoor Housing	PTZ Housing Accessory, IP66, IK10, Built-in Heater -58°F XNP-6320/6321, QNP-6230/6250/6320
Accessory	WWT-P-VESA	WAVE Recording Server Mount	VESA mount + adapter box for WWT-P and WRT-P Micro form factor
Accessory	WRR-P-HDDCRDL	WAVE recording server HDD Cradle	HDD cradle for WRR-P and WRR-Q servers (1U and 2U chassis)
Accessory	SBP-302F	Ceiling Tile Support Plate	Ceiling tile support plate for the XND-6081FZ/8081FZ, XND-6081RF/8081RF, XND-9082RF/8082RF and SHD-3000F5
Accessory	SPP-C7400	Audio and Alarm cable	Audio and Alarm cable for TNV-C7013RC, QNV-C8083R/9083R, XNV-C6083R/C7083R/C8083R/C9083R, XND-C6083RV/C7083RV/C8083RV/C9083RV. (Pack of 3)
Accessory	SHB-9000H	Box Camera (TNB-9000) Housing	TNB-9000 Box Camera Housing, Body/Sun shield : Aluminum, Front & Rear cap : ABS, Wall Mount Arm Included. Operating Temperature: -50°C ~ +60°C (-58°F ~ +140°F) / 10-100% RH (condensing), Weight: 6.2kg(13.67 lb), Color: White, IP66. Input Voltage 110vac, Thermostat controlled Fan and heater - UL 62368-1 Certified
Housing	SHB-4301HP	Fixed Housing	Indoor/Outdoor PoE Housing w/Mounting Bracket Accessory, Heater/Blower, IP66
Housing	SHB-4300H1	Fixed Housing	Indoor/Outdoor Housing w/Mounting Bracket Accessory, Heater/Blower -58°F-122°F, 24VAC, IP66
Housing	SHB-4200	Fixed Housing	Indoor/Outdoor Housing w/Mounting Bracket Accessory, 14°F-122°F, IP66
Housing	SHB-4200H	Fixed Housing	Indoor/Outdoor Housing w/Mounting Bracket Accessory, Heater/Blower, -31°F-122°F, 24VAC, IP66
Accessory	SHB-V-3200HPR	Outdoor enclosure	Outdoor enclosure with PoE+, IR and Wall mount for Box cameras. Compatible with most XNB and PNB Cameras. See complete camera compatibility list in the mount selection tool.
Accessory	SHB-V-WCPA	Conduit adapter plate	Conduit adapter plate for outdoor enclosure: SHB-V-3200HPR Enclosure
Accessory	SHB-V-DBHWGC	Pole Mount Adaptor	Pole mount adapter, (Ø 8.2", max 8.9") for outdoor enclosure: SHB-V-3200HPR. Note: The SHB-V-WCPA is also needed for pole mount installation.
Accessory	SBP-302CMW	Pendant Mount (white)	Telescopic pendant mount Accessory, requires a mounting plate SBP-302CMAW or SBP-302CMBW (white color)
Accessory	SBP-302CMAW	Mounting plate (white)	Mounting plate for the telescopic pendant mount SBP-302CMW (white color)
Accessory	SBP-302CM-06W	Extension pendant pipe 6" (white)	Extension pendant pipe 6" long, fit the SBP-302CMBW (Mounting backbox), SBP-302CMAW (mounting plate), SBP-302CMW (telescopic pendant mount) and the extension pipes SBP-302CMW-06 SBP-302CMW-12 and SBP-302CMW-36; white color
Accessory	SBP-302CM-12W	Extension pendant pipe 12" (white)	Extension pendant pipe 12" long, fit the SBP-302CMBW (Mounting backbox), SBP-302CMAW (mounting plate), SBP-302CMW (telescopic pendant mount) and the extension pipes SBP-302CMW-06 SBP-302CMW-12 and SBP-302CMW-36; white color
Accessory	SBP-302CM-36W	Extension pendant pipe 36" (white)	Extension pendant pipe 36" long, fit the SBP-302CMBW (Mounting backbox), SBP-302CMAW (mounting plate), SBP-302CMW (telescopic pendant mount) and the extension pipes SBP-302CMW-06 SBP-302CMW-12 and SBP-302CMW-36; white color
Accessory	SBP-302CMBW	Pendant back box (white)	Back box made to fit SBP-302CMW telescopic pendant mount and the extension pipes (SBP-302-CMW-06, SBP-302CMW-12 and SBP-302CMW-36). White color
Accessory	SBP-302CMSW	Swivel adapter for pendant mount (white)	Swivel adapter for pendant mount for SBP-302CMW, SBP-302CMW-06, SBP-302CMW-12, SBP-302CMW-36 and it also requires one mounting option either SBP-302CMAW or SBP-302CMBW; White color
Accessory	SBP-302CMASW	Swivel Joint + Telescopic pendant mount (white)	Telescopic pendant mount accessory with 90 degrees swivel joint, 4.5' to 8' adjustable, includes SBP-302CMAW for ceiling mount, White color

Monitor			
Monitor	SMT-3215	32" FHD Monitor	32" LED Monitor, Full HD 1920 x 1080, HDMI, DP, VGA, 16:9 aspect ratio, Built-in Speaker (2W X 2), VESA DPM Compatible (100x100mm) Actual screen size 15.5"
Monitors	SMT-3240	32" UHD Monitor	32" LED Monitor, UHD (3840*2160 60Hz), HDMI, DP, 16:9 aspect ratio, Built-in Speaker (2W X 2), VESA DPM Compatible (100x100mm)
Monitors	SMT-4343	43" UHD Monitor	43" UHD LED Monitor, 2160p (4K), HDMI, DP, 16:9 aspect ratio, Built-in Speaker (10W X 2), VESA DPM Compatible (100x100mm/400x200mm)
Monitor Set	SMT-4343S	43" UHD Monitor Set (Monitor+Desktop Stand)	43" LED Monitor, 2160p (4K), HDMI, DP, 16:9 aspect ratio, Built-in Speaker (2W X 2), VESA DPM Compatible (100x100mm/400x200mm) + Single monitor desktop stand, compatible with SMT-4343 monitor, black color, 100x100 VESA mountable
PVM	SMT-3231PV	32" AI Public View Monitor	SMT-3231PV -> 32" (31.55") AI Enabled IP public view monitor (AI PVM) PIP & PBP support, 1080p (1920 x 1080 60Hz), HDMI, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, AI face & Object detection. Display for visual deterrent, customizable text overlay with pre-configured "recording in progress" OSD 2MP IP camera built-in, 3.06mm fixed lens, (107.7" H and 59.0V), 120dB WDR, H.265/H.264/MJPEG, slide show & live video, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode, portrait and landscape display support, HPoE 802.3bt, DC 24V. ***Power adapter not included***
Monitor	SMT-3211PVM-PIP	32" PVM with PIP	32" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, PIP, customizable text overlay with pre-configured "recording in progress" OSD, 2MP IP camera built-in, 4.6mm fixed lens(73.8"H), 150dB WDR, H.265/H.264/MJPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode Power supply NOT included
Monitor	SMT-3211PVM	32" Without PIP	32" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, customizable text overlay with pre-configured "recording in progress" OSD, 2MP IP camera built-in, 4.6mm fixed lens(73.8"H), 150dB WDR, H.265/H.264/MJPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode Power supply NOT included
PVM	SMT-2731PV	27" AI Public View Monitor	27" AI Enabled IP public view monitor (AI PVM) PIP & PBP support, 1080p (1920 x 1080 60Hz), HDMI, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, AI face & Object detection display for visual deterrent, customizable text overlay with pre-configured "recording in progress" OSD 2MP IP camera built-in, 3.06mm fixed lens, (107.7" H and 59.0V), 120dB WDR, H.265/H.264/MJPEG, slide show & live video, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode, portrait and landscape display support, HPoE 802.3bt, DC 24V. ***Power adapter not included***
Monitors	SMT-2431	24" LED Monitor	24" LED Monitor, Full HD, 1080p (1920x1080), HDMI, VGA, 16:9 aspect ratio, VESA DPM Compatible (100x100mm)
Monitors	SMT-2212	22" LED Monitor	22" LED Monitor, Full HD, 1080p (1920x1080), HDMI, VGA, 16:9 aspect ratio, VESA DPM Compatible (100x100mm)
Monitor	SMT-1030PV	10" PVM monitor (Black)	10" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (75 x 75mm), black casing, face detection display for visual deterrent, 2MP IP camera built-in, 4.6mm fixed lens(73.8"H), 150dB WDR, H.265/H.264/MJPEG, slide show & live video, power supply included (12VDC) or PoE+ powered
Monitor Stand	SBM-3232	32" desktop stand	Single monitor desktop stand, compatible with SMT-3233 monitor, black color, 100x100 VESA mountable
Monitor Stand	SBM-4343	43" Desktop Stand	Single monitor desktop stand, compatible with SMT-4343 monitor, black color, 100x100 VESA mountable

Controllers			
Analog - Controller	SPC-2010	Controller	Controller, 3D joystick, 2 line text LCD display, built-in jog shuttle, up to 255 PTZ/zoom cameras, RS-485, DVR, supports Multi-protocol
USB - Controller	SPC-2001	Controller	Controller, USB 3D joystick
Analog - Controller	SPC-1010	Controller	Controller, PTZ joystick controller, 2 line text LCD display, up to 255 PTZ/zoom cameras, RS-485

Power Supplies			
Power Supply	SPO-8315	83W HPoE Injector	83W HPoE Injector, Fully compliant with IEEE802.3af/at/bt, PoE++, Built-in SFP slot, Compatible with XNP-9300RW / XNP-8300RW / XNP-6400RW, PNM-9085RQZ / PNM-9085RQZ1 / PNM-9084RQZ / PNM-9084RQZ1 / PNM-9322VQP
Power Supply	SPO-6011	60W PoE++ Injector	60W HPoE Injector, Fully compliant with IEEE802.3af/at/bt, PoE++, Built-in SFP slot, Compatible with XNP-9250R / XNP-8250R / XNP-6400R / TNB-9000
Power Supply	SPU-60240	AI PVM power adapter	Power adapter for AI PVM, 60W, 24V DC (SMT-3231PV, SMT-2731PV, SMT-1031PV, SMT-1031PVW)
Power Supply	PWR-DR12033	DIN Rail Mounting 33W Hardened Power Supply	12VDC 33Watt (2.75A) DIN Rail High Temp Power Supply (-40°C to +71°C With -40°C Start-Up)

EPIC WebRTC Media Server License			
EPIC WebRTC Media Server License	WRTC-EP5-1	EPIC WebRTC Media Server License	5 Years EPIC WebRTC Media Server License for one camera connection including Audio
EPIC WebRTC Media Server License	WRTC-EP3-1	EPIC WebRTC Media Server License	3 Years EPIC WebRTC Media Server License for one camera connection including Audio

Services			
Service	DIN-SSDA006/CO	On-site engineering service	This is an on site engineering service that will be provided by one of Hanwha Vision B2B security division trained personal for our STEP dealers to help configuring or training on product including cameras, recorders and software. This SKU is for one day, if multiple days are needed please reflect that by increasing the QTY of this SKU.
Service	DIN-SSDA003/CO	Professional Firmware Customization	This is a professional firmware customization service that will be provided by Hanwha Vision B2B security R&D Division to provide valuable functions on our network cameras and network recorders. This SKU is for one day engineering cost. For more details please contact us by emailing projectfwservice@hanwha.com
Service	DIN-SSDA008/CO	Remote engineering service	This is a remote engineering service that will be provided by a Hanwha Vision B2B security division trained personnel for our STEP dealers to help configure or train on product including cameras, recorders and software. A reliable phone connection and internet connection (for a connection to the surveillance system via a remote desktop software) is required to be provided by the STEP partner. This SKU is for one day. If multiple days are needed please reflect that by increasing the QTY of the SKU

Disclaimer:

We put our best effort and knowledge to maintain the accuracy of specifications and price. Should there be any discrepancies we reserve the right to follow our specifications and price set. Thanks for your understanding.