




G-Series PoE 8-Port

G-Series PoE 16-Port

G-Series PoE Network Video Recorder

Sophisticated Performance from an Affordable NVR



Remote management

Remotely power cycle cameras



Easy connect

Automatically detect cameras and assign IP addresses for supported models



No external network switch

8 or 16 built in PoE ports




Flexible installation

Rack and wall-mount options



Generous PoE Budget

15W simultaneous on all ports and up to 30W on any port



Pre-loaded software

Ships with 4 free Professional licenses

Specifications

	G-Series PoE 8-Port	G-Series PoE 16-Port
Maximum PoE Cameras	8	16
Included IP Licenses	4 PRO	4 PRO
PoE Power	15 W (all ports simultaneously) 30 W max (individual port) 120 W (total)	15 W (all ports simultaneously) 30 W max (individual port) 240 W (total)
Pre-Loaded VMS Software	Professional Enterprise (Optional)	Professional Enterprise (Optional)
Include SSA	3 Years	3 Years
Operating System	Linux Ubuntu 22.04	Linux Ubuntu 22.04
Maximum Storage	12TB	12TB
Maximum Hard Drives	1	1
Typical Video Storage Rate	120 Mbps	120 Mbps
Local Client Display Rate (1080p)	8 streams @ 30 FPS each	16 streams @ 30 FPS each
CPU	Intel Celeron	Intel Celeron
RAM	4 GB	4 GB
Monitor Output	HDMI, DVI-I 2 Simultaneous	HDMI, DVI-I 2 Simultaneous
NIC	1x 2.5Gbps, 1x 1Gbps	1x 2.5Gbps, 1x 1Gbps
USB	2x USB 2.0 Front, 4x USB 3.1 Rear	2x USB 2.0 Front, 2x USB 3.1 Rear, 2x USB 2.0 Rear
Audio Inputs	1	1
Audio Outputs	1	1
DVD	External (Optional)	External (Optional)
Accessories	Keyboard (on-screen), Mouse	Keyboard (on-screen), Mouse
Dimensions (H x W x D)	14.17in (W) x 1.92 (H) x 8.83in (D) 360mm (W) x 49mm (H) x 224.5mm (D)	16.92in (W) x 1.75 (H) x 13.70in (D) 430mm (W) x 44.5mm (H) x 348mm (D)
Weight	6 lbs 2.72 kg	10 lbs 4.54 kg
Regulatory	UL, CE, FCC	UL, CE, FCC
Input Voltage	54V-DC, 3.2A	120/240 VAC Auto-Sensing
Power Supplies	Auto-Sensing	Single
Power & Heat	260 Watts / 900 BTU/hr (Max) 65 Watts / 225 BTU/hr (Typical + PoE)	480 Watts / 1640 BTU/hr (Max) 120 Watts / 410 BTU/hr (Typical + POE)
Operating Temperature	32° - 104°F 0° - 40°C	32° - 104°F 0° - 40°C
Warranty	3 Years	3 Years