



# kramer

## MC3-2Ho

4K60 HDMI 2xOUT Card

| HDMI | 4K/60 UHD (4:4:4)



MC3-2Ho is a high-performance two-port HDMI output card which is part of the compatible modular matrices multi-signal cards family. MC3-2Ho can flexibly occupy any of the matrix card slots and its output signals are independently switched by the modular matrix to any of the matrix output ports

### FEATURES

**High Resolution Audio-Visual Experience** - Modular matrix output card supports high 4K60 4:4:4 AV signal distribution from any input port of the modular matrix

**HDMI™ Signal Distribution** - HDCP 2.2 compliant, supporting deep color, x.v.Color™, CEC, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified by the HDMI 2.0 standard

**Multi-channel Audio Transmission** - Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound



# kramer

## TECHNICAL SPECIFICATIONS

---

Outputs	2 HDMI: On female HDMI connectors
Video	Max Data Rate: 18Gbps (6Gbps per graphics channel) Max Resolution: 4K@60Hz (4:4:4) HDMI Support: HDR 10, 3D, Deep Color, x.v.Color™, ARC, Dolby® TrueHD, Dolby Digital Plus, DTS–HD®, and 7.1 multi–channel audio
User Interface	Content Protection: HDCP 2.2/1.4 compliant
Extension Line	Range at 4K60 (4:2:0) or 4K30 (4:4:4) Resolution 10m (32ft) Range at 1080p 12 bit (deep color) Resolution 15m (49ft)
Power	Consumption 5W
Regulatory Compliance (Standards Compliance)	Safety CE
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: –40° to +70°C (–40° to 158°F) Humidity: 10% to 90%, RHL non–condensing
Product Dimensions	12.90cm x 24.90cm x 2.00cm (5.08" x 9.80" x 0.79" ) W, D, H
Product Weight	0.2kg (0.5lbs) approx
Shipping Dimensions	16.50cm x 34.50cm x 5.90cm (6.50" x 13.58" x 2.32" ) W, D, H
Shipping Weight	0.4kg (0.9lbs) approx

