

RCI 125 kHz Credentials



PSC-1-H
125kHz Clamshell Card
 Proximity card for physical access control.
 2.2" W x 3.4" H x .06" D
 (56x86x1.5 mm)



PSI-4-H
125kHz Printable Card
 Printable proximity card for physical access control.
 2.1" W x 3.4" H x 0.046" D
 (53x86x1.17 mm)



PSM-2P-H
125kHz ISO Imageable Card
 ISO imageable proximity card for physical access control.
 2.1" W x 3.4" H x 0.031" D
 (53 x 86 x 0.79 mm)



PSM-2S-H
125kHz ISO Imageable Card with magnetic stripe
 ISO imageable proximity card for physical access control.
 2.1" W x 3.4" H x 0.031" D
 (53 x 86 x 0.79 mm)



PSK-3-H
125kHz Fob
 Proximity fob for physical access control.
 1.2" W x 1.5" H x 0.15" D
 (30 x 38 x 3.8 mm)



PDT-1-H
125kHz Disk Tag
 Disk tag credential for physical access control.
 1" diameter x 0.0625" thick
 (25.4 mm x 1.6 mm)



DE2-125
125kHz & 13.56MHz Card
 Dual frequency 125 kHz (proximity) and 13.56 MHz (MIFARE DESFire EV2 smartcard) for physical access control.
 2.1" W x 3.4" H x 0.031" D
 (53 x 86 x 0.79 mm)

See Fact sheet for specifications



Warranty Varying

How To Order

	Credential Type
PSC-1-H	Clamshell
PSI-4-H	Printable
PSM-2P-H	ISO imageable
PSM-2S-H	ISO imageable
PSK-3-H	Fob
PDT-1-H	Adhesive Tag
DE2-125	ISO imageable