


Field-Configurable Patch Panels

KEY FEATURES

- Meets EIA/ECA-310-E 19 in mounting standards
- Compatible with Signamax Keystone Modules to accommodate a multitude of applications
- Angled design eliminates the need for cable management panels saving space
- Wall-Mount are available with an 89D bracket for easier access to termination



Straight Panels

ORDERING INFORMATION

PART NO.	DESCRIPTION
24U-HDMMP	24-Port Field-Configurable Patch Panel, 1U
48U-HDMMP	48-Port Field-Configurable Patch Panel, 2U
72U-HDMMP	72-Port Field-Configurable Patch Panel, 2U
48U-HDMMP-1R	48-Port Field-Configurable Patch Panel, 1U

Wall-Mount Panels

ORDERING INFORMATION

PART NO.	DESCRIPTION
12U-M89	12-Port Wall-Mount Mini Patch Panel w/89D Bracket

Angled Rack-Mount Panels

ORDERING INFORMATION

PART NO.	DESCRIPTION
24U-HDMMP-A	24-Port Angled Field-Configurable Patch Panel, 1U
48U-HDMMP-A	48-Port Angled Field-Configurable Patch Panel, 2U
72U-HDMMP-A	72-Port Angled Field-Configurable Patch Panel, 2U



SPECIFICATIONS

DIMENSIONS

Wall-Mount: 2.38" D x 2.06" W x 10.0" H (60.5 mm x 52.3 mm x 254 mm)

Straight/Angled

Depth:

Straight Panel: CM Bar Installed: 6.0" (153 mm) / **Uninstalled:** 1.5" (38 mm)

Angled Panel: 4.0" (102 mm)

Height:

1 RMU: 1.75" (44.45 mm)

2 RMU: 3.50" (88.90 mm)

Jack Opening: 1.21/1.67" D x 0.58" W x 1.02" H (30.8/42.4 x 14.6 x 25.8 mm)

CONSTRUCTION

Panel: Steel with corrosive resistant black finish; rear nickel plated

89D Bracket: Thermoplastic

ENVIRONMENTAL CONDITIONS

Operating & Storage Temperature: -40 to 185°F (-40 to 85°C)

Operating RH: 93% (non-condensing)

COMPLIANCE

CEA310E

WARRANTY

5 - Year Limited Component