



kramer

C-BM/BM

BNC Coax Video Cable

| 3G HD-SDI - BNC



Kramer's C-BM/BM is constructed of high performance RG-6 cable with 75Ω BNC connectors at each end. It offers outstanding quality, durability, and high performance for any video signal application

FEATURES

Quality Construction - RG-6 cable for the highest resolution signals

High-Quality Connectors - True 75Ω BNC connectors maintain correct impedance end-to-end

Varied Selection of Lengths - Available in versions of 1.5 to 150ft (0.5 to 45.7m)

Cable Specs - Tested to 3G. For detailed cable specs, see Kramer BC-1X



kramer

TECHNICAL SPECIFICATIONS

COAX	Conductor: 18 AWG solid bare copper Dielectric: Skin foam Shield: (A) 61% braid 34 AWG aluminum wire. (B) Dual foil/Mylar 25% overlap rate
CONSTRUCTION	Outside Jacket: PVC Outside Jacket Color: Dark gray with white lettering
DIAMETERS	Center Conductor: 1.02mm (0.0403in) Dielectric: 4.57mm (0.179in) Outside Diameter: 6.95mm (0.391in)
ELECTRICAL	Impedance: 75 Ω DC Resistance: 21.8 Ω /km (6.6 Ω /1000ft) Capacitance: 53.1pF/m (16.1pF/ft) Velocity of Propagation: 82% Temperature: -20° to 75°C (-4° to 167°F) Attenuation (dB/100 ft.): -0.3dB @1MHz -0.6dB @5MHz -0.8dB @10MHz -1.6dB @50MHz -2.0dB @100MHz -2.8dB @180MHz -4.4dB @400MHz -5.7dB @750MHz -6.7dB @1000MHz
REGULATORY	UL: CL2 CSA: C(UL) CL2



kramer

CONFIGURATIONS

C-BM/BM-1.5	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-3	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-6	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-10	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-15	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-25	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-35	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-50	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-75	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-100	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-150	1 BNC (M) to 1 BNC (M) RG-6 Video Cable