



kramer

BCLS-31

CAT 6A U/UTP 23AWG 650MHz Bulk Cable
– Low Smoke & Halogen Free



Kramer's BCLS-31 is a high-performance CAT6A U/UTP cable designed for IT, LAN and Ethernet installations. It is constructed with four pairs of 23AWG solid bare copper conductors with a cross filler in an LSZH jacket with internal rip cord and sequential markings every meter and packed on a fumigated plywood reel. The unique zigzag jacket design provides excellent performance of "six around one" bundle transmission. BCLS-31 cable exceeds CAT 6A specifications to provide additional performance and bandwidth beyond the basic standard

FEATURES

High-Performance Single Cable Transmission

Zigzag Jacket Design - Provides excellent performance of six around one bundle transmission

Round & Smooth Jacket without Twisted Stripe

High-Quality Safety Properties

Sweep Frequency up to 650MHz

Length - Available in wooden drums of 500m (1640ft)



kramer

TECHNICAL SPECIFICATIONS

CONSTRUCTION	Conductor: 4 pairs of 23AWG solid bare copper Insulation: Polyolefin (PO); blue & white, orange & white, green & white, brown & white Twist: Left-hand Assembly: Left hand direction Rip Cord: Polyester multi-yarn Jacket: Low smoke zero halogen (LSZH), yellow (Pantone 116C)
Filler:	Polyolefin (PO)
DIAMETERS	Jacket: Diameter: 8.3 ±0.2mm; thickness: 1.10 ±0.01mm Insulation: Blue & white: 1.17 ± 0.02mm Orange & white: 1.12 ± 0.02mm Green & white: 1.15 ± 0.02mm Brown & white: 1.10 ± 0.02mm
ELECTRICAL	Temperature & Voltage Rating: 60°C @300V Spark Test: 2.5kV DC AC Leakage Current: ≤10mA (1.5kV AC) through overall jacket Conductor DC Resistance: ≤9.38Ω /100m Resistance Unbalance: ≤5% Dielectric Strength: 1.5kV AC for 2sec Insulation Resistance: ≥5000MΩ /m Mutual Capacitance: ≤5.6nF /100m Capacitance Unbalance: ≤330pF /100m pair-to-ground Characteristic Impedance: 100±15Ω @1~100MHz Coupling Attenuation: ≤55dB @30MHz, ≤41dB @500MHz
USAGE AND ENVIRONMENTAL	Cable Cold Bend: -20°C for 4hr Insulation Tensile Strength: 2400 PSI min. (1.69kg/m,2) NVP 67% Temperature Range: Storage & shipping: -20°C to 60°C; installation: 0°C to 60°C; operation: -20°C to 60°C Minimum Bending Radius: ≥4 times of overall diameter Maximum Pulling Tension: ≤110N
REGULATORY PERFORMANCE	ANSI/TIA-568-C.2 (2009): Balanced Twisted-Pair Telecommunications Cabling and Components Standards ISO/IEC 11801 (Edition 2.2): Information technology – Generic cabling for customer premises IEC 61156-5 (Edition 2.0): Multicore and symmetrical pair/quad cables for digital

communications – Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1000 MHz – Horizontal floor wiring – Sectional specification

EN 50288-6-1:2013: Multi-element metallic cables used in analogue and digital communication and control – Part 6-1: Sectional specification for unscreened cables characterized up to 250MHz – Horizontal and building backbone cables

REGULATORY
SAFETY

EN 50173-1:2011: Information technology – Generic cabling systems – Part 1: General requirements

IEC 60332-1-2: Tests on electric and optical fiber cables under fire conditions – Part 1-2: Test for vertical flame propagation for a single insulated wire or cable – Procedure for 1kW pre-mixed flame

IEC 61034-1 / 61034-2: Measurement of smoke density of cables burning under defined conditions

IEC 60754-2 Test on gases evolved during combustion of materials from cables

EU Directive 2011/65/EC (RoHS 2)

EU Directive 2006/95/EC (LVD)

CE compliance date: 2010.01.01



kramer

CONFIGURATIONS

BCLS-31YL-5	CAT 6A U/UTP LSZH Cable - Yellow
-------------	----------------------------------
