



kramer

KDS-SW2-EN7

4K AVoIP Encoder Switcher



KDS-SW2-EN7 auto-switch encoder with HDMI and USB-C inputs

FEATURES

Outstanding end-user experience -

- 1 HDMI and 1 USB-C with charging capabilities for laptop
- Easy-to-use KM/KVM – Searchable OSD Menu for KM and fully configurable KVM roaming
- Large scale video wall – up to 16x16
- Instantaneous switching time – 1 second

Ideal for large-scale deployments -

- Highly scalable – 999 channels build in support
- State of the art management device
- Rich set of management capabilities – Standard P3K Open API , LCD screen for configuration

Robust security -

- Cost-effective from day one
- Full product range for any site, any application
- Plug-and-play with Netgear M4250 AVoIP switches, Kramer Control, KDS-USB2, etc.

Simple planning and rollout -

- Cost-effective from day one
- Full product range for any site, any application
- Plug-and-play with Netgear M4250 AVoIP switches, Kramer Control, KDS-USB2, etc.



kramer

TECHNICAL SPECIFICATIONS

Inputs	1 HDMI: On female HDMI connectors 1 USB-C: On a female USB-C connector
Outputs	1 HDMI: On a female HDMI connector
Ports	2 Ethernet: On R-J45 connectors 1 Balanced Audio: On a 5-pin terminal block connector 1 RS-232: On a 3-pin terminal block connector 1 IR: On a 3.5mm TRS connector 1 USB Host: On a USB-B connector 2 USB Device: On USB-A connectors
USB Features	Integrated USB Hubs 2-layer USB hubs when connecting to KDS-DEC7
Network	Multicast Through RTSP (Real Time Streaming Protocol): IGMP snooping non-blocking, Layer 2 Unicast Through RTSP (Real Time Streaming Protocol) Bit Rate Peak: 850Mbps, 4K average: 350Mbps, 1080p average: 250Mbps
Video	Compression Standard: JPEG based, private stream Max Resolution: 4K@30Hz 4:4:4 HDR 10: Up to 4K30 4:2:2 12 bit
Video Streaming	Compression Standard: JPEG2K based, proprietary stream Max Input Resolution: 4K@60hz (4:2:0) Max Output Resolution: 4K@30hz (4:4:4) Max End-to-End Resolution: 4K@30hz (4:4:4) Scaler: Yes End-to-End Latency: 33msec Switching Time: 1sec
Resolution	4096x2160@60Hz, 1600x1200@60Hz, 1280x960@60Hz, 848x480@60Hz, 3840x2160@60Hz, 1600x900@60Hz, 1280x800@60Hz, 800x600@60Hz, 1920x1200@50Hz, 1440x900@60Hz, 1280x768@60Hz, 720x576@60Hz, 1920x1080@60Hz, 1400x1050@60Hz, 1280x720@60Hz, 720x480@50Hz, 1856x1392@60Hz, 1366x768@60Hz, 1224x768@70Hz, 640x480@60Hz, 1792x1344@60Hz, 1360x768@60Hz, 1152x864@70Hz, 640x400@85Hz, 1680x1050@60Hz, 1024x768@60Hz, 640x350@85Hz
Audio	Supported Formats LPCM, Dolby and DTS LPCM LPCM upto 7.1/24-bit/192kHz Dolby Dolby Atmos™, Dolby TrueHD, Dolby Digital Plus™, Dolby Digital EX, Dolby Digital 5.1, Dolby Digital 2/0 Surround, Dolby Digital 2/0 DTS DTS-HD Master Audio™, DTS-HD, DTS-ES Discrete 6.1, DTS-ES Matrix 6.1, DTS Digital Surround 5.1

Security	HTTPS, 802.1x, OWASP-10, AES-128 encryption of AV streaming with changeable key
User Interface	Indicators: LINK, NET and ON LEDs, front panel LCD Display Controls: Restart and factory reset rear panel button, embedded web pages, P3K API commands via Ethernet, front panel navigation buttons
Power	PoE (Power over Ethernet) 37V to 57V, maximum power consumption 19W (when USB at full load) Optional power supply 24V DC, 5A, max power 68W with USB-C charging
Environmental Conditions	Operating Temperature: 0 to + 45°C (32 to + 113 °F), 10% to 90%, non-condensing Storage Temperature: -20 to +70°C (-4 to + 158 °F), 10% to 90%, non-condensing Humidity: 10% to 90%, non-condensing
Product Dimensions	18.90cm x 14.50cm x 2.76cm (7.44" x 5.71" x 1.09") W, D, H
Product Weight	0.7kg (1.5lbs) approx
Shipping Dimensions	31.20cm x 17.90cm x 7.60cm (12.28" x 7.05" x 2.99") W, D, H
Shipping Weight	0.9kg (2.1lbs) approx

