

Product data sheet

Specifications



Galaxy VS UPS 50kW 208V for up to 5 internal 9Ah smart modular battery strings, Start-up 5x8

GVSUPS50K0B5FS

Overview

Presentation Highly efficient, easy-to-deploy 50kW, 208V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. This UPS is for up to 5 smart modular high capacity battery strings, but is supplied without batteries, so you can easily customize the battery runtime. Includes 5x8 start-up service.

Lead time Usually Ships within 2 Weeks

Main

Main Input Voltage 208 V 3 phase

Other Input Voltage 200 V
220 V

Main Output Voltage 208 V 3 phase

Other Output Voltage 200 V
220 V

Kw Rating 50 kW

Rated power in VA 50 kVA

Battery Type Internal modular battery
VRLA

Provided equipment Dust filter
Installation manual
Integrated network management
Start-Up Service
EcoStruxure Ready

Batteries & Runtime

Efficiency [View Efficiency Graph](#)

Battery Voltage 480V

End of Discharge Battery Voltage 384 V DC

End of Discharge Maximum Battery Current 136 A

Battery power in VAH 0 VAh runtime

Extendable Run Time 0

General

Redundant No

Product or Component Type Uninterruptible power supply (UPS)

Physical

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

color	White
Height	77.6 in (197 cm)
Width	21.7 in (55 cm)
Depth	33.3 in (84.7 cm)
Net Weight	652.6 lb(US) (296 kg)
USB compatible	No

Input

Input Frequency	40 - 70 Hz
Efficiency at full load	177...239 V 208 V
Maximum Input Current per Phase	179 A
Maximum Short Circuit Withstand (I _{cw})	65 kA
Input Total Harmonic Distortion	Less than 3% for full load
Load power factor	From 0.7 leading to 0.7 lagging without any derating
Input Power Factor at Full Load	0.99

Output

Max Configurable Power (Watts)	50 kW
Harmonic distortion	Less than 5%
Output Frequency (sync to mains)	50 Hz sync to mains 60 Hz sync to mains
Crest factor	2.5
Waveform Type	Sine wave
Output voltage tolerance	+/-1% after 50ms
Output Voltage THD	< 1% linear load and < 5% non-linear load
Overload Operation	10 minutes @ 125% and 60 seconds @ 150%
Bypass type	Built-in Static Bypass
Maximum configurable power in VA	50 kVA

Conformance

Standards	CSA C22.2 No 107.3 FCC Part 15 class A IEC 62040-1-1 IEC 62040-2 IEC 62040-3 UL 1778 5th edition OSHDP
-----------	--

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...3300 ft
Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)
Storage Relative Humidity	10...80 % non-condensing
Storage altitude	0...10000 ft (0.0000000000...3048.0000000000 m)

Acoustic level	65 dBA
Online Thermal Dissipation	10339 Btu/h
IP degree of protection	IP20

Communications & Management

Control panel	Touch Screen LCD User Interface
---------------	---------------------------------

Ordering and shipping details

GTIN	731304409823
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	82.0 in (208.2 cm)
Package 1 Width	39.8 in (101 cm)
Package 1 Length	29.7 in (75.5 cm)
Package 1 Weight	551.2 lb(US) (250 kg)

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)