



DTK-DF240S1 240VAC Surge Protective Device

Visual, audible, smart. **DITEK's DTK-DF240S1** sets a new standard for 240VAC power surge protection. Its patented design provides maximum critical load protection by minimizing AC supply voltage spikes and isolating incoming surges that originate from lightning or other sources. Each DF Series module features an LED health status indicator that flashes and sounds an audible alarm when protection has been compromised; and the wall-mountable enclosure includes dry contacts for remote notification when service is required.

Product Features

- Protects 240VAC single phase critical loads
- Audible alarm sounds when protection is compromised or module is removed
- Push-button delay included to silence audible alarm for 24 hours
- Rapid-Replacement modules for ease of installation
- Form C dry contacts for remote notification when service is required
- UL1283 EMI/RFI noise filtering ensures clean power for connected equipment
- Separate LED indicators for system power, ground presence and protection status
- Accepts both flexible and rigid conduit
- No additional enclosure required

Applications

- Fire Alarm Panels and Control Panels
- Electronic Fueling Equipment and Tank Monitors
- POS Devices and Lottery Machines
- Home Automation Systems

Accessories

- Replacement Module, p/n DTK-DF240M



Technical Specifications

Voltage Configuration:	240VAC Single Φ (2W + G)
MCOV:	300V
Protection Modes:	L-G, L-N, N-G
Voltage Protection Rating:	1200V L-G, L-N 1200V N-G
Surge Current Rating:	50,000A
Max. Continuous Current:	20A
SCCR:	10,000A
Nominal Discharge Current Rating (I_n):	5kA
Operating Frequency:	50/60Hz
EMI/RFI Filtering Attenuation:	Up to 35dB, 100kHz – 100MHz
Audible Alarm dB Level:	80dB @ 1' (MAX)

Mechanical Specifications

Connection Method:	Mechanical lugs, 12 AWG max $\frac{3}{4}$ " NPT pre-drilled holes In/Out
Housing:	ABS
Operating Temperature:	-4°F – 140°F (-20°C – 60°C)
Maximum Humidity:	95% non-condensing
Dimensions:	6.6" L x 5.4" W x 2.6" H (168 mm x 137 mm x 66 mm)
Weight:	15.5 oz (0.44 kg)

Quality Standards & Approvals

Certifications:	UL1449 5 th Edition, UL1283 CSA C22.2 No. 269.2-17
SPD Type:	Type 2
Warranty:	10 Year Limited Warranty

Find us in

MasterSpec[®]

a product of The American Institute of Architects

