

PUBLIC VIEW MONITOR

LARGE FORMAT

FEATURES

- 5MP WDR Camera with Varifocal Lens for Superior Image Quality
- Remote Zoom and Focus Capabilities for Simple Setup
- Power-over-Ethernet (PoE) Capable for Easy Installation
- Attention Grabbing Features Deliver High-Deterrent Value
- UL Listed

SPECIAL FEATURES

- Remote Varifocal Setting and Auto-Focus
- Face Blocking
- Video Motion Detection
- White LEDs (On, Off, Flashing, Motion On, Motion Flash)



ACCESSORIES

- MMB0302** Articulating Wall Mount, VESA 75x200, Black
- MMB0601** Ceiling Mount, Back-to-Back, 1.5" NPT, VESA 400x400 Black (w/ CM-XL-x Pole)
- MMB0602** Ceiling Mount, Single, 1.5" NPT, VESA 400x400, Black (w/ CM-XL-x Pole)
- MMB0603** Ceiling Mount, Single, 1.5" NPT, VESA 75-200, Black (w/ CM-XL-x Pole)
- MMB0604** Ceiling Mount, Back-to-Back, 1.5" NPT, VESA 75-200, Black (w/ CM-XL-x Pole)
- CM-XL-5-W** Telescoping Pole, 2-5.5' length, White (w/ MMB060x Ceiling Mount)
- CM-XL-11-W** Telescoping Pole, 6-11' length, White (w/ MMB060x Ceiling Mount)
- CM-XL2-21-W** Telescoping Pole, 8-21' length, White (w/ MMB060x Ceiling Mount)
- DCSP-CMXL** Drop Ceiling Support Plate, use with a CM-XL-x Pole, White
- CS-7** Unistrut, 7', Open Ceiling Framing Channel, White

| MODEL NUMBER | PVM21-B-2094-B | PVM27-B-2094-B | PVM32-B-2094-B |
|-----------------------------|------------------------------|------------------------------|------------------------------|
| DISPLAY | | | |
| Panel | 21.5" LED Backlight | 27" LED Backlight | 31.5" LED Backlight |
| Resolution | 1920 x 1080 | 1920 x 1080 | 1920 x 1080 |
| Aspect Ratio | 16:9 | 16:9 | 16:9 |
| Brightness | 250 NIT | 300 NIT | 300 NIT |
| Contrast Ratio | | 3000:1 | |
| Viewing Angle - W x H | | 178° x 178° | |
| Response Time | 18 ms | 12 ms | 8 ms |
| CABINET | | | |
| VESA Pattern | 100 x 100, 200 x 100 | 100 x 100, 200 x 100 | 200 x 200 |
| Dimensions - W x H x D (in) | 19.80 x 14.20 x 1.80 | 25.08 x 17.65 x 1.90 | 29.68 x 20.89 x 2.25 |
| Weight | 11.2 lbs (5.1 kg) | 18.2 lbs (8.3 kg) | 27.7 lbs (12.3 kg) |
| Construction | Black Plastic w/ Glass Front | Black Plastic w/ Glass Front | Black Plastic w/ Glass Front |
| Operating Temperatures | 32°F - 104°F (0°C - 40°C) | 32°F - 104°F (0°C - 40°C) | 32°F - 104°F (0°C - 40°C) |
| CONNECTIONS / POWER | | | |
| Input Voltage | 48VDC POE or 24VDC | 48VDC POE or 24VDC | 48VDC POE or 24VDC |
| Power Consumption | 35 Watts | 45 Watts | 65 Watts |
| Network | RJ45 | RJ45 | RJ45 |
| HDMI | 1 Input | 1 Input | 1 Input |
| USB | HDMI | HDMI | HDMI |
| Power | 2.5mm Barrel Plug | 2.5mm Barrel Plug | 2.5mm Barrel Plug |

CAMERA

| | |
|------------------------------|-------------------------------------|
| Image Sensor | 1/2.7" OmniVision 0505A20 |
| Resolution | 5MP, 2688 x 1944 |
| Dream Stream Settings | Maximum Frame Rate = 30 fps |
| Minimum Illumination | 0.01 Lux/F1.2 |
| S/N Ratio | 39 dB |
| Lens | Varifocal 2.8-12mm, Auto zoom/focus |
| Shutter Speed | 1/60—1/10,000 sec. |
| Video Format | H.264, H.265 |
| Compatibility | Vivotek, ONVIF Profile S |

CERTIFICATIONS

UL, CE, FCC Class B RoHS Compliant