



# AT-SWH-000

## Power Safety Kit

### Technical Specifications

<b>Model Name</b>	AT-SWH-000
<b>Supported Models</b>	AT-CAB-001, AT-CAS-001
<b>Feature</b>	Suitable for VIVOTEK AT-CAB-001 or AT-CAS-001 Cabinet Surge protection Fuse Alarm-door switch
<b>Operating Temperature</b>	MCB fuse: -40 °C ~ 75 °C (-40°F ~ 167°F) Surge protector: -40 °C ~ 80 °C (-40°F ~ 176°F) Door switch: -40 °C ~ 85 °C (-40°F ~ 185°F)
<b>Approvals</b>	MCB fuse: IEC/EN 60898-1, IEC/EN 60947-2, UL 1077 Surge protector: IEC 61643-11 / EN 61643-11 Door switch: EN 61058, UL 61058
<b>Weight</b>	MCB fuse: 125 g Surge protector: 240g Door switch: 10 g
<b>Dimensions</b>	MCB fuse: 88x17.5x69 mm Surge protector: 95x35.6x58 mm Terminal block 4x2.5 mm <sup>2</sup> (Gray): 72.6x5.1x35.5 mm Terminal block 4x2.5 mm <sup>2</sup> (Yellow/Green): 72.6x5.1x35.5 mm Terminal block 2x4 mm <sup>2</sup> (Yellow/Green): 57x6.1x35.5 mm Door switch: 41x10x30 mm Door switch cable: 300 mm Screw: 75 mm
<b>Included Accessories</b>	MCB fuse, surge protector type 2, terminal block 4x2.5 mm <sup>2</sup> (gray), terminal block 4x2.5 mm <sup>2</sup> (yellow/green), terminal block 2x4 mm <sup>2</sup> (yellow/green), door switch, door switch cable, screw