

## 22" BNC FRAMELESS LED MONITOR

24/7/365 Operating Capability



The 22" BNC frameless LED monitor is designed to excel in 24/7 video surveillance applications. Delivering full HD resolution and 16.7 million colors, the monitor displays every detail with precision. HDMI and VGA inputs and a BNC input/output easily accommodate multiple devices and allow for BNC looping. The monitor also features source auto detection and quick touch scalability for quick setup.

### FEATURES

- 21.5" Diagonal Viewing Size
- 1920x1080P Full HD Resolution
- 178° Ultra-Wide Viewing Angle
- Source Auto Detection
- Low Blue Light Technology
- Quick Touch Scalability 16:9/4:3
- BNC, VGA, HDMI and Audio Inputs
- Includes VGA, HDMI, Audio and Power Cables
- Two Built-In Speakers
- 30-Month Warranty
- Part #: OE-22LED3
- UPC: 840049310490
- Length: 19.3" (490.2mm)
- Width: 8.6" (218.4mm)
- Height: 14.1" (358.1mm)
- Weight: 4.85 lbs. (2.19kg)
- UL Listed



## MONITEUR BNC À DEL SANS CADRE DE 22 PO

Capacité de fonctionnement 24/7/365



Le moniteur BNC à DEL sans cadre de 22 po est parfait pour les applications de vidéosurveillance en permanence. Grâce à une résolution HD intégrale et à ses 16,7 millions de couleurs, ce moniteur saura afficher tous les détails avec précision. Les entrées HDMI et VGA et une entrée/sortie BNC accueillir plusieurs appareils et permettre le bouclage BNC. Le moniteur est aussi doté de fonctionnalités de détection automatique de la source et de mise à l'échelle pour une configuration facile.

### CARACTÉRISTIQUES

- Dimensions d'achage diagonales de 21,5 po
- Résolution HD intégrale 1920x1080 p
- Grand angle de vue de 178°
- Détection automatique de la source
- Technologie à faible lumière bleue
- Mise à l'échelle Quick Touch 16:9/4:3
- Entrées BNC, VGA, HDMI et audio
- Comprend des Câbles VGA, HDMI, audio et d'alimentation
- Deux haut-parleurs intégrés
- Garantie de 30 mois
- N° de pièce : OE-22LED3
- UPC : 840049310490
- Longueur : 19,3 po (490,2 mm)
- Largeur : 8,6 po (218,4 mm)
- Hauteur : 14,1 po (358,1 mm)
- Poids : 4,85 lb (2,19 kg)
- Homologué UL



TECHNICAL SPECIFICATIONS	
<b>Model</b>	OE-22LED3
<b>Screen Diagonal Dimension (inches)</b>	21.5"
<b>Viewable Area W x H</b>	18.8" x 10.2" (477.5mm x 259mm)
<b>LED Type</b>	Edge LED
<b>Pixel Pitch (mm)</b>	0.2493mm x 0.241mm
<b>Screen Maximum Resolution</b>	1920x1080
<b>Display Resolutions</b>	720x400; 640x480; 800x600; 1024x768; 1280x1024; 1366x768; 1920x1080
<b>Supported Input Resolutions</b>	720x400; 640x480; 800x600; 1024x768; 1280x1024; 1366x768; 1920x1080
<b>Refresh Rate (hertz)</b>	60Hz
<b>Color Depth (millions)</b>	16.7 million colors
<b>Brightness</b>	250 nits (250 cd/m <sup>2</sup> )
<b>Auto Adjust</b>	Yes
<b>Monitor Aspect Ratio</b>	16:9
<b>Display Aspect Ratio</b>	OSD options: Full/4:3/Over Scan
<b>Horizontal TV Lines</b>	1080
<b>Contrast Ratio</b>	4000:1SCR
<b>Response Time (ms)</b>	5 ms (GTG)
<b>View Angle H/V (degrees)</b>	178° x 178°/CR>10
<b>Digital Video Inputs</b>	HDMI up to 1920x1080
<b>Analog Video In/Out</b>	VGA up to 1920x1080
<b>Connectors</b>	HDMI x 1, VGA x 1, BNC IN x 1, BNC OUT x 1, AUDIO OUT x 1
<b>Audio Inputs (stereo)</b>	1 x 3.5mm mini-jack
<b>Speakers (watts)</b>	2 x 2 watts
<b>Stand-by (watts)</b>	<0.5 watt
<b>Power Consumption (watts)</b>	16 watts typical
<b>Monitor Body Dimensions</b>	19.3" x 1.5" x 11" (490.2mm x 38.1mm x 279.4mm)
<b>Dimensions Monitor+Stand</b>	19.3" x 8.6" x 14.1" (490.2mm x 218.4mm x 358.1mm)
<b>Panel Surface</b>	Matte black
<b>Case and Stand Material</b>	Plastic
<b>VESA Mounting Pattern (mm)</b>	75mm x 75mm
<b>Base/Stand Included</b>	Yes
<b>Base Tilt Angle</b>	-5°-15°
<b>Weight Cabinet Only</b>	4.08 lbs. (1.85kg)
<b>Weight Cabinet+Base Stand</b>	4.85 lbs. (2.19kg)
<b>Power Supply (internal)</b>	AC 100-240V-50/60Hz 1.1A
<b>Operating Temperature</b>	0°C-40°C / 32°F-104°F
<b>Storage Temperature</b>	-20°C-50°C / -4°F-122°F
<b>Operating Humidity</b>	10-90%
<b>Accessories Included in the Box</b>	Power cable/HDMI cable/VGA cable/Audio cable/IR Remote Stand support/Screws/Base of stand/User manuals
<b>Mounting Screw Size (mm)</b>	M4-L8 mm/4pcs
<b>Certifications</b>	CE/FCC/RoHS/HDMI/UL/WEEE/REACH
<b>Warranty</b>	30 Months