

Straight Non-Metallic Connectors

For use with non-metallic liquid tight conduit, type B only. Produced from UV rated plastic for long outdoor life.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
NMLT38	54380	3/8	1/2	25	100	1.545	.535	1.410
NMLT50	54500	1/2	1/2	25	100	1.545	.535	1.410
NMLT75	54750	3/4	3/4	10	50	1.600	.550	1.595
NMLT100	54100	1	1	5	25	1.975	.670	1.930
NMLT125	04223	1-1/4	1-1/4	5	25	2.293	.645	2.428
NMLT150	04222	1-1/2	1-1/2	2	10	2.175	.660	2.700
NMLT200	04221	2	2	2	10	2.400	.670	3.360



MADE IN USA.

Add suffix "BL" to Catalog # when ordering in black, for example NMLT38BL.

INSTALLATION INSTRUCTIONS

Arlington's reusable Liquid tight Fittings may be secured to conduit while fully assembled because of our no spin ferrule. Simply loosen nut, and screw onto conduit. A positive liquid tight seal is provided by our pressure sensitive internal gland when the nut is tightened. A liquid tight seal is also assured between the fitting and box by a sealing ring.

