



# RACK PDU, BASIC, 0U/1U, 220-240V, 32A, (4) C19, EMEA/ ASIA

AP6032A

### **Overview**

Lead time Usually in Stock

### Main

| Colour                    | Black                              |
|---------------------------|------------------------------------|
| Product or component type | PDU                                |
| PDU type                  | Basic                              |
| Cord length               | 3.7 m                              |
| Provided equipment        | Installation guide<br>Safety guide |

### Complementary

| Input Voltage            | 200 V                 |  |
|--------------------------|-----------------------|--|
|                          | 230 V                 |  |
|                          | 240 V                 |  |
| Height                   | 4.4 cm                |  |
| Width                    | 43.8 cm               |  |
| Output Voltage           | 200 V                 |  |
|                          | 230 V                 |  |
|                          | 240 V                 |  |
| Depth                    | 9.3 cm                |  |
| Net weight               | 2.78 kg               |  |
| mounting location        | Front                 |  |
|                          | Rear                  |  |
| Mounting preference      | No preference         |  |
| Input Plug Type          | IEC 60309 32 A 2P + E |  |
| mounting mode            | Not rack-mountable    |  |
| Rack units               | 1U                    |  |
| Mounting position        | Horizontal            |  |
| Permissible voltage      | 200240 V              |  |
| Max line current         | 32 A                  |  |
| Input current limits     | 32 A                  |  |
| Load capacity            | 7400 VA               |  |
| Network frequency        | 50/60 Hz              |  |
| Outlet type and quantity | 4 IEC 60320 C19       |  |

## **Environment**

| product certifications | CE   |  |
|------------------------|------|--|
|                        | IRAM |  |
|                        | VDE  |  |

# **Packing Units**

| •                            |                |
|------------------------------|----------------|
| Unit Type of Package 1       | PCE            |
| Number of Units in Package 1 | 1              |
| Package 1 Height             | 20.8 cm        |
| Package 1 Width              | 18 cm          |
| Package 1 Length             | 47.8 cm        |
| Package 1 Weight             | 3.75 kg        |
| SCC14                        | 10731304327827 |

# **Contractual warranty**

Warranty 2 years repair or replace



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

#### Resource performance

Energ

**Energy Efficient Product** 



Take-Back Program Available

### Well-being performance



Lead Free

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration             |
|--------------------------|-------------------------------|
| Eu Rohs Directive        | Compliant EU RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile      | End of Life Information       |

## **Product datasheet**

### **AP6032A**

Image of product / Alternate images

**Alternative** 



