

Product data sheet

Specifications



InfraStruxure PDU, 150kVA, 416A, 480V:208V Isolation Transformer, 84 Poles, 1 Subfeed

PDPB150G6F

Overview

Lead time Usually Ships within 3 Weeks

Main

Main Input Voltage 480 V 3 phase

Main Output Voltage 208 V 3 phase

Provided Equipment Installation guide
Network Management Card

Physical

Height 78.7 in (200 cm)

Width 23.6 in (60 cm)

Depth 42.1 in (107 cm)

Net Weight 1803.78 lb(US) (818.18 kg)

mounting location Front

Mounting preference No preference

Mounting Mode Not rack-mountable

Input

Input Frequency 60 Hz

Conformance

Product Certifications cUL Listed
UL Listed

Environmental

Ambient Air Temperature for Operation 32...104 °F (0...40 °C)

Relative Humidity 0...95 %

Operating altitude 0...3333 ft

Ambient Air Temperature for Storage 5...113 °F (-15...45 °C)

Storage Relative Humidity 0...95 %

Storage altitude 0...30000 ft (0.0000000000...9144.0000000000 m)

Ordering and shipping details

GTIN 731304303381

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.6 in (215 cm)
Package 1 Width	48.03 in (122 cm)
Package 1 Length	40.0000000000 in (101.6 cm)
Package 1 Weight	1904.002 lb(US) (863.64 kg)

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Eu Rohs Directive

Under investigation
