Eaton 9PX6K-10

Catalog Number: 9PX6K-10

Eaton 9PX UPS, Network card included, 3U, 6000 VA, 5400 W, L6-30P input w/10-foot line cord; Outputs: (2) L6-20R, (2) L6-30R, Hardwired, 208V

General specifications

Product Name

Catalog Number

Eaton 9PX UPS

9PX6K-10

UPC

Product Length/Depth

743172090522

28.4 in

Product Height

Product Width

5.1 in

17.3 in

Product Weight

Warranty

106 lb

3 year limited

Compliances

Certifications

FCC Part 15

IEC 62040-2:2006 Cat C2

CE Marked

NOM

CISPR22 Class A / FCC part 15 Class A cULus Listed



Battery

Runtime graph

View runtime graph

Battery management

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

Battery replacement

Hot-swappable internal batteries and extended battery modules (EBMs)

Battery type

Sealed, lead-acid

Extended battery capability

4 EBM maximum

Electrical output

Receptacle

(2) L6-20R, (2) L6-30R, Hardwired

Topology

Online/Double-conversion

Wattage

5400 W

VA rating

6000 VA

Output waveform

True sine wave

Output power factor

0.9

Output nominal voltage

120/240V default (200/208/220/230/240V)

Output frequency

50/60 Hz

Electrical input

Input connection

L6-30P

Input cord length

10 ft

Input nominal voltage

208V default (200/208/220/230/240V)

Nominal frequency

50/60 Hz

Input frequency range

60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz

Input power factor

>0.99 typical

Communications

Communication

RS-232 (RJ-45), USB

Expansion slots

(1) Mini-Slot (MS) expansion port with Gigabit Network Card (NETWORK-M2) included

Ethernet interface

Yes

Includes network card

Yes

Software compatibility

Intelligent Power Software Suite

User interface

Graphical display, UPS status in single view

Environmental

Altitude

Additional specifications

Special features

<1000m for nominal power, 10% power degrading every 1000m (up to 3000m)

BTU Rating

Online: 1245, Battery: 1895

Noise level

<45 dB at 1 meter

Relative humidity

0-95% non-condensing

Temperature range

0° to 40°C (32° to 104°F)

Hot-swappable internal batteries

Form factor

Rack/tower

Rack size

3U

Rack mounting kit

Yes

Efficiency

93% with resistive load

Package contents

9PX6K 6 kVA UPS

Gigabit Network Card

(Network-M2)

4-post rail kit (9RK)

User manual

Quick start guide

Tower pedestals

Intelligent Power Software

Suite CD

RS-232 serial cable

USB cable

Cable gland for hardwire

connection

Phillips head screw driver

Internal bypass

Yes

Warranty and support

Standard factory warranty

3-YEAR FACTORY

WARRANTY

- 3 years
- Parts, electronics and batteries coverage
- Standard ground shipping
- Technical support

Extended service plans

ADVANCED DEPOT

EXCHANGE

- 5-year depot repair:

Resources

Application notes

9PX5KP1 and 9PX6KP1 interconnect diagram

Brochures

Eaton 9PX 5-11 kVA UPS brochure

Drawings

Battery Integration System Pro-E drawing

9PX6K Pro-E drawing

Manuals and user guides

Eaton 9PX Maintenance Bypass User Guide

9PX UPS (5-6 kVA) user guide

9PX battery integration system user guide

9SW5Y-6000UC

- Expedited parts coverage for 5 years
- Parts, electronics and UPS batteries coverage
- Next business day shipping
- Technical support

5-YEAR ON-SITE PLAN:

WFLN75XX-6009UC

- On-site parts and labor coverage for years 5
- Parts, electronics and UPS batteries coverage
- 24x7 on-site labor coverage, next-day response
- Next-day shipping
- Technical support

Specifications and datasheets

9PX technical specifications: 5 and 6 kVA

Eaton Specification Sheet - 9PX6K-10



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.

