

# Eaton EMAT09-10

Catalog Number: EMAT09-10

Eaton Managed rack PDU, 1U, 5-20P, L5-20P input, 1.92 kW max, 120V, 16A, 10 ft cord, Single-phase, Outlets: (8) 5-20R

## General specifications



Product Name	Catalog Number
Eaton managed PDU	EMAT09-10
UPC	Product Length/Depth
743172082664	19 in
Product Height	Product Width
8 in	1.69 in
Product Weight	Warranty
7.1 lb	3 year
Compliances	Certifications
Contact Manufacturer	UL Listed

## Product specifications

### Form factor

1U

### Outlet control

Yes

### Phase

Single-phase

### Wattage

1.92 kW max

### Amperage Rating

16A

### Input voltage

120V

### Input connection

5-20P, L5-20P

### Outlets

(8) 5-20R

### Cord length

10 ft

### Frequency rating

50-60 Hz

### Operating Temperature

0° to 60°C (32° to 140°F)

## Resources

### Certification reports

[Eaton ePDU certificate of volatility](#)

[Eaton RoHS Declaration of Conformity: ePDU G3](#)

### Drawings

[Eaton Advanced Monitored and Managed ePDU visio stencil](#)

[Eaton ePDU Managed EMAT09-10 technical drawing](#)

### Manuals and user guides

[Eaton ePDU G3 replace and configure eNMC module](#)

[Eaton ePDU G3 1U and 2U installation addendum](#)

[Eaton ePDU G3 operations manual](#)

[Eaton Double-wide G3 ePDU installation and connectivity quick start guide](#)

[Eaton ePDU G3 instruction set - system objects](#)

### Specifications and datasheets

[Eaton Specification Sheet - EMAT09-10](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)