

Eaton PC2715

Catalog Number: PC2715

Eaton Basic rack PDU, 2U, (2) L6-30P input, 4.99 kW max, 208-240V, 24A, 0 ft cord, Single-phase, TAA compliant, Outlets: (2) L6-30R



General specifications

Product Name	Catalog Number
Eaton basic PDU	PC2715
UPC	Product Length/Depth
786685391205	8 in
Product Height	Product Width
0.0001 in	19 in
Product Weight	Warranty
0.0001 lb	3 year
Compliances	Certifications
TAA Compliant	UL Listed

Product specifications

Form factor

2U

Outlet control

No

Phase

Single-phase

Wattage

4.99 kW max

Amperage Rating

24A

Input voltage

208-240V

Input connection

(2) L6-30P

Outlets

(2) L6-30R

Cord length

Hardwired

Frequency rating

50-60 Hz

Operating Temperature

0° to 60°C (32° to 140°F)

Resources

Certification reports

[Eaton RoHS declaration of conformity: ePDU G3](#)

[Eaton RoHS Declaration of Conformity: ePDU G3](#)

Drawings

[Eaton PDU PC2715 technical drawing](#)

Installation instructions

[Eaton ePDU G3 troubleshooting guide](#)

Manuals and user guides

[Eaton ePDU G3 installation and connectivity quick start](#)

[Eaton ePDU G3 1U and 2U installation addendum](#)

[Eaton ePDU G3 operations manual](#)

[Eaton ePDU G3 replace and configure eNMC module](#)

Specifications and datasheets

[Eaton Specification Sheet - PC2715](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)