
VPC Vertical Patching Channel (VPC)

Siemon's enhanced Vertical Patching Channel (VPC) sets a new standard for cable management systems by improving appearance, accessibility and cable routing on both the front and rear of the rack. Designed as a stand-alone manager to be mounted between adjacent racks the VPC features a full length, hinged door on the front to conceal patch cord routing. The rear manager is open for ready routing of large bundles of horizontal/backbone cabling. With its easy access design, high capacity and professional appearance, the VPC is ideal for both installers and end users alike.





Rear channel retainers can be hinged in either direction and are removable enabling relocation to any position along the rear vertical channel



The VPC is fully side stackable for use in ultra high density environments. The doors can be individually opened 60° or adjacent doors can be removed for full access





All of the cable routing points on the vertical channels are rounded to allow patch cords to seamlessly enter and exit the managers without risk of cable deformation



Ordering Information

6-inch Enhanced Vertical Patching Channel

Part Number

Description

VPCA-6 2.1m x 152mm (7 ft. x 6 in.) vertical patching channel. Includes front cover, 6 rear channel

retainers and mounting hardware

height: 2.1m (7.0 ft.) width: 152.4mm (6.0 in.) depth: 304.8mm (12.0 in.)



Comprehensive cable management can be created using Siemon's RS-07 and HCM Series horizontal cable managers

12-inch Enhanced Vertical Patching Channel

Part Number Description

VPCA-12......2.1m x 305mm (7 ft. x 12 in.) vertical patching channel. Includes front cover, 12 rear channel

retainers and mounting hardware

height: 2.1m (7.0 ft.) width: 304.8mm (12.0 in.) depth: 304.8mm (12.0 in.)



VPCA-12 shown with two RS-07 racks and angled patch panels



CABLE MANAGER CAPACITY TABLE

	Cable Diameter in. (mm)											
Part Number	0.13 (3.30)	0.15 (3.81)	0.17 (4.32)	0.19 (4.83)	0.21 (5.33)	0.23 (5.84)	0.25 (6.35)	0.27 (6.86)	0.29 (7.37)	0.31 (7.87)	0.33 (8.38)	0.35 (8.89)
VPCA-6 (Front)	683	513	399	319	261	218	184	158	137	120	106	94
VPCA-6 (Rear)	1059	795	619	495	405	338	286	245	212	186	164	146
VPCA-12 (Front)	1464	1100	856	685	561	467	396	339	294	257	227	202
VPCA-12 (Rear)	2118	1591	1238	991	811	676	572	491	425	372	328	293

Cable capacities reflect a calculated fill rate of 40% which is intended to reflect 100% fill during actual use due to side cable entry.



Ordering Information

Vertical Manager - Accessories

Part Number Description

VCM-FGR-6......152mm (6 in.) Vertical Cable Manager Replacement Fingers, 9U, Set of 2

Part Number Description

VCM-DR(XX)..... Replacement Door

Use (XX) to specify width: 6 = 152mm (6 in.) 12 = 304mm (12 in.)



RS-VCM..... Quarter-turn Hook & Loop Cable Managers, Includes roll of (10)

457mm (18 in.) black hook & loop cable managers and (10) quarter-turn mounting clips



VP-SPL.....Quarter-turn Fiber Management Spool, Bag of 5



RS-CNL-MGR Channel retainers for use with VPCA-6, VPCA-12, RS-CNL and RS-CNL3



For related product information request Spec Sheet(s):

RS Rack System (PROD-SS-SRS) 19 inch Cable Managers (PROD-SS-CBM)

Because we continuously improve our products, Siemon reserves the right to change specifications and availability without prior notice.

North America P: (1) 860 945 4200

www.siemon.com/SIS

Asia Pacific P: (61) 2 8977 7500

Latin America P: (571) 657 1950/51/52

Europe P: (44) 0 1932 571771

China P: (86) 215385 0303

India Middle East

P: (971) 4 3689743

Siemon Interconnect Solutions P: (1) 860 945 4213

