

FLUKE®

Fluke 116

HVAC Multimeter

with Temperature and Microamps

Technical Data



Compact true-rms meter for HVAC troubleshooting

The Fluke 116 was specifically designed for the HVAC professional. It has everything needed in an HVAC meter including temperature and microamp measurements to quickly troubleshoot problems with HVAC equipment and flame sensors.

Features include:

- Built in thermometer for HVAC applications
- Microamps to test flame sensors
- LoZ: helps prevent false readings due to ghost voltage
- Large white LED backlight to work in poorly lit areas
- Resistance, continuity, frequency and capacitance
- Min/Max/Average with elapsed time to record signal fluctuations
- Compact ergonomic design for one-handed operation
- Compatible with optional magnetic hanger (ToolPak™)
- CAT III 600 V safety rated

General specifications

Accuracy is specified for 1 year after calibration, at operating temperatures of 18 °C to 28 °C, with relative humidity at 0 % to 90 %.

The accuracy specifications take the form of:
 $\pm ([\% \text{ of reading}] + [\text{counts}])$

| | |
|---|---|
| Maximum voltage between any terminal and earth ground | 600 V |
| Surge protection | 6 kV peak per IEC 61010-1 600 V CAT III, Pollution Degree 2 |
| Display | Digital: 6,000 counts, updates 4/sec |
| Bar graph | 33 segments, updates 32/sec |
| Operating temperature | -10 °C to + 50 °C |
| Storage temperature | -40 °C to + 60 °C |
| Battery | 9 volt Alkaline, NEDA 1604A/IEC 6LR61 |
| Battery life | 400 hours typical, without backlight |

Actual size



Accuracy specifications

| Measurement | Range | Resolution | Accuracy ± ([% of reading] + [counts]) |
|---|-------------------|------------|--|
| DC millivolts | 600.0 mV | 0.1 mV | 0.5 % + 2 |
| DC volts | 6.000 V | 0.001 V | 0.5 % + 2 |
| | 60.00 V | 0.01 V | |
| | 600.0 V | 0.1 V | |
| Auto volts | 600.0 V | 0.1 V | 2.0 % + 3 (dc, 45 Hz to 500 Hz) 4.0 % + 3 (500 Hz to 1 kHz) |
| AC millivolts ¹ true-rms | 600.0 mV | 0.1 mV | 1.0 % + 3 (dc, 45 Hz to 500 Hz) 2.0 % + 3 (500 Hz to 1 kHz) |
| AC volts ¹ true-rms | 6.000 V | 0.001 V | 1.0 % + 3 (45 Hz to 500 Hz) 2.0 % + 3 (500 Hz to 1 kHz) |
| | 60.00 V | 0.01 V | |
| | 600.0 V | 0.1 V | |
| Continuity | 600 Ω | 1 Ω | Beeper on < 20 Ω off > 250 Ω; detects opens or shorts of 500 μs or longer. |
| Ohms | 600.0 Ω | 0.1 Ω | 0.9 % + 2 |
| | 6.000 kΩ | 0.001 kΩ | |
| | 60.00 kΩ | 0.01 kΩ | |
| | 600.0 kΩ | 0.1 kΩ | |
| | 6.000 MΩ | 0.001 MΩ | |
| Ohms | 40.00 MΩ | 0.01 MΩ | 1.5 % + 2 |
| | | | |
| Diode test | 2.000 V | 0.001 V | 0.9 % + 2 |
| Capacitance | 1000 nF | 1 nF | 1.9 % + 2 |
| | 10.00 μF | 0.01 μF | |
| | 100.0 μF | 0.1 μF | |
| | 9999 μF | 1 μF | |
| | 100 μF to 1000 μF | | |
| Capacitance | > 1000 μF | | 5 % + 20 |
| Lo-Z capacitance | 1 nF to 500 μF | | 10 % + 2 typical |
| Temperature ² (Type-K thermocouple) | -40 °C to 400 °C | 0.1 °C | 1 % + 10 ² |
| | -40 °F to 752 °F | 0.2 °F | 1 % + 18 ² |
| AC μamps true-rms (45 Hz to 500 Hz) | 600.0 μA | 0.1 μA | 1.5 % + 3 (2.5 % + 3 > 500 Hz) |
| DC μamps | 600.0 μA | 0.1 μA | 1.0 % + 2 |
| Hz (V or A input) ³ | 99.99 Hz | 0.01 Hz | 0.1 % + 2 |
| | 999.9 Hz | 0.1 Hz | |
| | 9.999 kHz | 0.001 kHz | |
| | 50.00 kHz | 0.01 kHz | |

Notes:

¹ All ac voltage ranges except Auto-V/LoZ are specified from 1 % to 100 % of range. Auto-V/LoZ is specified from 0.0 V. Because inputs below 1 % of range are not specified, it is normal for this and other true-rms meters to display non-zero readings when the test leads are disconnected from a circuit or are shorted together. For volts, crest factor of ≤ 3 at 4000 counts, decreasing linearly to 1.5 at full scale. AC volts is ac-coupled. Auto-V LoZ, and ac mV are dc-coupled.

² Temperature uncertainty (accuracy) does not include the error of the thermocouple probe.

³ Frequency is ac coupled, 5 Hz to 50 kHz for ac voltage. Frequency is dc coupled, 45 Hz to 5 kHz for ac current.

Ordering information

Fluke-116 HVAC Multimeter with Temperature and Microamps

Included

TL75 Test Leads, 80BK Integrated Temperature Probe, holster, User's manual and 9 V battery (installed).



Fluke. Keeping your world up and running.™

Fluke Corporation

PO Box 9090, Everett, WA USA 98206

Fluke Europe B.V.

PO Box 1186, 5602 BD Eindhoven, The Netherlands

For more information call:

In the U.S.A. (800) 443-5853 or Fax (425) 446-5116

In Europe/M-East/Africa (31 40) 2 675 200 or Fax (31 40) 2 675 222

In Canada (800)-36-FLUKE or Fax (905) 890-6866

From other countries +1 (425) 446-5500 or Fax +1 (425) 446-5116

Web access: <http://www.fluke.com>

©2006 Fluke Corporation. All rights reserved. Specifications subject to change without notice. Printed in U.S.A. 8/2006 2634037 D-EN-N Rev B