

speakON® Series



FC Cable Connector

Chassis Connector

SPX Cable Connector

STX Cable Connector

STX Chassis Connector

Adapter

Specification		speakON FC Cable Con.	speakON Chassis + Combo	SPX Series Cable Con.	STX Series Cable Con.	STX Series Chassis	Adapter
Number of contacts		4 + 8	2, 4, 8	2, 4	4 + 8	4 + 8	4/2, 8
Rated current per contact	30 A	●	●	-	-	-	-
	40 A rms continuous	-	-	●	●	●	15 A
CSA approved rating	25 A (4 pole) rms continuous	-	10 A	●	●	-	-
	50 A audiosignal, duty cycle 50%	40 A	40 A	●	●	●	30 A
Combo	15 A rms continuous	-	●	-	-	-	-
Rated voltage	250 V ac	●	●	●	●	●	●
Termination	PCB	-	●	-	-	●	-
	FASTON® - Solder	-	●	-	-	●	-
	Screw Terminals	●	●	●	-	-	-
	Solder Terminals	●	●	●	●	●	-
Mounting	Thru holes	-	●	-	-	●	-
	Self tapping screw holes (A screw)	-	●	-	-	●	-
	Metal M3 thread	-	●	-	-	-	-
Shell	Plastic	●	●	●	-	-	●
	Metal	-	-	-	●	●	●

speakON Series 2019/07 V02 – Data subject to change without prior notice. © 2019 NEUTRIK®. NEUTRIK®, speakON® are registered trademarks of NEUTRIK AG. ALL RIGHTS RESERVED.

