



Pass & Seymour


Hospital Grade Devices GFCIs 15 & 20A, 125VAC

1595-HG, 2095-HG, 1595-HGNTL, 2095-HGNTL, 1595-HGTR, 2095-HGTR, 1595-HGL, 2095-HGL

Hospital Grade GFCIs offer superior durability and protection.

They include the same features and benefits as our Specification Grade GFCIs including our patented SafeLock™ protection. P&S has the broadest range of ground-fault protection with the first LED Nightlight/GFCI Combination, the first Tamper-Resistant GFCI, and an Illuminated version — all offered with the Hospital Grade rating.

For non-Hospital Grade, refer to GFCIs tab section, SF1101R4.



Features & Benefits

SafeLock™ Protection denies power if the GFCI is miswired or if the GFCI is damaged and protection is lost. This prevents the unsafe condition of power without protection.

Nickel post-plated mounting strap for superior corrosion resistance.

Trip indicator light (red lamp) makes it easy to identify tripped condition.

Side or internal screw-pressure-plate back wire termination with #14 – #10 AWG stranded or solid, copper or copper-clad conductors.

Captive screws make for easier installation.

Meets 2006 UL requirements.

Back wire clamp allows for fast installation of ground wires.


Two back wire holes per termination add wiring flexibility, eliminate pigtail and save box space.

Prevents line-load reversal miswire: No power to the face or downstream receptacles if wired incorrectly.

High-impact-resistant, thermoplastic construction for superior strength and durability.

1/4" thinner than competitors' GFCIs; leaves more room for wires in the box.

The most durable GFCI available. Exceeds UL943 voltage surge requirements; survives 100x the required UL 3kA/6kV voltage surge test cycles.



2095-HGLA

Field Uses/Vertical Markets

- Health Care
- Education
- Institutional

Hospital Grade Devices GFCIs 15 & 20A, 125VAC

Ordering Information

Additional Features & Benefits	Catalog Number	Rating A.	VAC	Color	NEMA Config. No.
Hospital Grade GFCI Receptacles					
 Patented SafeLock™ Protection is standard on all P&S Hospital Grade GFCIs.	1595-HG*	15	125	I, W, Brown, GRY, RED, LA	5-15R
	2095-HG*	20	125	I, W, Brown, GRY, RED, LA	5-20R
Hospital Grade Combination Nightlight/GFCI Receptacles					
 High impact-resistant lens made of Lexan®. Energy-efficient LED has average 20-year life expectancy, eliminating bulb replacement. Photocell turns nightlight ON in dark, OFF in daylight.	1595-HGNTL*	15	125	I, W, Brown, GRY, RED, LA	5-15R
	2095-HGNTL*	20	125	I, W, Brown, GRY, RED, LA	5-20R
Hospital Grade Tamper-Resistant GFCI Receptacles					
 Dual mechanical shutter system to help prevent insertion of foreign objects. Patented UL Listed shutter system.	1595-HGTR*	15	125	I, W, Brown, GRY, RED, LA	5-15R
	2095-HGTR*	20	125	I, W, Brown, GRY, RED, LA	5-20R
Hospital Grade Illuminated GFCI Receptacles					
 Green indicator light ON when power is available. LED turns OFF when unit has tripped or power has failed.	1595-HG*L	15	125	I, W, Brown, GRY, RED, LA	5-15R
	2095-HG*L	20	125	I, W, Brown, GRY, RED, LA	5-20R



*Color Designation

I Ivory - Brown RED Red
W White GRY Gray LA Light Almond

For more information on these and other P&S products refer to our Catalog or visit our web site.

Hospital Grade Devices GFCIs 15 & 20A, 125VAC



Pass & Seymour

Technical Specifications

3rd Party Compliance

cULus Listed File Number E42190, Standard UL498 Attachment Plugs and Receptacles, UL943 GFCIs. Federal Specification WC596, Hospital Grade. Standard CSA C22.2 No. 42 General Use Receptacles, CSA C22.2 No. 144 GFCIs. Conforms to NEMA WD-1 and WD-6.

Performance

Electrical

Dielectric Voltage	Withstands 1500V minimum
Trip Level	4 to 6 mA
Trip Time	.025 Second Nominal
Frequency	60 Hz
Maximum Working Voltage	125VAC
Voltage Range	102-132VAC

Mechanical

Terminal Identification	Terminals identified in accordance with UL498 (Hot, White, Green)
Terminal Accommodation	#14 AWG – #10 AWG solid or stranded copper conductor only
Product Identification	Ratings are a permanent part of device

Environmental

Operating Temperature	-35°C to +66°C
Maximum Humidity	95%
Flammability	UL94 V2

Materials


Face	Nylon	Hex Head Grounding Screw	Steel (Green)
Body	Nylon	Flat Head Mounting Screws	Zinc-Plated Steel
Contacts	.03" Brass (.8)	Test/Reset Buttons	Nylon
Mounting Straps	.05" Nickel-Plated Steel (1.3)	Nightlight Lens	* Lexan®
Terminal Screws	Nickel-Plated Steel #8 - 32	Tamper-Resistant Shutter	** Thermoplastic

* For 1595-HGNTL and 2095-HGNTL Nightlight versions only.

** For 1595-HGTR and 2095-HGTR Tamper-Resistant versions only.

Warranty

1 Year



Dimensions for
15 & 20 Amp



Nightlight/GFCI



Tamper-Resistant




Illuminated

Complimentary Devices & Accessories




HOSPITAL GRADE DEVICES

- Receptacles, Tamper-Resistant, Decorator
- GFCIs
- TVSS
- Isolated Ground
- Plugs & Connectors




GFCIs

- Specification Grade
- Hospital Grade
- Dead Front




DECORATOR DEVICES

- Construction Grade Switches
- Specification Grade Combo Switches
- Construction Grade Receptacles
- Commercial Grade Receptacles
- Specification Grade Hallway Lights



STRAIGHT BLADE RECEPTACLES

- Extra Heavy-Duty
- Heavy-Duty
- Construction Grade
- Construction Grade Leaded
- Commercial Grade



SWITCHES

- Heavy-Duty Toggle
- Heavy-Duty Lighted Toggle
- Heavy-Duty Security
- Heavy-Duty Locking
- Construction Grade Toggle
- Commercial Grade Toggle



WALL PLATES

- TradeMaster® Thermoplastic Nylon
- Screwless Polycarbonate
- Stainless Steel
- Brass
- Aluminum
- Dustproof Stainless Steel Covers

Also available...

- Light Almond Devices
- PlugTail™ Devices
- TVSS & Isolated Ground Devices
- Ground Continuity Monitoring (GCM)
- Straight Blade Plugs & Connectors
- Turnlok® Locking Devices
- Weatherproof Boxes & Covers
- IEC 309 Industrial Products
- Flexcor® Wire Mesh Grips
- Configurable Solutions



Legrand/Pass & Seymour
P.O. Box 4822
Syracuse, NY 13221-4822
800-223-4185

North America Headquarters
60 Woodlawn Street
West Hartford, CT 06110
Phone: 1.877.BY.LEGRAND (295.3472)
Fax: 1.860.232.2062
www.legrand.us

Legrand Canada
570 Applewood Crescent
Vaughan, ON, L4K 4B4
Phone: 905.738.9195
Fax: 905.738.9721
www.legrand.ca