THE NEXT GENERATION IN ACCESS HARDWARE

BlueDiamond™ Multi-Technology Readers

The Honeywell BlueDiamond platform offers a complete, next-generation access control experience. With multi-technology readers, a feature-rich mobile app and the ability to support mobile and physical credentials, organizations can upgrade to the BlueDiamond experience at their own pace.

BlueDiamond multi-technology readers are among the most versatile access control readers on the market. They work seamlessly with existing infrastructures and leverage open credentialing standards. The readers comply with ISO 14443 Type A standards, and are access control platform agnostic. BlueDiamond readers support standard output protocols including Wiegand, OSDP, OSDPv2, and Supervised F/2F (SF/2F).

Capable of supporting a wide range of smart cards – including HID* iCLASS*, MIFARE* and DESFire® EV1, EV2, and EV3 – and proximity cards means BlueDiamond multitech readers provide a seamless migration path from less secure card technologies to a more secure, open standard with DESFire EV1, EV2, and EV3 card technology and offer a pathway to mobile keys with BlueDiamond mobile credentials.

With a cybersecurity mindset and privacy-by-design development strategy, Honeywell is providing one of the most customer-centric reader solutions on the market.







Honeywell BlueDiamond Multi-Technology Readers

FEATURES & BENEFITS



Multi-tech readers offer simultaneous support for:

- 125 kHz proximity cards
 - HID Proximity
 - AWID® Proximity
 - CASI/GE Security ProxLite
- 13.56 MHz smart cards
 - MIFARE DESFire EV1/EV2/EV3
 - MIFARE Classic ISO 14443, or secure sector data
 - Vicinity Card Serial Number ISO 15693
 - HID iCLASS**
- Support for key diversification based on NXP standard
- Support for NFC wallet-based credentials

Slim profile with fingerprintresistant black textured finish

Support for Honeywell

NFC credentials

BlueDiamond Bluetooth® and



Readers are mobile-enabled and ready for use with BlueDiamond Bluetooth credentials - no need to add or replace hardware.*



Firmware updates, custom key loading and configuration changes



Wiegand, OSDP or SF/2F with Optical tamper switch or without secure channel encryption auto-configuring with Honeywell access panels





* Future release

** Support for HID iCLASS Classic or Standard, not Elite Key, SE or SEOS.

SPECIFICATIONS

TABLE 1. PRODUCT SPECIFICATIONS HON-R11325-05TB HON-R11330-05TB HON-R11320-05TB Multi-Technology Multi-Technology Multi-Technology Mini-Mullion Reader Standard Size Reader Standard Size Reader with Keypad Mechanical 96 mm × 52 mm × 21 mm 120 mm × 76 mm × 21 mm **Dimensions** $[3.8 \text{ in} \times 2.1 \text{ in} \times 0.8 \text{ in}]$ $[4.2 \text{ in} \times 3.0 \text{ in} \times 0.8 \text{ in}]$ Housing Molded polycarbonate/ABS **Finish** Black, textured, fingerprint resistant Mounting Wall surface or standard US, UK, or EU switchbox **Environmental** Operating temperature -35 °C to 65 °C [-31 °F to 149 °F] Relative humidity 0 % to 100 % relative humidity, non-condensing **IP65** Ingress protection rating **Network Accessories** Voltage 10 Vdc to 16 Vdc Average current draw at 35 mA 35 mA 67 mA 12 Vdc Peak current draw at 67 mA 73 mA 105 mA 12 Vdc Data voltage Rest > 4 Vdc / Active < 1 Vdc Reader interface Wiegand, OSDP, Supervised F/2F (SF/2F)*** 1 RGB LED Indication 1 RGB LED + illuminated keypad Sounder Integral speaker Read Range Up to 10 cm [4 in] for RFID cards, up to 9 m [30 ft] for Bluetooth Warranty Warranty 5-year limited warranty Certifications FCC Part 15 | UL294 | CE Marked | RoHS | WEEE Certifications Contact Your Honeywell representative for certification documents

^{***}Support for Supervised F/2F protocol on a BlueDiamond reader is indicated by a label visible on the physical reader.

ORDERING INFORMATION

TABLE 2. ORDERING INFORMATION	
Mobile-Enabled Readers	
HON-R11330-05TB	BlueDiamond multi-technology reader, mini-mullion size single gang, DESfire, prox, terminal block wiring
HON-R11320-05TB	BlueDiamond multi-technology reader, standard size single gang, DESfire, prox, terminal block wiring
HON-R11325-05TB	BlueDiamond multi-technology reader, standard size single gang, keypad, DESfire, prox, terminal block wiring
Pre-Encoded Credentials	
HON-EV28KPP	DESFire EV2 ISO composite 8K 13.56 MHz
HON-EV28KPXPP	DESFire EV2 ISO composite 8K with proximity chip
Licenses	
BDM-CRD	Per mobile credential per user fee
BDM-RDR	Per reader fee for unlimited credentials. Applies to every reader used for use with mobile credentials only
BDM-IOSBUNDLE	One-time setup fee for NFC Wallet-based credentials
BDM-IOSUSER	New "adds to wallet" or activation of NFC credential

One NFC user has two credentials (based on PACS).

The Honeywell BlueDiamond mobile app is available for iOS® and Android® devices, as well as the Apple Watch®.

For Android™-compatible options, please contact your authorized Honeywell agent.

One Phone credential and one Watch credential = One pass for one NFC user.

Android is a trademark or registered trademark of Google LLC in the United States and other countries.

 $\ensuremath{\mathsf{IOS}}$ is a trademark or registered trademark of Cisco in the United States and other countries.

Apple, Apple Watch, and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries and regions.

Bluetooth is a trademark or registered trademark of the Bluetooth Special Interest Group (SIG) in the United States and other countries.

AWID is a trademark of Applied Wireless Identification Group.

OSDP is a trademark of Security Industry Association.

OSDP is a trademark of Security Industry Association.

MIFARE, DESFIRE is a trademark of NXP B.V.

 \mbox{HID} and iCLASS are trademarks or registered trademarks of \mbox{HID} Global Corporation, part of ASSA ABLOY

BlueDiamond is a trademark of Honeywell International Inc. in the United States and other countries.

Honeywell reserves the right, without notification, to make changes in product design or specifications.

 $\label{eq:hbt-sec-bldmdrdr-ds-us-en-082024-Rev01} \end{center} \begin{tabular}{ll} \$

For More Information

buildings.honeywell.com/security

Honeywell Building Automation

Commercial Security 715 Peachtree St. NE Atlanta, GA 30308 1.800.323.4576 www.honeywell.com



