

Low Profile IN-AND-OUT™ Covers for New or Existing Construction

Low profile when not in use and a deeper, weatherproof-in-use extra-duty cover when cord is plugged in. Non-metallic cover and base. Comes in clear or textured/ paintable white. UV rated plastic for long outdoor life.

FEATURES AND BENEFITS

- Low profile when not in use—weatherproof-while-in-use
- IN position provides a sealed box to keep bugs out
- Extends quickly and easily into the OUT position to accommodate a plug
- Fits over all boxes or openings in new or existing projects
- The 61 Series has an installed, oversized base for large openings or a 3.5" round outlet box
- Installed gaskets
- Install option: Cover is removable for easier device installation
- Vertical and horizontal styles

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | ORIENTATION/COVER COLOR | UNIT PKG | STD PKG | DIM A | DIM B | DIM C IN | DIM C OUT | DIM D | DIM E |
|----------------|--------------------------|-------------------------|----------|---------|-------|-------|----------|-----------|-------|-------|
| 60VC | 00682 | Vertical/Clear | 1 | 4 | 6.274 | 3.752 | 1.670 | 3.005 | - | - |
| 60VW | 00680 | Vertical/White | 1 | 4 | 6.274 | 3.752 | 1.670 | 3.005 | - | - |
| 61VC | 00683 | Vertical/Clear | 1 | 4 | 6.274 | 3.752 | 1.670 | 3.005 | 5.561 | 4.250 |
| 61VW | 00681 | Vertical/White | 1 | 4 | 6.274 | 3.752 | 1.670 | 3.005 | 5.561 | 4.250 |
| 60HC | 00686 | Horizontal/Clear | 1 | 4 | 4.192 | 5.836 | 1.670 | 3.005 | - | - |
| 60HW | 00684 | Horizontal/white | 1 | 4 | 4.192 | 5.836 | 1.670 | 3.005 | - | - |
| 61HC | 00687 | Horizontal/Clear | 1 | 4 | 4.192 | 5.836 | 1.670 | 3.005 | 3.500 | 5.561 |
| 61HW | 00685 | Horizontal/white | 1 | 4 | 4.192 | 5.836 | 1.670 | 3.005 | 3.500 | 5.561 |




Note: Meets 2015 CEC (Rule 26-702), NEMA 3R, 2017 NEC 406.9 (b); Where a weatherproof-in-use cover is required for 15 or 20 AMP receptacles installed outdoors. **PATENTED. ADDITIONAL PATENTS PENDING.**


**WEATHERPROOF-IN-USE
EXTRA-DUTY**



60VC



60V



61V

61 Series base shown separately for dimensional purposes only.

INSTALLATION INSTRUCTIONS



1 Feed device through opening (cover is removable for easier access).



2 Install wiring device per manufacturer's instructions, Local and National Electrical Codes using the pre-drilled holes in base.



3 Install plate and the installation is done!



60VW

IN for **GOOD LOOKS** and to stay bug free...



61HW

OUT to **PLUG IN** for weatherproof-in-use!



To close: Bow out sides of extended cover and push in.

IN-AND-OUT™ Cover includes...

Low profile cover, (1) standard duplex and (1) standard GFCI face plate, installation screws, and installed gaskets.

Scan For Video

