Nail On Fan & Fixture Boxes with Steel Mounting Bracket

Plastic box with steel mounting bracket for fast and easy nail on installation to a single or double joist.

FEATURES AND BENEFITS

- No loose parts to misplace–totally self-contained!
- FB417S features convenient indicator marks for 1/2", 5/8", and 3/4" ceiling thicknesses
- Works well on single or double wood joists
- Fan/fixture installation screws are parked…ready for easy fan/fixture bracket installation!
- FB417SLP also works with wood and manufactured I-beams
- UL rated: 70 lb fan/fixture; CSA rated: 50 lb fan/fixture
- 2-Hour Fire Rating

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	DESCRIPTION / CU. IN.	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
FB417S	72171	For up to 1-1/2" ceiling thickness (Including drywall on furring strips or hat channel) 20.0 cu. in.	25	25	4.563	3.500	4.279
FB417SLP	72199	For 1/2" to 5/8" ceiling thicknesses only 20.0 cu. in.	25	25	6.625	2.906	4.570

Refer to chart on page R-24 for load ratings and number of single conductors.

PATENTED.

E170558



FB417S FB417SLP

FB417S

FB417SLP
Low Profile

EACH FAN/FIXTURE BOX INCLUDES…

Plastic box with steel mounting bracket, installed NM cable connector, mud cover, second KO, two parked-in-place bracket nails, and two fan/fixture bracket installation screws (screwed in place until removed by installer).

INSTALLATION INSTRUCTIONS



Saves Time!

Nails to the Joist for a Super Secure Installation!

All photos shown with FB417S

Note: Install fan or fixture (not included) in accordance with manufacturer's instructions and all local applicable electrical codes, using the parked screws provided.