

Fan & Fixture Mounting Boxes with Installed Steel Bracket

FBB450







FBB900

EACH FAN/FIXTURE BOX INCLUDES...

Mounting block with installed steel bracket, installed NM cable connector, four captive fan/fixture #10, 1-1/2" installation screws, ready to tighten.



NO need to a 2x8 or extra trimming! Notch the box as necessary, keeping bottom of box level, with short side of box touching rafter. Screw the bracket to the rafter with (4) supplied #10 1-1/2" wood screws through the pre-drilled screw holes in bracket.



NO need for a 2x4! Mount steel bracket to angled rafters with short sides of box touching each rafter. Keep bottom of box level. Screw the bracket to the rafters with (4) supplied #10 1-1/2" wood screws through the pre-drilled screw holes in bracket.




Push cable through installed NM cable connector in box.






Note: Install fan or fixture (not included) in accordance with manufacturer's instructions and all local applicable electrical codes, using the parked screws provided.



FEATURES AND BENEFITS

- Easy, secure installation
- No loose parts-Captive fan/fixture bracket installation screw.
- Installed NM cable connector AND steel mounting bracket
- 14.5 cu. in. box with 8" square mounting surface handles large fan canopies
- Paintable/ textured finish
- UL ratings: 70 lb fan, 200 lb fixture
- CSA rating: 50 lb fan or fixture

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	DESCRIPTION / CU. IN.	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	DIM D
FBB450	11230	Fits sloped ceilings up to 45° Installed 16″ steel mounting bracket /14.5 cu. in.	1	1	8.000	8.000	9.729	3.875
FBB900	11231	Fits Cathedral Ceilings 80° or greater/Installed 12" steel mounting bracket /14.5 cu. in.	1	1	8.000	8.000	6.364	3.875
							LR49636	
D	B							



INSTALLATION INSTRUCTIONS



Push cable through Install drywall ceiling. installed NM cable connector in box.



Installing fan bracket on installed box on sloped ceiling.