





# Wire Basket Tray System

## Round Cross-Wire Basket Tray



### Features

- T-weld construction prevents snags
- 5mm round wire minimum
- High load rating
- Easy to cut and fabricate fittings in the field
- 100% recycled steel
- 2" x 4" mesh opening
- Use factory support hardware or fabricate supports at the job site
- Painted tray includes factory installed masking to ensure proper grounding at splices; no need to remove paint during installation

10 Feet per Length 118.3" (3m) 10 pc. min. order qty. 2" Deep Tray	Tray Width	Load (Lb/ft)	Tray Weight per Length (Lb)	Splice Quantity*		Finish	
				90° Sweep Elbow	Straight Splice	Pre-Galvanized	Black Powder Coat
	4" (102)	45	7	2	2	<b>HBT0204</b>	<b>HBT0204BK</b>
	6" (152) ●	50	9	3	4	<b>HBT0206</b>	<b>HBT0206BK</b>
	8" (203) ●	52	10.5	4	4	<b>HBT0208</b>	<b>HBT0208BK</b>
	12" (305) ●	58	12	6	4	<b>HBT0212</b>	<b>HBT0212BK</b>
	16" (406) ●	70	15	7	4	<b>HBT0216</b>	<b>HBT0216BK</b>
	18" (457) ●	70	23	9	4	<b>HBT0218</b>	<b>HBT0218BK</b>
	20" (508) ●	73	25	9	5	<b>HBT0220</b>	<b>HBT0220BK</b>
	22" (559)	73	27	12	5	<b>HBT0222</b>	<b>HBT0222BK</b>
	24" (610) ●	75	31	12	5	<b>HBT0224</b>	<b>HBT0224BK</b>
	26" (660)	73	33	13	6	<b>HBT0226</b>	<b>HBT0226BK</b>
	28" (711)	73	35	14	6	<b>HBT0228</b>	<b>HBT0228BK</b>
	30" (762)	70	38	15	6	<b>HBT0230</b>	<b>HBT0230BK</b>
32" (813)	70	39	16	6	<b>HBT0232</b>	<b>HBT0232BK</b>	
	4" (102)	49	12	2	4	<b>HBT0404</b>	<b>HBT0404BK</b>
	6" (152) ●	49	13	3	5	<b>HBT0406</b>	<b>HBT0406BK</b>
	8" (203) ●	78	15	4	6	<b>HBT0408</b>	<b>HBT0408BK</b>
	12" (305) ●	78	23	6	6	<b>HBT0412</b>	<b>HBT0412BK</b>
	16" (406) ●	108	27	7	7	<b>HBT0416</b>	<b>HBT0416BK</b>
	18" (457) ●	116	29	9	7	<b>HBT0418</b>	<b>HBT0418BK</b>
	20" (508) ●	116	31	9	7	<b>HBT0420</b>	<b>HBT0420BK</b>
	22" (559)	116	33	12	8	<b>HBT0422</b>	<b>HBT0422BK</b>
	24" (610) ●	116	35	12	8	<b>HBT0424</b>	<b>HBT0424BK</b>
	28" (711)	108	39	14	9	<b>HBT0428</b>	<b>HBT0428BK</b>
	8" (203) ●	116	23	4	6	<b>HBT0608</b>	<b>HBT0608BK</b>
	12" (305) ●	123	27	6	6	<b>HBT0612</b>	<b>HBT0612BK</b>
	16" (406) ●	123	31	7	7	<b>HBT0616</b>	<b>HBT0616BK</b>
	18" (457) ●	127	33	9	7	<b>HBT0618</b>	<b>HBT0618BK</b>
	20" (508) ●	127	35	9	7	<b>HBT0620</b>	<b>HBT0620BK</b>
	22" (559) ●	127	37	12	8	<b>HBT0622</b>	<b>HBT0622BK</b>
	24" (610) ●	150	39	12	8	<b>HBT0624</b>	<b>HBT0624BK</b>
	8" (203) ●	116	27	4	8	<b>HBT0808</b>	<b>HBT0808BK</b>
	12" (305) ●	116	31	6	8	<b>HBT0812</b>	<b>HBT0812BK</b>
	16" (406) ●	116	35	7	9	<b>HBT0816</b>	<b>HBT0816BK</b>
	18" (457) ●	116	37	9	9	<b>HBT0818</b>	<b>HBT0818BK</b>
	20" (508) ●	116	39	9	9	<b>HBT0820</b>	<b>HBT0820BK</b>

### Field Configurable Fittings




**90° Sweep Elbow**  
Use appropriate quantity of splice kits




**Tee Fitting**  
Use one HBTC5 corner splice per each

### Supports and Hardware



**Ordering Information**  
See page U-12

### Wire Diameter



.1969" Dia.  
"Round" Wire Design

Note: ●UL Classified as equipment ground conductor (painted tray cUL Classified only).  
All dimensions are +/- 0.25". Custom paint colors available in addition to Black Powder Coat (Contact Hubbell).  
\*See page U-13 for details and page U-14 for wire fill and maximum load chart.  
HBT0202 (2x2 tray) available as special order. MOQ 40 pcs. Top wire utilizes side weld.

Dimensions in Inches (mm)