

BNC CONNECTORS COMPRESSION PLUGS



ADI PRO BNC Compression Plugs are designed to facilitate quick, secure termination of coaxial cables while maintaining optimal signal quality. Ideal for HD digital or analog audio and video installations.



FEATURES

Indoor, commercial and residential applications

Terminate raw coaxial cable quickly and securely

Corrosion resistant, with nickel-plated body and gold-plated contact

0E-BNCCOMH75 and 0E-BNCCMH75C boast an improved design for an even tighter connection

Limited Lifetime Warranty

RECOMMENDED TOOLS



0E-BNCCMPTL
Universal Compression Tool
BNC, F and RC



0E-BNCCRTOOL
Universal Crimp Tool
BNC, F, N, TNC, UHFST, SC

Product Specifications

PART #	Cable Type	Imp.	Qty.
0E-BNCCOMPTP	RG59 (PVC) 18-22 AWG	50Ω	10-pk
0E-BNCCOM75T	RG59, RG6 (PVC)	75Ω	10-pk
0E-BNCCOM75C	RG59, RG6 (PVC)	75Ω	100 (jar)
0E-BNCCOMH75	RG59 (PVC) 20 AWG	75Ω	10-pk
0E-BNCCMH75C	RG59 (PVC) 20 AWG	75Ω	100 (jar)











Materials: Nickel-plated zinc (body); Gold-plated brass (contact)



For more information, contact
your ADI salesperson or visit
adiglobal.com/adiexclusivebrands

BNC CONNECTORS

COMPRESSION PLUGS

BNC CONNECTOR	CABLE TYPE	IMPEDANCE	CABLE DIAMETER		FINISH	QTY.	PART #	
			DIELECTRIC	JACKET				
Twist-On Plug Male		RG58 (PVC) RG59 (Plenum) 20-22 AWG	50Ω	.116" - .146"	.195" - .242"	Nickel (body) Gold (contact)	10-pk	0E-BNC59PTOT
		RG59 (PVC) RG6 (Plenum) 18-22 AWG	50Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCT56PTP
		RG59 (PVC) RG6 (Plenum) 18-22 AWG	75Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCT5675T
Compression Plug Male		RG59 (PVC) 18-22 AWG	50Ω	.146"	.242"	Nickel (body) Gold (contact)	10-pk	0E-BNCCOMPTP
		RG59, RG6 (PVC)	75Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCCOM75T
		RG59 (PVC) 20 AWG	75Ω	.146"	.242"	Nickel (body) Gold (contact)	10-pk	0E-BNCCOMH75
							100 (jar)	0E-BNCCMH75C
Crimp Plug Male		RG59, RG6 (PVC)	50Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNC2UTP
		RG58 (PVC) RG59, RG6 (PVC or Plenum)	50Ω	.116" - .146" - .185"	.195" - .242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCCRIMPT
							100 (jar)	0E-BNCCRIMPC
		RG58 (PVC) RG59, RG6 (PVC or Plenum)	75Ω	.116" - 0.146" - .185"	.195" - .242" - 0.275"	Nickel (body) Gold (contact)	10-pk	0E-BNCCR75TP
							100 (jar)	0E-BNCCRI75C
						10-pk	0E-BNCU75TP	
T-Connector Male/2x Female		--	50Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCM22FTP
Coupler Female/Female		--	50Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCFFTP
		--	75Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCF75TP
Adapter BNC Plug/F Jack		--	--	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCM2FFTP
Adapter BNC Jack/RCA Plug		--	--	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCFRCAMT

For more information, contact
your ADI salesperson or visit
adiglobal.com/adiexclusivebrands

ADI
PRO