

2205 series overhead door contacts

floor mount magnetic contacts for overhead doors

The 2205 series overhead door magnetic contact is designed for use in environments where a heavy-duty unit is required. The floor mount units are constructed using a rugged low-profile extruded aluminum switch housing and a cast aluminum magnet housing. The reed switch assembly is fully encased in GE Security's exclusive polyurethane potting material to prevent damage due to moisture or humidity.

A wide operating gap of up to 3 inches makes installation easy and helps prevent false alarms caused by loose-fitting doors. The contacts are available with a universal-style magnet that allows for greater installation flexibility.

Specifications

Voltage:	2205: 100 VAC/VDC max. 2207: 30 VAC/VDC max.
Current:	2205: 0.5 A max. 2207: 0.25 A max.
Power:	2205: 7.5 W max. 2207: 3.0 W max.
Loop type:	2205: Closed 2207: Open or Closed
Electrical configuration:	2205: Normally open 2207: SPDT (2207AD: DPDT)
Gap distance:	Up to 3 in. 2207AH: 3/4 to 2-1/2 in.
Dimensions:	2205/2207: 3.50 x 1.50 x 1.50 in. (89 x 38 x 38 mm) 2205AU/2207AU: 3.50 x 1.50 x 2.125 in. (89 x 38 x 54 mm) 2207AH: 3.50 x 1.50 x 1.0 in. (89 x 38 x 25 mm)
Housing:	Bar Stock aluminum
Color:	Anodized aluminum
Regulatory:	UL, CUL (2207AH: UL only)

Ordering information

2205A-L	Overhead door floor mount extra heavy duty magnetic contact with aluminum housing, closed loop, wide gap, 3 in. gap size, 3 ft. stainless steel armored cable
2205AU-L	Overhead door floor mount extra heavy duty magnetic contact with aluminum housing, universal magnet, closed loop, wide gap, 3 in. gap size, 3 ft. stainless steel armored cable
2207A-L	Overhead door floor mount extra heavy duty magnetic contact with aluminum housing, SPDT, wide gap, 3 in. gap size, 3 ft. stainless steel armored cable
2207AU-L	Overhead door floor mount extra heavy duty magnetic contact with aluminum housing, universal magnet, SPDT, wide gap, 3 in. gap size, 3 ft. stainless steel armored cable
2207AD-L	Overhead door floor mount extra heavy duty magnetic contact with aluminum housing, DPDT, wide gap, 3 in. gap size, 3 ft. stainless steel armored cable
2207AH-L	Overhead door floor mount higher security magnetic contact with aluminum housing, biased for higher security, SPDT, 3/4 to 2-1/2 in. gap size, 3 ft. stainless steel armored cable



- Miniature, low-profile design
- Stainless steel armored cable for added security and reliability
- Wide operating gap for overhead doors
- Model available for high-security applications
- Fully sealed switch
- Mounting hardware included

