Eaton EMA112-10

Catalog Number: EMA112-10

Eaton Managed PDU, 1PH, 0U, NEMA 5-15P input, 10 ft cord, 1.44kW, 12A, 120V, 16 Outlets (16) 5-15R

General specifications

Product Name	**Catalog Number**
Eaton managed PDU	EMA112-10
UPC	**Product Length/Depth**
743172078896	66.5 in
Product Height	**Product Width**
2.56 in	2.05 in
Product Weight	**Warranty**
13 lb	3 year
Compliances	**Certifications**
RoHS Compliant	UL Listed
TAA Compliant	

EAT·N

Powering Business Worldwide

Product specifications

Form factor

0U (Vertical)

Outlet control

Yes

Phase

Single-phase

Wattage

1.44 kW max

Amperage Rating

12A

Input voltage

120V

Input connection

5-15P

Outlets

(16) 5-15R

Cord length

10 ft

Frequency rating

50-60 Hz

Serial interface

RS-232

Operating Temperature

0° to 60°C (32° to 140°F)

Resources

Certification reports

Eaton ePDU certificate of volatility

Eaton RoHS Declaration of Conformity: ePDU G3

Drawings

Eaton ePDU Managed eMA112-10 technical drawing

Eaton Advanced Monitored and Managed ePDU visio stencil

Manuals and user guides

Eaton ePDU G3 replace and configure eNMC module

Eaton ePDU G3 operations manual

Eaton Double-wide G3 ePDU installation and connectivity quick start guide

Eaton ePDU G3 instruction set - system objects

Eaton ePDU G3 1U and 2U installation addendum

Service and troubleshooting

EMA112-10 eNMC replacement configuration file

Specifications and datasheets

Eaton Specification Sheet - EMA112-10