

USKPR

SLAVE KEYPAD WITH 26-BIT WIEGAND READER



- Satellite Keypad-Card Reader for all Quantum Series
- Up to 8-32 USKPR can be interfaced with the Quantum Series
- Single relay
- Audible tone and LED indicator for valid and invalid access
- Independent access
- 4-Digit access code and 26-BIT Wiegand Reader
- Brushed stainless steel, dark gray powder coated back box
- Tamper Proof Screws
- Indoor or outdoor

24 months warranty

TECHNICAL SPECIFICATION

POWER INPUT: 12VAC 40VA or 12VDC 2 Amps (12VAC is supplied by Pach & Company).
CURRENT CONSUMPTION: 50mA Idle, 475mA operation.
EMERGENCY BATTERY: 12VDC, 4Ahr rechargeable (customer supplied).
COMMUNICATION: RS-485 (maximum distance not to exceed 4000 ft, daisy chain connection).
OPERATING ENVIRONMENT: 10°F to 145°F. Relative Humidity 0% to 95%.

RELAY OUTPUT: From C Dry Contact 120VAC 10A/ 24VDC 10 A/ 250VAC 7A with 5 seconds output duration.
MOUNTING: Surface, Indoor or outdoor
CONSTRUCTION: 16 Gauge Cold Rolled Steel with Brushed Stainless Steel Faceplate.
DIMENSION:
 Main Unit: 6-1/8" (H) x 7-1/16" (W), 1-1/2" (D)
 Card Reader: 4-1/16"(H) x 1-7/8" (W) x 13/16" (D)
SHIPPING WEIGHT: 5 lbs.

ORDERING PART NUMBER

USKPR

OPTIONS AND ACCESSORIES

UIISO: ISO 26 bit wiegand card (credit Card Size)
UFOB: 26 bit wiegand keyfob
UCLAM: 26 bit wiegand card with punch hole for badge holder
USP1: AC and Telephone surge protector

UPM1S: 42" H Single arm pedestal
UPM6L: 64" H Single arm pedestal
UPM2: Double Vertical Arm pedestal
UPM5: Double Horizontal Arm pedestal
UPM12E: 12" Expansion Arm use for all UPMs