


24/4 CAT 5E CABLE OUTDOOR DIRECT BURIAL



SPEC SHEET



0E-CAT5DB1BK (1,000ft)

0E-CAT5DB5BK (500ft)

Physical Characteristics

Conductor: 24 AWG Solid Bare Copper

Insulation: PP (Polypropylene)

Conductor Color Code:

- Pair 1: Blue - White / Blue

- Pair 2: Orange - White / Orange

- Pair 3: Green - White / Green

- Pair 4: Brown - White / Brown

Rip Cord (Y/N): Yes

Fill Type: Gel

Jacket: LLDPE (Linear Low Density Polyethylene), Sunlight-Resistant

Jacket Legend:

ADI PRO PN XXXX 24/4 UTP CAT 5E OUTDOOR RATED DIR BUR ANSI/TIA

568.2-D SUN RES (ROHS) DDMMYY YYYYFT


Nominal Wall Thickness: 0.0295"

Nominal Cable Diameter: 0.220"

Temperature Range:

Installation: 0°C to + 75°C / Operating: -20°C to + 75°C

Operating Voltage: 300V



Applications

IEEE802.3: 1000BASE-T (Gigabit Ethernet), 100 BASE-TX, 10 BASE-T, 155Mp/s, 622Mp/s ATM, ANSI X3.263: 100Mb/s, 4/16 Mb/s Token Ring, Broadband and Baseband Analog Video



**For more information contact
your ADI sales person or visit
adiglobal.com/adiexclusivebrands**

24/4 CAT 5E CABLE OUTDOOR DIRECT BURIAL



Standard Compliance

- ANSI/TIA 568.2-D
- Sunlight Resistance - In compliance with UL444
- RoHS Compliant Directive

Certifications



Electrical Characteristics

Velocity of Propagation: 69% Nominal

DC Resistance	Resistance Unbalanced	Capacitance	Capacitance Unbalanced	Mutual Capacitance	Propagation Delay	Delay Skew
9.38 Ω / 100m Max. @ 20°C	5% Max. @ 20°C	5.6 nF / 100m Max. @ 20°C	330 pF / 100m Max. @ 20°C	5.6 nF / 100m Max. @ 20°C	570 ns / 100m Max. @ 20°C	45 ns / 100m Max. @ 20°C

Frequency (MHz)	Attenuation (dB/100m)	NEXT (dB/100m)	PSNEXT (dB/100m)	ACRF (dB/100m)	PSACRF (dB/100m)	RL (dB/100m)	Delay (dB/100m)
1	2.0	65.3	62.3	63.8	60.8	20.0	570
4	4.1	56.3	53.3	51.8	48.8	23.0	552
8	5.8	51.8	48.8	45.7	42.7	24.5	547
10	6.5	50.3	47.3	43.8	40.8	25.0	545
16	8.2	47.2	44.2	39.7	36.7	25.0	543
20	9.3	45.8	42.8	37.8	34.8	25.0	542
25	10.4	44.3	41.3	35.8	32.8	24.3	541
31.25	11.7	42.9	39.9	33.9	30.9	23.6	540
62.5	17.0	38.4	35.4	27.9	24.9	21.5	539
100	22.0	35.3	32.3	23.8	20.8	20.1	538
200	32.4	30.8	27.8	17.8	14.8	18.0	537
250	36.9	29.3	26.3	15.8	12.8	17.3	536
300	41.0	28.1	25.1	14.3	11.3	16.8	536
350	44.9	27.1	24.1	12.9	9.9	16.3	536

* Spec meets ANSI/TIA/EIA 568.2-D standard to 100MHz. Sweep Tested to 350MHz. All values are dB/100m (328 ft.). Table values above 100MHz are for reference only.



**For more information contact
your ADI sales person or visit
adiglobal.com/adiexclusivebrands**