



AU-004



Technical Specifications

Product Information	
Rated Impedance	8 ohm
PoE Standard	IEEE 802.3af
Max. Power Consumption	15W
Frequency Ranges	500-2KHZ +-10dB 400-12KHZ +-20dB
Max. Sound Pressure Level	96dB
Microphone	50Hz-20kHz at 1Pa, 50cm distance, SPL 115dB at 1kHz

Network	
SIP Support	RFC 3261
Interface	WAN: RJ-45x1, 10/100Mbps Fast Ethernet port
Supported Protocols	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Audio Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
Security	Password protection, IP address filtering, Digest authentication, firewall

VSS Integration	
Broadcasting	Supported
Automatic Trigger Audio Clips	Supported

VORTEX Integration	
Broadcasting	Supported
Automatic Trigger Audio Clips	Supported

General	
Casing	Metal
Power	PoE (Power over Ethernet, IEEE 802.3af) or DC 12-24V
Operating Temperature	-35°C ~ 60°C (-31°F ~ 140°F)
Dimensions	200 x 90 mm
Weight	1 kg
Certifications	CE, FCC, VCCI, BSMI